

# Datasheet

## Eve Double Plus

### Technical specification



**ALFEN**  
POWER TO ADAPT

### Product Variants

	Article no.
<i>EU generic variants</i>	
Eve Double Plus, 3 phase, 2x type 2 socket, 1 power supply cable	904463021
Eve Double Plus, 3 phase, 2x type 2 socket, 2 power supply cables	904463022
Eve Double Plus, 1 phase, 2x type 2 shutter socket, 1 power supply cable	904463013
Eve Double Plus, 3 phase, 2x type 2 shutter socket, 1 power supply cable	904463023
Eve Double Plus, 3 phase, 2x type 2 shutter socket, 2 power supply cables	904463024
Eve Double Plus, 3 phase, 2x fixed charging cable, 1 power supply cable	904463025
Eve Double Plus, 3 phase, 2x fixed charging cable, 2 power supply cables	904463026
<i>Eve Double Plus DE</i>	
Eve Double Plus DE, 3 phase, 2x type 2 socket, 1 power supply cable	904463121
Eve Double Plus DE, 3 phase, 2x type 2 socket, 2 power supply cables	904463122
Eve Double Plus DE, 3 phase, 2x type 2 socket, 1 power supply cable, SPD	904463141
Eve Double Plus DE, 3 phase, 2x type 2 socket, 2 power supply cables, SPD	904463142
Eve Double Plus DE, 3 phase, 2x fixed charging cable, 1 power supply cable	904463125
Eve Double Plus DE, 3 phase, 2x fixed charging cable, 2 power supply cables	904463126
Eve Double Plus DE, 3 phase, 2x fixed charging cable, 1 power supply cable, SPD	904463145
Eve Double Plus DE, 3 phase, 2x fixed charging cable, 2 power supply cables, SPD	904463146

### Technical Specifications

Number of sockets	2
Types of sockets	<ul style="list-style-type: none"><li>Type 2 sockets, in accordance with IEC 62196-2</li><li>Type 2 shutter sockets, in accordance with IEC 62196-2</li><li>Fixed charging cables, with plug in accordance with IEC 62196-2 (charging cable holders integrated in product)</li></ul>
Nominal output voltage (+/- 10%)	400 V (3x230 V)
Maximum current	32 A per phase *
Maximum power	22 kW
Permissible cos phi	0.9-1
Earthing systems	TN-S, TN-C-S, TT, IT **



Energy meter, per socket	4 quadrant meter, MID certified, EN 50470 class B • additional Eichrecht certification (only for Eve Double Plus DE)	
Stand-by power consumption	Eve Double Plus: 12.5 W Eve Double Plus DE: 11.8 W	
Switch-Disconnector	1 power supply cable 4P, 80 A, 400 V	2 power supply cables 8P, 40 A, 400 V
Contactors	Integrated per socket, simultaneous activation of all phases Extra safety relay in series for emergency situations	
Over-current protection	Integrated in firmware, over-current response scenarios: 110-125% after 100 seconds 125% and higher after 5 seconds	
Residual current protection (not included with art. no. 904463013 and 904463023)	Per socket integrated: RCD type B, 30 mA, 4P	
Residual current operated circuit-breaker with integral overcurrent protection (only included with art. no. 904463013 and 904463023)	Per socket integrated: - RCBO 1P+N, 40 A, 30 mA, type A - RCBO 3P+N, 40 A, 30 mA, type A	
6 mA DC RCD functionality (only included with art. no. 904463013 and 904463023)	Peak let through current: 3 kA Let through energy: 6.5 kA <sup>2</sup> s With disconnection times according to IEC 62955	
Overvoltage protection (only included with art. no. 90446314X)	Per power supply cable: Surge protection device (SPD) Type 2+3	
Overvoltage category	OVC III	
Rated insulation voltage U <sub>i</sub>	500 V	
Rated impulse withstand voltage U <sub>imp</sub>	4 kV	
Rated diversity factor RDF	1	
Display	7" IPS color display Resolution: 1024 x 600 pixels Brightness: 1000 cd/m <sup>2</sup> Contrast ratio: 800:1	
Status indication	Integrated in display	
Authentication methods	Plug&Power (not available on Eve Double Plus DE) RFID card Autocharge (encoded MAC address) ISO15118 Plug & Charge * * * Girocard (only for Eve Double Plus DE) * * *	

\* When input current per phase exceeds the design current, use of Standard Load Balancing is required.

\* \* Caution: not all vehicles support the IT system. In that case an isolation transformer is required.

\* \* \* Will be available in future firmware releases, also depending on car and back office integration.

# Datasheet

## Eve Double Plus

### Technical specification



### Environmental Conditions

Operating temperature *	-25 °C to +40 °C
Electrical safety class	Class I
Ingress protection	IP54
Impact protection	IK10
Environmental conditions	Indoor / outdoor use
Electromagnetic environment class	E2 **
Mechanical environment class	M1 **
Pollution degree	PD2

\* More information about the indicated operating temperature:

- The stated charging performance is solely applicable to the charging station itself. The actual performance depends on the vehicle and the grid connection.
- A front cover in a colour other than RAL9016 Traffic White, and the addition of customizations, can increase the heat transfer from solar radiation transferred to the charging station. This also affects the charging performance.

\*\* according to 2014/32/EU (Measuring Instruments Directive)

Charging stations which are installed outside without protection will be affected by weather conditions and will discolour. Alfén recommends to install the charging stations in a sheltered environment to optimize the lifetime of the product.

### Information on Radio Frequency

Alfén charging stations are approved according to the Radio Equipment Directive (2014/53/EU). The frequency bands and maximum power of this equipment are listed here. All radio equipment is mentioned in this table, the presence or activation for each radio equipment depends on the specific configuration. These are maximum values for all models and component sub suppliers.

The Maximum power is rated power plus maximum tolerance.

Radio equipment	Frequency / Frequency bands	Max. power
DCS1800/PCS1900	1800 / 1900 MHz	30 dBm
GSM850/EGSM900	850 / 900 MHz	33 dBm
LTE-FDD	B1/B2/B3/B4/B5/B8/B12/B13/B17/B18/B19/B20/B25/B26/B27/B28/B66/B85	21 dBm
RFID card reader	13.56 MHz	7 dBuA/m at 10 m
Wi-Fi 802.11 b/g/n *	2.4 GHz to 2.4835 GHz	19 dBm

\* Will be available in future firmware releases.

# Datasheet

## Eve Double Plus

### Technical specification



### Communication and Protocols

Controller board	Alfen Hardware Platform (AHP) version 2
Vehicle communication	Mode 3 in accordance with IEC 61851-1 ed. 3 (2017) ISO15118 hardware ready (HomePlug Green PHY)
RFID card reader authentication	ISO/IEC 14443A/B, 13.56 MHz MIFARE Classic 1K/4K, MIFARE Ultralight, DESFire (EV1/EV2) Maximum length: 10 bytes
Mobile communication	LTE Cat-M1 2G Wi-Fi / Wireless LAN (802.11 b/g/n, 2.4 GHz) *
Back office communication	OCPP 1.6 (JSON) OCPP 1.6 (JSON) + Security Whitepaper OCPP 2.0.1 (JSON) (upgradeable) **
Ethernet	RJ-45: 2x1/100 BaseT 2 ethernet ports for ethernet daisy chaining
Available inputs for Smart Charging	<ul style="list-style-type: none"><li>RJ-11: DSMR 4.0-4.2 and SMR 5.0 (port P1)</li><li>RJ-45: Modbus TCP/IP Client (Energy Management System) * or Modbus TCP/IP (external energy meter)</li><li>RS-485: Modbus RTU (external energy meter) *</li><li>Télé-Information Client (TIC) (Linky smart meter)</li><li>Suspend Signal §14a EnWG *</li></ul>

\* Will be available in future firmware releases.

\*\* Ongoing integration, consult the Alfen Knowledge Base for the latest overview.

### Available Memory

RFID card	Local list: approx. 1,000 tokens (via the Back office) White list: approx. 1,200 tokens (local)
Transaction database	Approx. 1,500 transactions (of 4 h with 15 min wh metering values)
Logging for diagnostics	Approx. 1,750,000 lines

# Datasheet

## Eve Double Plus

### Technical specification



**ALFEN**  
POWER TO ADAPT

### Cyber Security

Default network interfaces	Web Service on port 443, finds charging station using mDNS
Privacy	When using the NFC reader, the charging station will read, process and cache the unique identifier contained within the tag. This data, along with location data (if configured), can be erased in the ACE Service Installer
SIM card	Mini SIM card (4G), gold plated APN username and password authentication via: <ul style="list-style-type: none"><li>• PAP</li><li>• CHAP *</li></ul>
Charging Station Management System authentication	TLS 1.2 with x509 certificates. Supported CSMS root certificate algorithms: <ul style="list-style-type: none"><li>• RSA-2048/4096</li><li>• ECDSA (P-256 or P-384)</li></ul>
EVSE authentication	HTTP Basic authentication <ul style="list-style-type: none"><li>• with TLS</li><li>• with TLS and Client Side Certificates</li><li>• without TLS</li></ul>
Diagnostic files	Encryption: AES-128-CBC
Firmware update files	Encrypted and signed. Algorithms: Encryption: AES-256-CBC Signature: ECDSA (P-384) with SHA-256
Root certificate	Installed in the factory, updateable through OCPP management system using UpdateFirmware message, or locally with ACE Service Installer
Tamper detection *	Security notification will be sent to the back office

\* Will be available in future firmware releases.

### Casing

Type	Wall-mounted charging station	
Mounting options	Wall mounting Pole mounting (optional)	
Material	Fibre-reinforced polyester (Sheet Moulding Compound - SMC)	
Colour	RAL 9016 (Traffic White): front side RAL 7043 (Traffic Grey B): front side (optional) RAL 7043 (Traffic Grey B): rear	
Locking	Torx T25 tamper resistant screws	
Casing	Dimensions (H x W x D)	Weight
Model with sockets	590 x 338 x 230 mm	17.4 kg
Model with fixed charging cables	590 x 338 x 265 mm	16.7 kg
• Charging cables	4 m (2x)	3.7 kg (2x)

# Datasheet

## Eve Double Plus

### Technical specification



Packaging *	Dimensions (L x W x H)	Weight
Box with Eve Double Plus, both models / Eve Double Plus DE, model with sockets	770 x 390 x 320 mm	18.9 kg
Box with Eve Double Plus DE, model with fixed charging cables	800 x 590 x 330 mm	28.3 kg
Box with charging cable	400 x 290 x 140 mm	4.1 kg

\* Eve Double Plus DE charging stations have the fixed charging cables connected to the charging station ex-factory. Non-DE charging stations have the charging cables delivered separately in two boxes (one charging cable per box).

### Installation Instructions

Residual current protection Optional (depending on installation and local regulations)	<b>Standard:</b> (Per power supply cable)  - 3-phase: RCD 4P $\geq$ 100 mA Type B - 3-phase: RCD 4P $\geq$ 100 mA Type A Selective *	<b>Type 2 shutter socket, 1 power supply cable variants:</b> (art. no. 904463013 and 904463023)  - 1-phase: RCD 2P $\geq$ 100 mA Type B - 3-phase: RCD 4P $\geq$ 100 mA Type B - 1-phase: RCD 2P $\geq$ 100 mA Type A Selective * - 3-phase: RCD 4P $\geq$ 100 mA Type A Selective *
Over-current & short-circuit current protection	<b>Standard:</b> (Per power supply cable)  3-phase: 4P 40 A MCB or fuse gG Rated conditional short-circuit current: 10 kA	<b>Type 2 shutter socket, 1 power supply cable variants:</b> (art. no. 904463013 and 904463023)  - 1-phase: 2P 40 A MCB or fuse gG - 3-phase: 4P 40 A MCB or fuse gG Rated conditional short-circuit current: 10 kA
Nominal input voltage	$V_{L1-N}$ : 230 V (+/-10%) $V_{L2-N}$ : 230 V (+/-10%) $V_{L3-N}$ : 230 V (+/-10%) $V_{L1-L2}$ : 400 V (+/-10%) $V_{L1-L3}$ : 400 V (+/-10%) $V_{L2-L3}$ : 400 V (+/-10%) $V_{PE-N}$ : $\approx$ 0 V	

# Datasheet

## Eve Double Plus

### Technical specification



**ALFEN**  
POWER TO ADAPT

Advised cable cross-section of the power supply cable  
(based on assumed max. 50 m cable length)

14 to 25.5 mm clamping range of the cable gland  
- 1-phase 7.4 kW: 3 x 6 mm<sup>2</sup>  
- 3-phase 22 kW: 5 x 6 mm<sup>2</sup>  
• 1 power supply cable variant:  
- Rigid copper: max. 16 mm<sup>2</sup>  
- Flexible copper: max. 16 mm<sup>2</sup>  
- Flexible copper with ferrule: max. 16 mm<sup>2</sup>  
• 2 power supply cables variant:  
- Solid copper (rigid): max. 6 mm<sup>2</sup>  
- Flexible copper (stranded): max. 10 mm<sup>2</sup>  
- Stranded copper (without ferrule): max. 10 mm<sup>2</sup>

Advised Ethernet cable types

Cat5, Cat5e or CAT6

Nominal frequency

50 Hz

Earthing system

TN system: separate PE cable

TT system: separately installed earthing electrode < 100 Ω spreading resistance

IT system: connected to a shared reference (common earth) with other metal parts

\* A limited number of suppliers have an A type RCD available

### Standard and Selectable Settings Ex-Works

Authorization	Plug&Power (not available on Eve Double Plus DE) RFID card Autocharge (encoded MAC address) * ISO15118 Plug & Charge * / * *
Smart Charging	Off Standard Load Balancing (1 power supply cable variants only) Active Load Balancing + Smart Charging Network *
Personalized display	Off (Alfen logo) On (your own logo) *
Languages supported	English, Dutch, German, French, Spanish, Portuguese, Italian, Norwegian, Swedish, Finnish, Czech, Danish, Hungarian, Icelandic, Latvian, Polish, Romanian, Slovak, Slovenian.
Management system	Stand alone OCPP charging station management systems
Direct Payment Solution	Off On * • QR code payments • Payment Terminal • Giro-E (only for Eve Double Plus DE) * *

\* Optional feature. Adding it will result in additional costs when purchasing your charging station. The default settings are always mentioned first. For more information about the optional features, contact your sales representative.

\* \* Will be available in future firmware releases.



**ALFEN**  
POWER TO ADAPT

## Accessories

	Article no.
Type 2 spiral charging cable for fixed cable variants, 4 m, 3-phase, up to 32 A (22 kW)	203100322-ICU
Eve Double Pole	803881440-ICU
Eve Double Duo Pole	803881390-ICU
Concrete base	833829300-ICU
Metal base	803828601-ICU
Wall Cover Eve Double	803881382-ICU
Additional RFID Card	203120010-ICU
Payment Terminal Wall Mount	904464010
Payment Terminal Double pole (Eve Double Pole not included)	904461300
Payment Terminal Double Duo pole (Eve Double Duo Pole not included)	904461310