

# Alfen Charging Solutions

Select your Alfen charging station



## Home

### Eve Single S-line



Traffic White / Traffic Grey

#### Key specifications

- > RFID authorisation
- > 3.7–22 kW

1 phase			3 phases		
Socket type 2	Socket type 2 shutters	Fixed cable	Socket type 2	Socket type 2 shutters	Fixed cable
904460 603	904460 605	904460 607	904460 623	904460 625	904460 627

## Business/Home

### Eve Single Plus



Traffic White / Traffic Grey

#### Key specifications

- > RFID authorisation
- > 3.7–22 kW
- > 3.5" LCD display
- > ISO 15118 hardware ready
- > Ethernet daisy chaining

3 phases		
Socket type 2	Socket type 2 shutters	Fixed cable
904460 223	904460 225	904460 227
DE Eichrecht compliant 904460 323		DE Eichrecht compliant 904460 327

## Business

### Eve Double plus



Traffic White / Traffic Grey

#### Key specifications

- > RFID authorization
- > 3.7–22 kW
- > 2x RCD type B
- > 7" LCD display
- > ISO 15118 Hardware ready
- > Ethernet daisy chaining

1 phase				3 phases		
1 feeder cable		2 feeder cables				
Max 63A		Max 32A		Max 64A (2 * 32A)		
Socket type 2 shutters	Socket type 2 shutters	Socket type 2	Fixed cable	Socket type 2	Socket type 2 shutters	Fixed cable
904463 013	904463 023	904463 021	904463 025	904463 022	904463 024	904463 026

# Alfen Charging Solutions

## Select your Alfen charging station



### Business

#### Eve Double plus DE



Traffic White / Traffic Grey

#### Key specifications

- > RFID authorization
- > 3.7-22 kW
- > 2x RCD type B
- > 7" LCD display
- > ISO 15118 Hardware ready
- > Ethernet daisy chaining
- > Eichrecht compliant

1 phase

3 phases

1 feeder cable

2 feeder cables

Max 63A

Max 32A

Max 64A  
(2 \* 32A)

Socket type 2 shutters

Socket type 2 shutters

Socket type 2

Fixed cable

Socket type 2

Socket type 2 shutters

Fixed cable

904463 013

904463 023

904463 021

904463 025

904463 022

904463 024

904463 026

### Public

#### Twin 5 Plus



Traffic White / Traffic Grey

#### Key specifications

- > RFID authorization
- > 3.7-22 kW per socket
- > 2x RCD type B
- > 7" LCD display
- > ISO 15118 Hardware ready
- > Ethernet daisy chaining

3 phase

No GCB

GCB Dutch CAM

GCB Belgian 25D60

Socket Type 2

934452 752

934452 750

934452 760

### Optional Licenses

#### All AC Products

##### Personalisation Display

905661003

##### Direct Payment solutions

905661020

##### Plug & Charge (ISO 15118) authorisation

905661030

##### Bidirectional charging (V2X)

tbd

#### Single Socket Chargers

##### Power increase 32A (for Eve Single S-line only)

905661000

##### RFID Authorisation (for Eve Single S-line only)

905661002

##### Smart Charging Network + Active Load Balancing, Single socket

905661014

#### Double Socket Chargers

##### Smart Charging Network + Active Load Balancing, Dual Socket

905661012