



General

Model name	Article no.
E-socket V2	803873061-ICU
E-socket V2.1	803873180-ICU
Accessories	Article no.
Eve Single Pole bracket E-socket	803873063-ICU
Eve Single Duo pole bracket E-socket	803873066-ICU
Eve Single Duo pole two E-sockets	803881383-ICU
Eve Double Duo pole cover two E-sockets	803881384-ICU

General Product Specifications

Number of sockets	1
Type of socket	Socket Type E, conform IEC 60884-1, CEE7/5, NF C 61-314, NF C15-100
Nominal output voltage (+/- 10%)	230 V _{ac} ; 1-phase
Maximum design current	Max. 16 A for 120 minutes
Maximum design power	3.6 kW, 1-phase
Nominal input voltage	V _{L-N} : 230 V (+/- 10%) V _{PE-N} : ≈0 V
Nominal frequency	50 Hz
Cable diameter	7-core cable, 1.5 mm ² per core
Relay	Integrated, max. 20 A at 70°C
Overcurrent protection	Legrand MCB, 2P B20A 10 kA
Short-circuit protection	Legrand MCB, 2P B20A 10 kA
Residual current protection	Through charging station and/or installation cabinet

Operating Conditions

Operating temperature	-25°C to +40 °C
Relative atmospheric humidity	5 to 95 %
Electrical safety class	Class I
Degree of protection (casing)	IP54
IK protection (mechanical impact)	IK10



Casing

Type	Wall-mounted unit
Material	Polycarbonate, UV resistant
Color	RAL 7035 (Light Grey)
Locking	Cylinder screws M4 x 24/10 according to ISO 7045
Dimensions (H x W x D)	122 x 120 x 105 mm