

Knickarm-Roboter der FR Serie – ESD zertifizierbar



Model	RV-4FRLM	RV-7FRM	RV-7FRLM	RV-13FRM	RV-13FRLM	RV-20FRM
W.-Genauigkeit (mm)	± 0,02	± 0,02	± 0,02	± 0,05	± 0,05	± 0,05
Traglast (kg)	4	7	7	13	13	20
Reichweite (mm)	649	713	908	1094	1388	1094
IP-Klasse	IP67	IP67	IP67	IP67	IP67	IP67
Optional:	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)



Model	RH-3FRH5515	RH-6FRH5520	RH-12FRH8535	RH-20FRH8535	RH-20FRH10035
Genauigkeit (mm)	± 0,02	± 0,02	± 0,02	± 0,02	± 0,02
Traglast (kg)	3	6	12	12	20
Reichweite (mm)	550	550	850	850	1000
IP-Klasse	IP20	IP54, IP65	IP54, IP65	IP54, IP65	IP54, P65
Optional:	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)	(ISO-Klasse 3)

