



FACTORY AUTOMATION

ELECTROMAGNETIC CLUTCH/BRAKE TENSION CONTROLLER

GENERAL CATALOG 2024

ROLL to ROLL Collection





Our Factory Automation business is focused on "Automating the World" to make it a better, more sustainable environment supporting manufacturing and society, celebrating diversity and contributing towards an active and fulfilling role.

Mitsubishi Electric is involved in many areas including the following:

Energy and Electric Systems

A wide range of power and electrical products from generators to large-scale displays.

Electronic Devices

A wide portfolio of cutting-edge semiconductor devices for systems and products.

Home Appliance

Dependable consumer products like air conditioners and home entertainment systems.

Information and Communication Systems

Commercial and consumer-centric equipment, products and systems.

Industrial Automation Systems

Maximizing productivity and efficiency with cutting-edge automation technology.



The Mitsubishi Electric Group is actively solving social issues, such as decarbonization and labor shortages, by providing production sites with energy-saving equipment and solutions that utilize automation systems, thereby helping towards a sustainable society.

OVERVIEW


INTRODUCTION	4
ELECTROMAGNETIC CLUTCH/BRAKE	
Powder Clutch/Brake	A-4
Tension Controller	
Tension Controller	B-4
Clutch Amplifier	B-29
Tension Meter/Tension Amplifier	B-37
Tension Detector	B-50
Common Item	
Corresponding Table for a Powder Clutch Brake and a Tension Controller with a Built-in Amplifier for the Clutch	C-2
Mechanical Load Torque Calculation Method	C-3
How to Determine the Moment of Inertia J	C-4
Moment of Inertia J Calculation Quick Reference Table	C-6
SI Unit and Non-SI Unit Conversion Table	C-7
Product List	C-8
List of Compatible Products	C-10
How to Confirm the Date of Manufacture	C-12

Roll-to-Roll control equipment


The Roll-to-Roll control equipment proposed by Mitsubishi Electric Corporation offers a capability for simple and efficient combinations of FA equipment to expand the capacity of tension control.

While each product improves the productivity in each field, establishing a network environment improves the visualization of production lines.

Using Mitsubishi Electric FA equipment for the entire production and processing of a variety of long materials such as film, textiles, and printable electronics maximizes the advantages.



Powder Clutch/Brake




Micro Powder Clutch/Brake



Clutch Amplifier






Tension Controller



Tension Detector




Tension Meter




System Components for Unwinding and Winding Machines

For winding and unwinding machines for long materials such as paper, film, thread, electric wire, various sheets, and tape, technology for controlling the material tension is important to ensure higher speed and performance.

As a general electric manufacturer, Mitsubishi Electric Corporation provides system components for various products ranging from actuators such as clutches and brakes to tension controllers that control them.





Powder Clutch/Brake

The powder clutches and brakes of Mitsubishi Electric, which use magnetic iron powder for transmitting torque, offer advantages such as a smooth fluid clutch and high efficiency upon coupling of the friction plate clutches.

These products are now indispensable for tension control as actuators for winding and unwinding long materials such as paper, thread, electric wire, various sheets, and tape. They are also suitable for buffer startup, power absorption, and overload safety devices (torque limiter).

1. Easy control over a wide range

Transmission torque changes continuously in response to changes in the exciting current, and so can be easily controlled over a wide range.

2. Continuous slip operation

The powder enables continuous slip on the working surface as well as stable transmission torque regardless of the slip rotation speed.

3. Stable torque

Due to the shape of the operating surface and powder leakage prevention structure, the distribution of powder can be kept uniform and stable torque can be reproduced even if the current is repeatedly turned on and off.

4. Large heat capacity

The products using powder have excellent heat resistance and an ideal cooling structure, and so can be used even in harsh continuous slip operation.

5. Smooth connection and drive

With almost equal coefficients of static and dynamic friction, load-based acceleration/deceleration can be obtained without shock at the time of complete connection.



Powder clutch



Powder brake

Explanation of icons



: Protruding shaft type




: Through shaft type

Powder clutch	Product lineup (rated torque: N·m)	Powder brake	Product lineup (rated torque: N·m)
ZKG-AN   Natural cooling type	0.5 1 2 5 10	ZKG-YN   Natural cooling type	0.5 1 2 5
ZKB-AN   Natural cooling type	0.6 3 6	ZKB-YN   Natural cooling type	0.6 3 6
ZKB-BN   Natural cooling type  Forced air cooling type	12 25 50 100 200	ZKB-XN   Natural cooling type  Forced air cooling type	12 25 50 100 200
ZA-A1   Natural cooling type	6 12 25 50 100 200	ZKB-HBN   Thermo block cooling	25 50 100 200
		 ZA-Y   Natural cooling type	6 12 25 50 100 200
		ZX-YN   Natural cooling type	3 6 12

Tension Controller Lineup



LE7-40GU-L
tension controller



LE-10WTA-CCL/LD-10WTB-CCL
tension controller

Feedback control	Open-loop control (LE7-DCA used)	Feed forward/feedback combined control (combined with LE7-DCA)
1-shaft control	Built-in clutch amplifier	RS-485 communication
Ethernet	USB interface	CC-Link V2 (LE7-CCL used)

Feedback control (LE-10WTA-CCL)	Open-loop control (LD-10WTB-CCL)	Feed forward/feedback combined control
Up to 2-shaft control	CC-Link V2	RS-422 communication (GOT connection)
RS-485 communication (LM-10WA-485 used)	USB interface (LM-10WA-USB used)	

Feedback Type Tension Controller

This type of controller directly measures the material tension using the tension detector, and performs feedback control so that the tension during unwinding and winding matches the set value. This method can accurately control tension with regard to the set value.

LE7-40GU-L tension controller

Built-in clutch amplifier.
Supports various FA networks, including CC-Link V2.
[Rated output: 24 V DC, 2.7 A]



LE-10WTA-CCL tension controller

Enables tension control for up to 2 shafts when the optional adapter is added.
Incorporates the CC-Link V2 remote device station function.



Open-Loop Type Tension Controller

This type of controller detects the reel diameter using sensors and controls the unwinding and winding torque.
This method can stably control tension without being sensitive to sudden disturbances.

LE7-40GU-L + LE7-DCA reel diameter calculation option

Supports open-loop control with LE7-40GU-L + LE7-DCA.



LD-10WTB-CCL tension controller

Enables tension control for up to 2 shafts when the optional adapter is added. Incorporates the CC-Link V2 remote device station function.



LD-30FTA tension controller

Open-loop type tension controller using the integrated thickness monitoring method (based on the initial diameter and material thickness).

[Rated output: 24 V DC, 3 A]



Order production
from April 2024

End of September 2025
Scheduled completion
of production

LD-05TL tension controller

This type of tension controller performs unwinding and winding with the reel diameter signal from the touch lever (potentiometer) as input.

[Rated output: 24 V DC, 0.5 A]



Order production
from April 2024

End of September 2025
Scheduled completion
of production

*: LE-10WTA-CCL + LD-10WTB-DCA
LD-10WTB-CCL + LE-10WTA-TAD

Mitsubishi Electric offers various types of equipment including tension controllers, tension detectors and tension meters required for tension control to allow you to choose the ideal products for your application and control needs.



LM7-1LG/LM7-2LG
tension meter

Up to 2 shafts
supported
(LM7-2LG)

CC-Link IE TSN

SLMP communication



LX7-F
tension detector

Outside wall
mounting

Inside wall
mounting

Rated load
50 to 500 N

Differential
transformer type
sensor



LD-10PAU-A/LD-10PAU-B
power amplifier

1-shaft
control

RS-422
communication
(GOT connection)

RS-485
communication
(LD-10PAU-B)

Tension Meter/Tension Amplifier

Tension meters display the material tension detected by the tension detector, and output the corresponding signal to external equipment. Some types of tension meters can handle multiple shafts or can perform digital display suitable for tension monitoring.

LM7-1LG/LM7-2LG tension meter

Tension meter that displays tension, outputs a signal in proportion to the tension, and is capable of outputting tension values via CC-Link IE TSN, SLMP communication, and analog signals.



LM-10WA-CCL tension meter

Tension meter displays the tension, and outputs a signal in proportion to the tension. Incorporates the CC-Link V2 remote device station function.



LM-10PD tension meter

Tension meter displays the tension, and outputs a signal in proportion to the tension.



LM-10TA tension amplifier

Compact tension amplifier outputs a voltage signal (0 to 5 V DC or 10 V DC) in proportion to the input signal sent from the tension detector.



Clutch Amplifier

These devices change the current and voltage of powder clutches and brakes in accordance with variable resistors provided on the panel, external signals and external variable resistors.

LD-10PAU-A/LD-10PAU-B power amplifier

Constant-current control type clutch amplifier controls the exciting current of 24 V DC type compact clutches and brakes.

[Rated output: 24 V DC, 1.0 A]

[RS-485 communication function built in (LD-10PAU-B)]



LE-50PAU power amplifier

Constant-current constant-voltage control type clutch amplifier controls the exciting current of clutches and brakes. [Rated output: 24 V DC, 4 A]



LD-40PSU power supply unit

Constant-voltage control type power supply unit adjusts the output (0 to 24 V DC) in accordance with the setting of the variable resistor provided on the panel surface or the input signal (0 to 5 V DC) for control sent from the outside.

[Rated output: 24 V DC, 3.8 A]



Order production
from April 2024

End of September 2025
Scheduled completion
of production

Tension Detector

The tension applied on the material translates to a load, and then this load value is accurately converted to an electrical signal.

LX-TD tension detector

Stationary tension detector used in combination with the feedback type tension controller or tension meter to obtain the tension signal. [Rated load: 50 to 2000 N]



LX7-F tension detector

Flange type tension detector used in combination with the feedback type tension controller or tension meter to obtain the tension signal. [Rated load: 50 to 500 N]



Comparison of Various Clutches and Brakes

Comparison


Powder clutch/brake and friction plate type clutch/brake	Powder clutch/brake	Friction plate type clutch/brake
External dimensions	Large overall	Small
Torque control	Easy	Difficult
Slip on friction surfaces	Continuous slip possible	Not practical in principle
Engaging work	Large	Small
Mounting condition	Restricted, for example, oblique and vertical mounting not allowed	Practically no restriction
Price	Expensive	Inexpensive
Application	Especially suitable for buffer startup, tension control, and torque limiter	Suitable for engaging and braking in general

Comparison based on power feeding method to electromagnetic coil	Static coil clutch/brake	Rotating coil clutch/brake
External dimensions	Rather large, especially in axial direction	Small
Construction	Somewhat complicated due to ball bearings and others attached	Simple
Power feeding condition	No concerns	Wet type is vulnerable to power feeding failure
Rotation speed	No restrictions (restricted by other factors)	Not suitable for high-speed application
Assembly into clutch box	Easy	Somewhat complicated due to installation of brush
Maintenance	Practically none required	Brush replacement required

Usage and Control Methods


Winding, unwinding, and intermediate control

■ Unwinding control




- The figure above shows the outline of an unwinding control system that uses a powder brake.
- Since unwinding tension equals braking torque divided by unwinding radius, tension can be kept constant by reducing the braking torque according to the decrease in reel diameter.
- A speed increaser and speed reducer such as gears are installed as necessary between the reel shaft and the powder brake.

■ Winding control



- The figure above shows the outline of a 2-shaft switchover winding control system that has a servo motor.
- This is an example of a feedback controlled tension control system based on the signals from the tension detector and in which pre-drive control for the auto feeder is also performed.

■ Intermediate shaft control




- The figure above shows the outline of an in-feed control system that uses a powder clutch/brake.
- In-feed control systems include a feed motor before the main shaft motor, while outfeed systems include a feed motor after the main shaft motor.

Usage and Control Methods


Types of tension control

Manual control




- Manual control of winding or unwinding tension and of countershaft tension in a system that uses a clutch/brake and only has small variations in reel diameters.
- Performs sudden control during stop and remote operation of the variable resistor.

Open-loop control



- Unwinding braking torque and winding torque shall be controlled based on the reel diameter measured on a non-contact basis.
 - There are five types of reel diameter-detection methods. Those with fewer sensors require more settings to be made.
 - (1) Speed/thickness setting method: No sensor
 - (2) Integrated thickness method: Single sensor (reel shaft)
 - (3) Ratio calculation method: Double sensor
 - (4) Touch lever method: Potentiometer
 - (5) Ultrasonic sensor method: Ultrasonic sensor
- The figure above shows a ratio calculation method using the reel shaft pulse and measuring pulse.


Feedback control



- Closed loop tension control using a tension detector is called the feedback method.
- When performing externally sequenced multiple-shaft switchover control, new reel preset control is performed based on the reel change input signal. However, pre-drive control shall be performed externally.

Torque control and speed control


Torque control



- As is shown in the figure above, when the braking torque of the powder brake for the unwinding reel is T (N·m), the tension (F) of the unwound material equals $2T/D$ (N).
- Tension is kept constant by decreasing the braking torque according to the decrease in the reel diameter D (m).
- "Torque control" refers to the type of tension control system, such as the one shown in the figure above, in which braking torque or winding torque is applied to the winding or unwinding reel so as to deliver the prescribed tension to the material.

Torque control requires no dancer rolls and can allow for the construction of a system that uses simple tension control, such as manual or open-loop control. In this system, a powder clutch/brake or servo motor (torque mode) can be used as an actuator.

Speed control




- "Speed control" refers to the type of system, such as the one shown in the figure above, in which the rotation speed of the unwinding reel or feed reel is controlled so as to keep the dancer roll in the target position. The position of the dancer roll is detected by a potentiometer.
- Since the dancer roll moves down when the in-feed speed is too fast, and moves up when it is too slow, this system requires fast response and stable control operation. The absolute precision of tension, however, depends on the precision of the air pressure. Please note that the tension controller manufactured by Mitsubishi Electric cannot perform speed control. Mitsubishi Electric offers motion controllers and inverters as control equipment for speed control.

This system is suitable for lower tension control in a system with small operation tension in proportion to the inertia compensated tension upon acceleration or deceleration or for a system that is designed to handle materials with low elasticity. A servo motor can be used as the actuator in this type of system.

Various Manufacturing Processes Require

Coater/Laminator

Applies the coating agent on the film, laminates it, and winds it.



Coater

Highly-advanced control technology is required to prevent uneven application of the coating agent on the film. When a coated film is dried in a later process, it may elongate or shrink due to fluctuations in temperature. Tension control is required during winding and unwinding of film.

① Unwinding a long material


Tension control is applied to prevent uneven application of the coating material. The feedback type tension controller ensures highly accurate tension control.

② Coating area

Because floppy motion is a concern if the distance from coating to winding is long, the tension is controlled also in the mid point.

Slitter

Makes a slit of the specified width in a material such as film, paper and metal, and winds the material at the same time.



The basic structure consists of winding, unwinding, and Slitter (knife), and a tension controller is provided as the winding and unwinding processes greatly affect the product quality.

① Unwinding a long material

The tension detector measures the tension which is then controlled to be constant by the feedback type tension controller, which changes the feeding voltage to the powder brake according to the measured tension.


② Slit part

The slitter (knife) cuts the sheet to the specified width using the knife laid out in the line center. The optimal tension is maintained before and after knitting to ensure clean cutting.

③ Winding of long material

The combined operation of potentiometer and open-loop type tension controller securely controls the tension. The open-loop control is also effective to control the tension when there is no space to mount a tension detector.

Tension Control



Laminator

The tension in the laminating area is kept constant to prevent warps and wrinkles, and to improve the bonding quality in the laminating area. Laminators are classified into several types by binding method such as dry laminator, wet laminator, hot-melt laminator and extrusion laminator.

③ Unwinding a long material

Tension control is applied to prevent uneven application of the coating material. The feedback type tension controller ensures highly accurate tension control.

④ Laminating area

2 materials are caught together and bonded to each other. At the same time, the main motor determines the production line speed.

⑤ Winding part

When the winding ratio between the maximum diameter and the minimum diameter is large, taper tension control can be used as needed to improve the winding quality. The tension controller has a taper tension function, and the taper ratio can be changed easily.



Small, lightweight,
all-in-one type
tension controller

CC-Link IE Field Basic

CC-Link


Built-in clutch amplifier

LE7-40GU-L Tension Controller

Compatible with various control methods


Feedback Control

While the material tension is directly monitored with the tension detector, feedback control is performed so as to match the target tension.




Open-Loop Control

This method keeps the tension constant by controlling the torque according to changes in the reel diameter which are calculated using the signal from the sensor.



Feed Forward/Feedback Combined Control

This method combines highly stable open-loop control and high-precision feedback control to implement more advanced tension control.




High Control Responsiveness

Thanks to high control responsiveness, the tension is stabilized even during acceleration/deceleration such as when starting and stopping the material line. Various functions are standard equipment so that the product can be used more reliably for diverse applications.

Other features include:

- Constant slip control
- Stall/new reel preset automatic calculation
- Automatic calculation of inertia compensation
- Broken liner taper tension control
- Reel diameter/length measurement timing detection
- Peripheral speed synchronization signal
- Pre-drive output

etc.



This tension controller is easy to handle with an easy-to-read display and easy-to-understand panel design in addition to sophisticated control functions.

Also equipped with a clutch amplifier for a powder clutch/brake, you can easily introduce high-performance tension control.


Easy to use

A 3.8-inch high-resolution TFT liquid crystal touch panel monitor enables intuitive operation. The controller supports English, Japanese, and Chinese (simplified).




Compact housing

The product is significantly smaller and lighter than the standard product*. With a clutch amplifier also built into the compact housing, the powder clutch/brake can be controlled directly.




Supports various communications

The controller includes Ethernet and RS-485 communication functions as standard and can connect to existing FA networks. It can also handle tension control in conjunction with network-compatible drive equipment such as inverters and servo amplifiers.



Connection to CC-Link network with LE7-CCL network option



Ethernet saves man-hours and enables long-distance transmission

LE-10WTA-CCL LD-10WTB-CCL

Tension Controller

For diverse tension control

High-functional films, high-functional fibers and printed electronics ... The following models expand the possibilities of diverse tension control.

By connecting the tension detector input adapter and reel diameter calculation adapter to the main unit, various methods of tension control are possible.

Tension control
**2 shafts
maximum**

Capable
of being installed
with DIN rails
as an in-panel
equipment



LM-10WA-TAD

Tension detector input adapter



LE-10WTA-CCL
tension controller

Tension detector
input adapter



Main unit



LD-10WTB-CCL
tension controller

Reel diameter
calculation adapter




Main unit



LD-10WTB-DCA

Reel diameter calculation adapter

“Network adaptability” allows incorporation into the line.



Highly advanced tension control

Enable tension control for up to 2 shafts

Diversified communication functions

Enable manipulation and display of settings from the panel using the graphic operation terminal.

Improved support for motor control

GT2104-P


Display main body



Connection cable




[System Configuration]



The LE-10WTA-CCL is supplied with one tension detector input adapter as an accessory.

The LD-10WTB-CCL is supplied with one reel diameter calculation adapter as an accessory.

[Control Examples]




LM7-1LG LM7-2LG tension meter **NEW**

CC-Link IE TSN support improves tension accuracy

Even during acceleration/deceleration, when tension fluctuations increase, use in combination with CC-Link IE TSN allows for rapid detection and suppression of tension fluctuations.

In addition, high-precision tension control helps improve material quality and cycle time.




LM7-1LG
(1 tension
detection shaft)

LM7-2LG
(2 tension
detection shafts)


CC-Link IE TSN allows multi-shaft control!

- With a time-division protocol, the update cycle of cyclic data is shorter than before, enabling high-frequency tension acquisition even with multiple shafts
- Allows centralized management of equipment status using an SNMP monitoring tool, with the ability to perform anomaly analysis in chronological order



Sample application (slitter)


When tension fluctuates during acceleration/deceleration



Improved
function


NEW meter (LM7-1LG, LM7-2LG)

Quick corrective control suppresses tension fluctuations




Configuration tool reduces startup costs

A CC-Link IE TSN configuration tool (free) is available to set, duplicate, and save parameters, reducing startup costs. Tension values and unit conditions (such as errors and alarms) can also be monitored, which simplifies debugging.




Replacement of the current model (LM-10PD)

Replacement can be completed without changing the panel cut dimensions because the existing panel cut can be used as is.



Comparison with current model

Item	Current model (LM-10PD)	NEW Tension meter (LM7-1LG, LM7-2LG)
Unit power supply	100 to 240 V AC	24 V DC
Analog output	5 points/shaft · Tension output (total): 0 to 5 V/1 to 5 V/ 0 to 10 V/4 to 20 mA · Output for tension meter (total): 0 to 1 mA · Output for recorder (total, left, right): 0 to 5 V	3 points/shaft · Tension output (total, left, right): 0 to 5 V/1 to 5 V/0 to 10 V/ 0 to 20 mA/4 to 20 mA
Contact output	2 points/shaft · Upper limit detection/lower limit detection	1 point/shaft · Upper limit detection/lower limit detection/upper & lower limit detection



LX7-F Flange-Type Tension Detector

This flange type tension detector is electrically compatible with a stationary tension detector (LX-TD). It can be attached directly to the wall of equipment, minimizing the width of the equipment. This detector, with a smaller footprint than a stationary tension detector, can be used for more complicated material path line devices and for tension control with a high degree of freedom.


New options
for tension
detectors

Connection to tension controller/
tension meter



Easily connected to the tension controllers and tension meters manufactured by Mitsubishi Electric with the included cable.

Secured electrical compatibility
with LX-TD tension detector



Since the compatibility with LX-TD tension detectors minimizes necessary changes in connections and settings of tension controllers and tension meters, you can introduce these products safely when updating your existing equipment.

Note: The color scheme of the dedicated cable is different. Refer to the manuals for details.

Built-in High-accuracy sensor

The “differential transformer sensor”, proven with the standalone type (LX-TD Series), is mounted in the body. This sensor is capable of highly accurate load measurements with its high output voltage and resistance to electrical noise. In addition, the sensor is resistant to impact and has outstanding durability.



Thin disc type

The thin body allows the equipment width to be minimized. A high degree of layout freedom is achieved as the path line can be changed easily and reels can be set near each other.

Nickel plated iron body

By using iron for the body, the thermal expansion rate is the same as that of other machine frames, thus suppressing the effects of ambient temperature. The surface is treated with electroless nickel plating to increase the corrosion resistance.



Electromagnetic Clutch/Brake

■ Powder Clutch/Brake

Table of Contents

ELECTROMAGNETIC CLUTCH/BRAKE

LINE-UP	A-3
Powder Clutch/Brake	
Features	A-4
Basic structure and operation	A-4
Precautions on mounting	A-5
Performance	A-6
Structure diagram (typical example)	A-8
ZKG-AN micro powder clutch	A-10
ZKB-AN powder clutch	A-12
ZKB-BN powder clutch	A-14
ZA-A1 powder clutch	A-18
ZKG-YN micro powder brake	A-20
ZKB-YN powder brake	A-22
ZKB-XN powder brake	A-24
ZKB-HBN powder brake	A-28
ZA-Y powder brake	A-30
ZX-YN powder brake	A-34
Selection	A-36
Powder clutch/brake specification contact sheet	A-42
Usage precautions	A-44

LINE-UP

Explanation of icons:   : Protruding shaft type   : Through shaft type

	Shaft	Cooling	Clutch	Brake	Torque (N·m)	Features	Figure page
Powder type	Protruding shaft 	Natural cooling	ZKG-AN 	ZKG-YN 	ZKG-AN 0.5 to 10 ZKG-YN 0.5 to 5	• Compact micro series • Small moment of inertia of rotating part • Available from 5 r/min	A-10 to A-11 A-20 to A-21
			ZKB-AN 	ZKB-YN 	0.6 to 6	• Available from 5 r/min	A-12 to A-13 A-22 to A-23
		Combination of natural cooling and forced air cooling	ZKB-BN 	ZKB-XN 	12 to 200	• A large heat capacity can be obtained by blowing air into the air gap. • Available from 5 r/min	A-14 to A-17 A-24 to A-27
		Thermoblock cooling	-	ZKB-HBN 	25 to 200	• Heat capacity increased by using a thermoblock for a driven member and by including an axial flow fan • Available from 5 r/min	A-28 to A-29
	Through-shaft 	Natural cooling	-	ZX-YN 	3 to 12	• Ultra-thin type • Available from 5 r/min	A-34 to A-35
			ZA-A1 	ZA-Y 	ZA-A1 6 to 200 ZA-Y 6 to 200	• Heat capacity increased by rotating the periphery to improve heat dissipation • Available from 15 r/min	A-18 to A-19 A-30 to A-33

Powder Clutch/Brake

■ Features

The powder clutches and brakes of Mitsubishi Electric, which use magnetic iron powder for transmitting torque, offer advantages such as a smooth fluid clutch and high efficiency upon coupling of the friction plate clutches.

Mitsubishi Electric is a pioneer of powder clutches and brakes in Japan and, with its extensive know-how, track record and achievements, has been fulfilling customers' needs.

Taking advantage of many features, these products are now indispensable for tension control as an actuator for winding and unwinding long objects such as paper, thread, electric wire, various sheets, and tape. They are also suitable for buffer startup, power absorption, and overload safety devices (torque limiter).

1. Easy control over a wide range

Transmission torque changes continuously in response to changes in the exciting current, so the transmission torque can be easily controlled over a wide range.

2. Continuous slip operation

The powder enables continuous slip on the working surface as well as stable transmission torque regardless of the slip rotation speed.

However, the powder must be used within the permissible continuous heat dissipation.

3. Stable torque

Due to the shape of the operating surface and powder leakage prevention structure, the powder is always distributed evenly, and therefore stable torque can be reproduced even if the current is repeatedly turned on and off.

4. Large heat capacity

The products using powder have excellent heat resistance and an ideal cooling structure, and so can be used even in harsh continuous slip operation.

5. Smooth connection and drive

With almost equal coefficients of static and dynamic friction, load-based acceleration/deceleration can be obtained without shock at the time of complete connection.

■ Basic structure and operation

The basic structure of the powder clutch is shown in the figure at right. The drive member (input side) and driven member (output side) are placed on a concentric cylinder separated by a powder gap, and both members are supported by bearings so that they can freely rotate.

Powder with high magnetic permeability (magnetic iron powder) is put in the powder gap, and the exciting coil is arranged on the outer circumference so that the magnetic flux flows to it.



While the drive member is rotating without being excited, the powder is pressed against the working surface of the drive member by centrifugal force, leaving the drive member disconnected from the driven member.

When the coil is excited, powder is connected in a chain along the generated magnetic flux. At this time, torque is transmitted by the coupling force between powders and the frictional force between the powder and the working surface.

Thus, the powder clutch can also be called a friction clutch using powder as a medium.


In addition, the product in which the driven member (output side) is fixed becomes a powder brake.

Cross section of ZKB-XN powder brake



When shut down


When current is not passed through the exciting coil, the clutch is released and torque is not transmitted. At this time, powder is pressed against the outer periphery of the powder gap by centrifugal force.




When connected

When the coil is excited, the magnetic flux connects the powder in a chain inside the powder gap and transmits the torque.

■ Precautions on mounting



Shaft vertical mounting inhibited



- (1) Powder clutch/brake cannot be used while mounted with the shaft perpendicular to the mount (uniform distribution of powder is not obtained).
- (2) Do not use with the input and output reversed.
It is not recommended due to durability and torque stability.
- (3) Be sure to use an elastic coupling to connect to the load shaft.
When mounting a pulley or the like, observe the allowable shaft load range.
- (4) Key dimensions are compliant with the old JIS (except for ZX series).
For details, refer to the external dimensions of each model.
- (5) Be careful of the tightening torque and overlapping allowance of the mounting bolt.
 - For the tightening torque, refer to the instruction manual.
 - Secure the following values for the overlapping allowance of the mounting bolt.
(D: Nominal diameter of bolt)
When the bracket is made of steel: 0.8 to 1.2 D
When the bracket is made of cast iron or aluminum: 1.5 to 2.0 D
- (6) Coil has no positive or negative polarity.
- (7) Be sure to perform break-in operation before starting regular operation. (For details, refer to the usage precautions.)
- (8) For the ZKG series, note the heat dissipation area of the mounting plate.
- (9) Since the outer periphery of the ZA series rotates, be sure to cover the whole body with a wire mesh or the like with good ventilation.
- (10) For details, refer to the installation example of each model.

Performance

1. Exciting current vs. torque characteristics

Fig. 1 shows an example of the exciting current vs. torque characteristics of a powder clutch.

As is clear from this figure, the torque is proportional to the exciting current over a wide range, indicating good controllability of torque. Although there are some differences depending on the model, the torque is almost proportional to the current in the range of 5 to 100% of the rated torque.




Fig. 1 Exciting current vs. torque characteristics (typical example)

2. Slip rotation speed vs. torque characteristics

Fig. 2 shows the slip rotation speed vs. torque characteristics when the current is set as a parameter. If the exciting current is kept constant, torque can be kept constant irrespective of the slip rotation speed (the difference in rotational speed between the drive member and driven member). This is because powder (magnetic iron powder), which is also called semisolid, is used as a medium for power transmission. In other words, this characteristic means that there is no difference between the static friction torque and dynamic friction torque, indicating the ease of torque control.

This characteristic not only allows continuous slip and increases the heat capacity but also widens the scope of application of powder clutches and brakes such as for tension control and buffer startup.

In the case of tension control, for example, the slip rotation speed of the clutch/brake changes according to the reel diameter, but this characteristic enables simple and accurate control merely by controlling the exciting current regardless of the slip rotation speed.




Fig. 2 Slip rotation speed vs. torque characteristics

3. Operation characteristics

This section explains the operation characteristics required when you want to control the startup time or when considering high-frequency repetitive operations.

Fig. 3 shows the operations of engaging and disengaging the powder clutch. When voltage is applied to the exciting coil, the exciting current rises exponentially with the coil time constant ($T = L/R$) determined by resistance R and inductance L of the exciting coil. Torque rises very slightly behind the exciting current regardless of the slip rotation speeds on the driving side and driven side. The clutch continues to accelerate the load with that torque.

In other words, the clutch can raise the torque to the preset level even if the driving side and driven side are not perfectly connected. This characteristic is ideal for buffer start/stop and fast start/stop as well as a large clutch heat capacity.

When particularly rapid connection or braking is required, the rise of torque can be accelerated by exciting the coil with a high voltage power supply after reducing the coil time constant by inserting a series resistance in the exciting coil, or by overexciting the voltage 2 or 3 times the rated voltage by the torque time constant.

At the rated excitation, the torque rises perfectly in coil time constant T of 4 or 5 T . On the other hand, the time taken for the torque to disappear when the excitation is interrupted is approx. 1 T .

For the coil time constants for individual models, refer to the respective specification tables.




Fig. 3 Operating characteristics of powder clutch

Table 1 ZKB series coil time constants and torque time constants

Model name	Coil time constant (s)	Torque time constant (s)
ZKB-0.06AN	0.03	0.09
ZKB-0.3AN	0.08	0.13
ZKB-0.6AN	0.08	0.13
ZKB-1.2BN	0.10	0.18
ZKB-2.5BN	0.12	0.20
ZKB-5BN	0.13	0.27
ZKB-10BN	0.25	0.5
ZKB-20BN	0.35	1.2

Table 2 ZA series coil time constants and torque time constants

Model name	Coil time constant (s)	Torque time constant (s)
ZA-0.6A ₁	0.04	0.08
ZA-1.2A ₁	0.04	0.10
ZA-2.5A ₁	0.06	0.13
ZA-5A ₁	0.09	0.17
ZA-10A ₁	0.14	0.30
ZA-20A ₁	0.30	0.90
ZA-0.6Y	0.10	0.20
ZA-1.2Y ₁	0.13	0.20
ZA-2.5Y ₁	0.15	0.25
ZA-5Y ₁	0.17	0.35
ZA-10Y ₁	0.30	0.70
ZA-20Y ₁	0.60	1.0

Table 3 ZKG series coil time constants and torque time constants

Model name	Coil time constant (s)	Torque time constant (s)
ZKG-5AN	0.02	0.04
ZKG-10AN	0.03	0.07
ZKG-20AN	0.05	0.10
ZKG-50AN	0.06	0.13
ZKG-100AN	0.09	0.37
ZKG-5YN	0.020	0.04
ZKG-10YN	0.020	0.04
ZKG-20YN	0.034	0.07
ZKG-50YN	0.045	0.09

Table 4 ZX-YN series coil time constants and torque time constants

Model name	Coil time constant (s)	Torque time constant (s)
ZX-0.3YN-24	0.035	0.09
ZX-0.6YN-24	0.05	0.1
ZX-1.2YN-24	0.07	0.15

Note 1. The time constants of ZKB-XN, YN, WN, and HBN are the same as those in Table 1.

Note 2. The values in the tables are measurement examples of the slip rotation speed of 200 r/min after completion of running-in.

If the powder clutch has been left for a long time or the idling time is long, the torque time constant may become larger. Also note that as the powder deteriorates, the torque time constant increases.

Note 3. The tables show the values at a coil temperature of 75°C.

4. Allowable continuous heat dissipation

Although the powder clutch/brake can be used in continuous slip mode, the temperature of clutch/brake parts including powder rises due to the heat generated by slip. To solve this problem, an allowable continuous heat dissipation is provided for each model, and the powder clutch/brake needs to be used within that range.

Note that the allowable continuous heat dissipation differs depending on the cooling method: natural cooling, forced air cooling, or other means. The rated value is shown for each model, but be careful regarding natural cooling as the value varies depending on the input rotation speed.

For calculation of the heat dissipation being used, refer to page A-36.

5. Allowable connection workload

When starting or braking loads with inertia with the clutch or brake, the powder and working surface slip and generate frictional heat. This heat generation raises the temperature of each part of the clutch/brake as well as the powder itself. If the heat generation is excessive, the temperature of the friction part rises abnormally. To prevent this problem, an allowable connection workload is determined for each model. The clutch/brake should, therefore, be used within this range.

6. Idling torque

Even if the exciting current is interrupted completely, idling torque is generated due to mechanical losses arising from residual magnetism of the powder, grease of the bearing, and friction such as a seal.


Brakes cannot perform torque control below this idling torque.

In the case of clutches, idling torque refers to the torque caused by the output shaft when forced to rotate while being dragged by the input shaft (dragged torque). Clutches, like brakes, cannot perform torque control below this torque.


Since this idling torque depends on the model, refer to the specifications of each model.

■ Structure diagram (typical example)


ZKG-AN structure diagram (typical example)




ZKG-YN structure diagram (typical example)




ZKB-BN structure diagram (typical example)




ZKB-XN structure diagram (typical example)




ZKB-HBN structure diagram (typical example)




ZX-YN structure diagram (typical example)



ZA-A1 structure diagram (typical example)



ZA-Y1 structure diagram (typical example)



ZKG-AN micro powder clutch

0.5 1 2 5 10



Natural cooling type

Rated torque: 0.5 to 10 N·m

Natural cooling protruding shaft type

Compact design micro series

Small moment of inertia of rotating part

Available from 5 r/min



Specifications


(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgcm ²)		Allowable rotational speed (r/min)	Weight (kg)
		Current (A)	Power (W)	Time constant (s)	Input side	Output side		
ZKG-5AN	0.5	0.35	8.4	0.02	2.1×10^{-1}	1.7×10^{-2}	1800	0.67
ZKG-10AN	1	0.47	11.3	0.03	3.46×10^{-1}	4.6×10^{-2}	1800	0.88
ZKG-20AN	2	0.55	13.2	0.06	6.80×10^{-1}	1.03×10^{-1}	1800	1.27
ZKG-50AN	5	0.8	19.2	0.06	1.85	4.0×10^{-1}	1800	2.3
ZKG-100AN	10	1.0	24	0.09	5.30	1.10	1800	4.1


Note: The idling torque is 3% or less of the rated torque at 1000 r/min and 5% or less at 1800 r/min.

Outline dimensions (mm)

ZKG-5AN to 50AN




ZKG-100AN




Model name	L1	L2	L3	L4	L5	L6	L7	L8	D1	D2	D3	D4 (h7)	D5 (g7)	D6	d (g6)	T
ZKG-5AN	77	47	16.5	13.5	5.5	10.5	9	8.5	70	60	50	48	40	30	5	4.5
ZKG-10AN	83	48.5	18.5	16	5.5	12	10	8.5	76	66	56	54	42	34	7	6.5
ZKG-20AN	95	53	22.5	19.5	6.5	15	13	9.5	85	75	65	63	48	40	9	8.5
ZKG-50AN	111	64	25	22	6	18	16	12	100	90	80	78	60	50	12	11.5
ZKG-100AN	See the above figures.															

Characteristics


● Standard torque characteristics (typical example)



● Allowable continuous heat dissipation characteristics (see item (4) of mounting example for heat dissipation area)




● Allowable continuous slip torque characteristics




Mounting example

1. Mounting the ZKG-AN type powder clutch



2. When the ZKG-AN type powder clutch is used as a brake



- (1) Fasten the fitting part of the mounting flange to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the clutch and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).
- (4) The heat dissipation area of the mounting plate should be at least 350 cm² (ZKG-100AN is 650 cm²) or more.
- (5) Pay attention to the length of the mounting screw on the input side (using a screw of the depth or more described in the external dimensions may damage the internal bearing).

ZKB-AN

powder clutch

0.6 3 6



Natural cooling type

Rated torque: 0.6 to 6 (N·m)

Natural cooling protruding shaft type

Available from 5 r/min




Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)		Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)	Input side	Output side			
ZKB-0.06AN	0.6	0.46	11	0.03	6.10×10^{-5}	6.60×10^{-6}	1800	1.8	3.5
ZKB-0.3AN	3	0.53	12.7	0.08	3.00×10^{-4}	8.00×10^{-5}	1800	3.3	7.5
ZKB-0.6AN	6	0.81	19.4	0.08	6.00×10^{-4}	1.83×10^{-4}	1800	4	10

Note: The idling torque of 0.06AN is 4% or less of the rated torque, that of 0.3AN is 2% or less, and that of 0.6AN is 1% or less.

Outline dimensions (mm)





(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	L6	L7	D1	D2	D3	D4 (g7)	Q	R		Key part		
													Diameter	Depth	d (h7)	W (p7)	T ($\frac{9}{-0.2}$)
ZKB-0.06AN	132	65	41	22	15	9	16	88	70	55	33	-	-	-	8	3	9.1
ZKB-0.3AN	154	84	42	22	14	13.5	24.5	120	75	64	42	-	M3	6	10	4	11.5
ZKB-0.6AN	164	86	46	26	14	16	22	134	80	64	42	-	M4	8	12	4	13.5

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics



● Allowable continuous slip torque characteristics



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the clutch shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).

ZKB-BN

powder clutch

12 25 50



Natural cooling type


Forced air cooling type

Rated torque: 12 to 50 (N·m)

Natural cooling/forced air cooling protruding shaft type

Available from 5 r/min

The heat capacity is increased by blowing air into the air gap.



Specifications


(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)		Forced air cooling allowable continuous heat dissipation (slip rate)*			Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)	Input side	Output side	Wind pressure (Pa)	Air volume (m ³ /min)	Power (W)			
ZKB-1.2BN	12	0.94	22.5	0.10	1.34×10^{-3}	4.90×10^{-4}	3×10^4	0.2	250	1800	5.5	20
ZKB-2.5BN	25	1.24	30	0.12	3.80×10^{-3}	1.49×10^{-3}	5×10^4	0.4	380	1800	10	33
ZKB-5BN	50	2.15	51.5	0.13	9.50×10^{-3}	4.80×10^{-3}	1×10^5	0.6	700	1800	16	60

Notes: 1. *: For the cooling air, be sure to use clean dry air passed through an air filter (complete oil removal type).

2. The idling torque is 1% or less of the rated torque.

Outline dimensions (mm)





(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	D1	D2	D3	D4 (g7)	Q	R		Key part		
											Diameter	Depth	d (h7)	W (p7)	T ($\frac{3}{2}$)
ZKB-1.2BN	192	94	49	29	15	152	126	64	42	1/8	M4	8	15	5	17
ZKB-2.5BN	230	102	64	43	17	182	160	78	55	1/8	M5	10	20	5	22
ZKB-5BN	294	112	91	55	30	219	196	100	74	1/4	M6	12	25	7	28

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (at natural cooling)



● Allowable continuous slip torque characteristics (at natural cooling)



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the clutch shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).
- (4) For the ZKB-5BN, install mounting plates on both sides.

ZKB-BN powder clutch

100 200



Natural cooling type

Forced air cooling type

Rated torque: 100 to 200 (N·m)

Natural cooling/forced air cooling protruding shaft type

Available from 5 r/min

The heat capacity is increased by blowing air into the air gap.



Specifications


(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)		Forced air cooling allowable continuous heat dissipation (slip rate)*			Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)	Input side	Output side	Wind pressure (Pa)	Air volume (m ³ /min)	Power (W)			
ZKB-10BN	100	2.4	57.6	0.25	3.50×10^{-2}	2.50×10^{-2}	6×10^4	1.1	1100	1800	37	140
ZKB-20BN	200	2.7	64.8	0.37	9.15×10^{-2}	6.89×10^{-2}	5×10^4	1.6	1900	1800	59	225

Notes: 1. *: For the cooling air, be sure to use clean dry air passed through an air filter (complete oil removal type).

2. The idling torque is 1% or less of the rated torque.

Outline dimensions (mm)




(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	D1	D2	D3	D4 (g7)	Key part		
										d (h7)	W (p7)	T ($\frac{9}{32}$)
ZKB-10BN	360	160	100	65	28	278	160	140	100	30	7	33
ZKB-20BN	408	190	109	69	30	327	174	150	110	35	10	38.5

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (at natural cooling)



● Allowable continuous slip torque characteristics (at natural cooling)



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the clutch shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).
- (4) Install mounting plates on both sides.

ZA-A1 powder clutch

6 12 25 50 100 200



Natural cooling type

Rated torque: 6 to 200 (N·m)

Natural cooling through-shaft type

Available from 15 r/min

Heat capacity increased by rotating the periphery to improve heat dissipation




Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)		Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)	Input side	Output side			
ZA-0.6A1	6	0.74	17.8	0.04	2.70×10^{-3}	5.00×10^{-4}	1800	2.7	14
ZA-1.2A1	12	0.9	21.6	0.04	6.30×10^{-3}	1.10×10^{-3}	1800	4.5	25
ZA-2.5A1	25	1.1	26.4	0.06	1.20×10^{-2}	2.30×10^{-3}	1800	6.3	39
ZA-5A1	50	1.4	33.6	0.09	2.60×10^{-2}	5.80×10^{-3}	1800	11	60
ZA-10A1	100	2.0	48	0.14	7.00×10^{-2}	1.50×10^{-2}	1800	19.5	117
ZA-20A1	200	2.5	60	0.30	2.10×10^{-1}	0.50×10^{-1}	1000	41	255


Note: The idling torque is 2% or less of the rated torque.

Outline dimensions (mm)



Model name	L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	D1	D2	D3	D4 (g7)	D5	D6	D7	D8	D9	P		R		Q		Key part		
																					Diameter	Depth	Diameter	Depth	Diameter	Depth	d (H7)	W (F8)	T (^{+0.2} / ₀)
ZA-0.6A1	86	21	58	7	16	1	56	8	21	1.1	3	128	82	73	70	60	19	60	-	16	M6	12	-	-	M4	8	15	4	16.5
ZA-1.2A1	103	32	58	13	20	2	63	13	25	1.1	4	160	96	-	80	68	24	68	54	19	M6	15	M4	10	M6	11.5	18	5	20
ZA-2.5A1	119	36	66	17	20	2	69	17	31	1.1	4	180	114	-	90	80	27	80	64	21	M6	15	M4	10	M6	12	20	5	22
ZA-5A1	141	47	74	20	20	3	103	-	35	1.3	5	220	140	-	110	95	-	95	78	31.4	M8	20	M6	12	M8	12	30	7	33
ZA-10A1	166	49	100	17	30	4	122	-	40	1.65	5	275	176	130	125	110	-	110	95	37	M10	25	M6	12	M10	18	35	10	38.5
ZA-20A1	198	59	118	21	30	3	150	-	45	1.95	6	335	218	-	155	136	-	125	-	48	M10	20	-	-	M10	15	45	12	49

Removal reference example





By using the groove (φD9) of the clutch hollow shaft as shown on the left, you can remove the clutch easily by jacking action.


(Dimensions of washers and others should be determined as appropriate with reference to the dimensions of the shaft section.)

Characteristics


● Standard torque characteristics (typical example)



● Allowable continuous heat dissipation characteristics




● Allowable continuous slip torque characteristics




Mounting example

1. In the case of shaft drive



2. In the case of belt drive



- (1) Provide the fin rotation stop screw with a clearance in the axial direction as well as on the side hole of the fin detent plate (arranged by customer) (see the enlarged view). Tightening the fin applies excessive force to the bearings inside the clutch and will damage the bearings.
- (2) When using a pulley drive, observe the range of allowable axial load (see page A-47) and do not overstretch the belt. Failure to do so may cause a bearing failure (noise, locking, etc.)
- (3) Be careful of the length of the fin rotation stop screw. If the fin rotation stop screw is too long, the tip of the screw may interfere with the bracket (rotating part).

Model name	Screw holes	Overlapping allowance of the mounting bolt (mm)
ZA-0.6A1	2-M4×8	4-8
ZA-1.2A1	2-M6×11.5	6-11.5
ZA-2.5A1	2-M6×12	6-12
ZA-5A1	2-M8×12	8-12
ZA-10A1	2-M10×18	10-18
ZA-20A1	2-M10×15	10-15

- (4) Always use an elastic coupling to connect the input side and shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling. Provide the elastic coupling with a thrust play. Installation without thrust play will cause a bearing failure (noise, locking, etc.) inside the clutch.
- (5) Since the outer periphery rotates, be sure to cover the whole body with a wire mesh or with good ventilation.

ZKG-YN

micro powder brake

0.5 1 2 5



Natural cooling type

Rated torque: 0.5 to 5 (N·m)

Natural cooling protruding shaft type

Compact design micro series

Small moment of inertia of rotating part

Available from 5 r/min




Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgcm ²)	Allowable rotational speed (r/min)	Weight (kg)
		Current (A)	Power (W)	Time constant (s)			
ZKG-5YN	0.5	0.35	8.4	0.02	9.40×10^{-3}	1800	0.4
ZKG-10YN	1	0.42	10.1	0.02	2.75×10^{-2}	1800	0.54
ZKG-20YN	2	0.5	12	0.04	5.25×10^{-2}	1800	0.96
ZKG-50YN	5	0.6	14.4	0.05	1.25×10^{-1}	1800	1.3

Note: The idling torque is 3% or less of the rated torque at 1000 r/min and 5% or less at 1800 r/min.



Outline dimensions (mm)




Model name	L1	L2	L3	L4	L5	L6	L7	L8	D1	D2	D3	D4 (g7)	S	d (g7)	T
ZKG-5YN	45	29	5	11	10.5	9	3	4	70	60	50	24	4.5	5	4.5
ZKG-10YN	50	30	7	13	12	10	4	4	76	66	56	30	4.5	7	6.5
ZKG-20YN	59	34	9	16	15	13	6	5	90	80	70	40	4.5	9	8.5
ZKG-50YN	66	36	11	19	18	16	8	5	108	95	82	44	6	15	14

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (heat dissipation area of the mounting plate is 350 cm² or more)



● Allowable continuous slip torque characteristics



Mounting example



- (1) Fasten the fitting part of the mounting flange to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).
- (4) The heat dissipation area of the mounting plate should be at least 350 cm².

ZKB-YN

powder brake

0.6 3 6



Natural cooling type

Rated torque: 0.6 to 6 (N·m)

Natural cooling protruding shaft type

Available from 5 r/min




Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)	Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)				
ZKB-0.06YN	0.6	0.46	11	0.03	6.10×10^{-5}	1800	1.7	3.5
ZKB-0.3YN	3	0.53	12.7	0.08	3.00×10^{-4}	1800	3.1	7.5
ZKB-0.6YN	6	0.81	19.4	0.08	6.00×10^{-4}	1800	3.7	10

Note: The idling torque of 0.06YN is 4% or less of the rated torque, that of 0.3YN is 2% or less, and that of 0.6YN is 1% or less.

Outline dimensions (mm)





(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	L6	D1	D2	D3	D4 (g7)	R		Key part		
											Diameter	Depth	d (h7)	W (p7)	T (_{0.2})
ZKB-0.06YN	93	52	41	22	15	4	88	70	55	33	-	-	8	3	9.1
ZKB-0.3YN	106	64	42	22	14	6	120	75	64	42	M3	6	10	4	11.5
ZKB-0.6YN	114	68	46	26	14	6	134	80	64	42	M4	8	12	4	13.5

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics



● Allowable continuous slip torque characteristics



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).

ZKB-XN

powder brake

12 25 50



Natural cooling type

Forced air cooling type

Rated torque: 12 to 50 (N·m)

Natural cooling/forced air cooling protruding shaft type

Available from 5 r/min

The heat capacity is increased by blowing air into the air gap.



Specifications


(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)	Forced air cooling allowable continuous heat dissipation (slip rate)*			Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)		Wind pressure (Pa)	Air volume (m ³ /min)	Power (W)			
ZKB-1.2XN	12	0.94	22.5	0.10	1.34×10^{-3}	3×10^4	0.2	250	1800	5.2	20
ZKB-2.5XN	25	1.24	30	0.12	3.80×10^{-3}	5×10^4	0.4	380	1800	9	33
ZKB-5XN	50	2.15	51.5	0.13	9.50×10^{-3}	1×10^5	0.6	700	1800	14.5	60

Notes: 1. *: For the cooling air, be sure to use clean dry air passed through an air filter (complete oil removal type).

2. The idling torque is 1% or less of the rated torque.

Outline dimensions (mm)





(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	D1	D2	D3	D4 (g7)	Q	R		Key part		
											Diameter	Depth	d (h7)	W (p7)	T ($\frac{0}{-0.2}$)
ZKB-1.2XN	132	83	49	29	15	152	126	64	42	1/8	M4	8	15	5	17
ZKB-2.5XN	155	91	64	43	17	182	160	78	55	1/8	M5	10	20	5	22
ZKB-5XN	193	102	91	55	30	219	196	100	74	1/4	M6	12	25	7	28

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (at natural cooling)



● Allowable continuous slip torque characteristics (at natural cooling)



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).

ZKB-XN

powder brake

100 200



Natural cooling type


Forced air cooling type

Rated torque: 100 to 200 (N·m)

Natural cooling/forced air cooling protruding shaft type

Available from 5 r/min

The heat capacity is increased by blowing air into the air gap.



Specifications


(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)	Forced air cooling allowable continuous heat dissipation (slip rate)*			Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)		Wind pres- sure (Pa)	Air volume (m ³ /min)	Power (W)			
ZKB-10XN	100	2.4	57.6	0.25	3.50×10^{-2}	6×10^4	1.1	1100	1800	34	140
ZKB-20XN	200	2.7	64.8	0.37	9.15×10^{-2}	5×10^4	1.6	1900	1800	53	225

Notes: 1. *: For the cooling air, be sure to use clean dry air passed through an air filter (complete oil removal type).

2. The idling torque is 1% or less of the rated torque.

Outline dimensions (mm)




(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	D1	D2	D3	D4 (g7)	Key part		
										d (h7)	W (p7)	T ($\frac{d}{2}$)
ZKB-10XN	239	139	100	65	28	278	160	140	100	30	7	33
ZKB-20XN	278	169	109	69	30	327	174	150	110	35	10	38.5

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (at natural cooling)



● Allowable continuous slip torque characteristics (at natural cooling)



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).

ZKB-HBN powder brake

25 50 100 200



Thermoblock cooling

Rated torque: 25 to 200 (N·m)

Thermoblock cooling protruding shaft type

Heat capacity increased by fixing a thermoblock for a driven member and by including an axial flow fan

Available from 5 r/min



Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kg·m ²)	Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)	Voltage AC (V)	Axial flow fan				Quantity
		Current (A)	Power (W)	Time constant (s)						Power consumption (W)	Current (A)	50 Hz	60 Hz	
ZKB-2.5HBN	25	1.24	29.8	0.12	3.80×10^{-3}	1800	11	33	200	43	40	0.29	0.25	1
ZKB-5HBN	50	2.15	51.5	0.13	9.60×10^{-3}	1800	16.5	65	200	43	40	0.29	0.25	1
ZKB-10HBN	100	2.4	57.6	0.25	3.50×10^{-2}	1800	37	125	200	43	40	0.29	0.25	1
ZKB-20HBN	200	2.7	64.8	0.37	9.15×10^{-2}	1800	59	205	200	43	40	0.29	0.25	2

Notes: 1. The idling torque is 1% or less of the rated torque.

2. The axial flow fan specifications of ZKB-20HBN show the numerical values per axial flow fan.


● Thermal switch specifications

Operation temperature	100°C
Contact allowable rating	120 V AC 5A/240 V AC 3A (resistive load)
Contact	Normally closed contact

Note: The operation temperature is set as an ambient temperature of 30°C.

Outline dimensions (mm)


ZKB-2.5, 5HBN



Lead wire display correspondence table

	Mark	Lead wire color
Axial flow fan	200	Gray
Thermal switch	T	Blue
Powder brake	BR	Black

ZKB-10, 20HBN





(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	L4	L5	L6	D1	D2	D3	D4 (g7)	R		Key part		
											Diameter	Depth	d (h7)	W (p7)	T (±0.2)
ZKB-2.5HBN	227	163	64	43	17	62	182	160	78	55	M5	10	20	5	22
ZKB-5HBN	265	174	91	55	30	62	219	196	100	74	M6	12	25	7	28
ZKB-10HBN	326	226	100	65	28	62	278	160	140	100	M10	20	30	7	33
ZKB-20HBN	366	257	109	69	30	62	327	174	150	110	M10	20	35	10	38.5

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics



● Allowable continuous slip torque characteristics




Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When mounting a pulley or the like, ensure it is within the range of allowable shaft load (see page A-47).
- (4) Provide space (30 mm or more) near the brake so as not to block the cooling wind.
- (5) If the axial flow fan is stopped or the cover is clogged, the inside of the brake may become hot and cause burnout. For this reason, be sure to connect the thermal switch to provide a protection circuit.
- (6) Since the brake is the open type, when using it in a place with a lot of dust, arrange a duct to convey clean air.

Connection diagram of the ZKB-HBN powder brake



ZA-Y

powder brake

6 12 25 50



Natural cooling type

Rated torque: 6 to 50 (N·m)

Natural cooling through-shaft type

Available from 15 r/min

Heat capacity increased by rotating the periphery to improve heat dissipation





Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)	Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)				
ZA-0.6Y	6	0.3	7.2	0.10	1.55×10^{-3}	1800	2.4	15
ZA-1.2Y1	12	0.39	9.4	0.13	5.50×10^{-3}	1800	5	25
ZA-2.5Y1	25	0.73	17.5	0.15	9.40×10^{-3}	1800	7.4	39
ZA-5Y1	50	0.94	22.6	0.17	2.30×10^{-2}	1800	11	60

Note: The idling torque of ZA-0.6Y is 5% or less of the rated torque and that of ZA-1.2Y1 and others is 3% or less of the rated torque.



Outline dimensions (mm)




Model name	L1	L2	L3	L4	L5	L6	L7	D1	D2	D3	D4 (g7)	D5	P		Key part		
													Diameter	Depth	d (H7)	W (F8)	T (r ^{0.2})
ZA-0.6Y	68	53	15	2	64	1.1	3	116	116	80	70	12.5	M5	12	12	4	13.5
ZA-1.2Y1	88	58	26	5	86	1.1	4	160	144	100	74	19	M6	17	18	5	20
ZA-2.5Y1	100	66	28	5	92	1.1	4	180	170	140	100	21	M10	19	20	5	22
ZA-5Y1	106	74	27	5	101	1.3	5	220	195	150	110	31.4	M10	19	30	7	33

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics (at natural cooling)



● Allowable continuous slip torque characteristics (at natural cooling)



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Be careful of the length of the mounting bolt. If the mounting bolt is too long, the tip of the bolt may interfere with the rotating part.

Model name	Screw holes	Overlapping allowance of the mounting bolt (mm)
ZA-0.6Y	3-M5 × 12	8-11
ZA-1.2Y1	3-M6 × 17	9-16
ZA-2.5Y1	3-M10 × 19	15-18
ZA-5Y1	3-M10 × 19	15-18

- (3) Set the concentricity between the brake side threading shaft and the load shaft to 0.05 mm or less.
- (4) Since the outer periphery rotates, be sure to cover the whole body with a wire mesh or the like with good ventilation.

ZA-Y powder brake

100 200




Natural cooling type

Rated torque: 100 to 200 (N·m)

Natural cooling through-shaft type

Available from 15 r/min

Heat capacity increased by rotating the periphery to improve heat dissipation




Specifications

(Rated voltage: 24 V DC)

Model name	Rated torque (N·m)	Coil (75°C)			Moment of inertia J (kgm ²)	Allowable rotational speed (r/min)	Weight (kg)	Powder weight (g)
		Current (A)	Power (W)	Time constant (s)				
ZA-10Y1	100	1.21	28.8	0.3	6.60×10^{-2}	1800	22	105
ZA-20Y1	200	1.9	45.6	0.6	2.00×10^{-1}	1000	40	235

Note: The idling torque is 3% or less of the rated torque.



Outline dimensions (mm)




Model name	L1	L2	L3	L4	L5	L6	D1	D2	D3	D4 (g7)	D5	P	Key part		
												Depth	d (H7)	W (F8)	T (^{+0.2} ₀)
ZA-10Y1	140	29	5	130	1.65	5	275	250	150	110	37	22	35	10	38.5
ZA-20Y1	160	42	6	152	—	—	335	320	240	160	—	30	45	12	49

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics



● Allowable continuous slip torque characteristics



Mounting example



- (1) Fasten the fitting part of the bracket to the mounting plate and fix it.
- (2) Be careful of the length of the mounting bolt. If the mounting bolt is too long, the tip of the bolt may interfere with the rotating part.

Model name	Screw holes	overlapping allowance of the mounting bolt (mm)
ZA-10Y1	6-M10 × 22	15-21
ZA-20Y1	6-M10 × 30	15-29

- (3) Set the concentricity between the brake side threading shaft and the load shaft to 0.05 mm or less.
- (4) Since the outer periphery rotates, be sure to cover the whole body with a wire mesh or the like with good ventilation.

ZX-YN

powder brake

3 6 12



Natural cooling type

Rated torque: 3 to 12 (N·m)

Natural cooling through-shaft type

Ultra-thin type

Available from 5 r/min





Specifications

Model name	Rated torque (N·m)	Coil (75°C)				Moment of inertia J (kgm ²)	Allowable rotational speed (r/min)	Weight (kg)
		Voltage (V)	Current (A)	Power (W)	Time constant (s)			
ZX-0.3YN-24	3	24	0.4	9.6	0.035	3.5×10^{-5}	400	1.1
ZX-0.6YN-24	6	24	0.4	9.6	0.050	9.0×10^{-5}		1.8
ZX-1.2YN-24	12	24	0.5	12	0.070	1.6×10^{-4}		2.3

Note: The idling torque is 10% or less of the rated torque.

Outline dimensions (mm)




(Paint color Munsell 10Y 7.5/1)


Model name	L1	L2	L3	D1	D2	D3 (h5)	Key part		
							d (H7)	W (Js9)	T (°0.2)
ZX-0.3YN-24	43	25	6.5	88	80	47	15	5	17.3
ZX-0.6YN-24	49	30	6.5	105	97	55	20	6	22.8
ZX-1.2YN-24	50	30	7	118	110	62	25	8	28.3

Characteristics


● Standard torque characteristics (typical example)




● Allowable continuous heat dissipation characteristics



● Allowable continuous slip torque characteristics



Mounting example



- (1) Fasten the fitting part of the bearings to the mounting plate and fix it.
- (2) Always use an elastic coupling to connect the brake-side threading shaft and load shaft, and set the concentricity, perpendicularity, etc. of the shafts at this time within the allowable value of the elastic coupling to be used.
- (3) When supporting the load shaft with built-in bearings, be careful not to implement 3-point support. (The brake has 2 built-in bearings.)

Selection

■ When used in continuous slip condition

Normally, the powder clutch/brake are used in the continuous slip condition. The heat dissipation P (heat generation due to slip) in this case is expressed by the following equation.

$$P = 0.105 \times T \times N_r \text{ (W)} \cdots \cdots \cdots (1)$$

where,

Nr: Slip rotation speed (r/min)

T: Transmission torque (N·m)

Select the model of the clutch/brake so that the heat dissipation obtained by equation (1) is within the allowable continuous heat dissipation. If the allowable continuous heat dissipation is insufficient with natural cooling, forced cooling is required. When the clutch/brake is used in continuous slip, the size of the clutch/brake is often determined by the heat dissipation, and the operating torque may be very small compared to the rated torque of the clutch/brake. In such a case, appropriate selection can be performed by using a proper deceleration device and changing the operating torque to the range where it can be easily controlled.

■ Selection of powder clutch/brake for tension control

1. Machine specifications and selection calculation

Fig. 1 on page A-38 shows the flow chart for selecting the powder clutch/brake capacity when using it as a typical usage example for tension control.

When selecting a model, it is necessary to consider the 3 points of (1) torque, (2) rotational speed, and (3) heat dissipation (heat generation due to slip). These points are calculated from the machine specifications (tension, line speed, and reel diameter or roll diameter) by the following formula.

$$(1) \text{ Torque} \quad T = F \times \frac{D}{2} \text{ (N·m)} \cdots \cdots \cdots (2)$$

$$(2) \text{ Rotation speed} \quad N_r = \frac{V}{\pi \times D} \text{ (r/min)} \cdots \cdots \cdots (3)$$

$$(3) \text{ Heat dissipation} \quad P = 0.105 \times T \times N_r \text{ (W)} \cdots \cdots \cdots (4)$$

where,

F: Tension (N)

D: Raw web reel diameter or roll diameter (m)

V: Line speed (m/min)

Nr: Slip rotation speed (r/min) of powder clutch/brake

(This is the slip difference between the input and the output rotation speeds for the powder clutch, and the input rotation speed for the powder brake.)

Based on these calculation results, select the powder clutch/brake according to the flow shown in Fig. 1 on page A-38.

2. Points of selection and points to be noted

(1) Torque

Calculate the maximum and minimum values of torque and check whether they are within the controllable range. The torque controllable range of the powder clutch/brake is from the rated torque to the range of the idling torque of the product. (Because there is a torque loss of the bearing and seal inside the product, even if the exciting current is set to 0 A, the torque does not become 0 N·m. This idling torque, which is usually approx. 2% of the rated torque, depends on the product, so refer to the specification column of each model for actual selection.)

The controllable range is from idling torque to 100% of the rated torque, but using it within the range as close to the rated torque as possible can obtain better controllability. In particular, when the control unit uses an open-loop system such as a reel diameter detection type or a manual type, it is recommended to use it in a range of 5 to 100%, which excels in linearity of the exciting current-torque characteristics.

(2) Rotation speed

Both the powder clutch/brake must have a maximum rotation speed less than the allowable rotation speed. Also, the powder brake must have a minimum rotation speed of 15 r/min or more, and the powder clutch must have a rotation speed difference of 15 r/min or more between the input and output (that is, both the powder clutch/brake also require a slip rotation speed of 15 r/min or more).

If the rotation speed is low and a sufficient slip rotation speed cannot be secured for unwinding of a machine with a slow line speed, use a powder clutch rather than a powder brake and secure slip rotation speeds by applying rotation in the direction opposite to the direction of rotation of the unwinding reel using a geared motor or the like. (ZKB-N series, ZKG-N series, and ZX-YN series can be used from 5 r/min or more.)

(3) Heat dissipation (heat generation)

The heating value per unit time generated when the powder clutch/brake slips is called heat dissipation. In tension control, the powder clutch/brake is used in the continuous slip state and therefore the temperature of the powder clutch/brake body is increased by the slip heat. The heat dissipation (heat generation) during operation needs to be suppressed below the allowable continuous heat dissipation of the operating model.

3. When an unwinding powder brake is used

Assuming that the gear ratio of the unwinding reel and brake shaft is 1 (direct connection),

Slip rotation speed = rotation speed of unwinding reel

Therefore, the formula for calculating the heat dissipation (heat generation) is as follows:

$$P = 0.105 \times T \times N_r = 0.105 \times \left(F \times \frac{D}{2} \right) \times \left(\frac{V}{\pi \times D} \right) = 0.0167 \times F \times V \quad \dots\dots\dots (5)$$

The heat dissipation (heat generation) is determined by the machine tension and line speed and is not affected by the reel diameter.

4. When a winding powder clutch is used

Assuming that the gear ratio of the winding reel and clutch shaft is 1 (direct connection),

Slip rotation speed = powder clutch input rotation speed - rotation speed of winding reel

Normally, the input rotation speed of the powder clutch is set to a constant rotation speed of 15 r/min or more than the maximum rotation speed of the winding reel. The heat dissipation (heat generation) is also changed by the change of the reel diameter (rotation speed of the winding reel).

So, the maximum heat dissipation during operation is calculated by the following formula.

$$P_{\max} = 0.105 \times T_{\max} \times N_{r\max} = 0.105 \times T_{\max} \times (N_i - N_{\min}) \dots\dots\dots (6)$$

where,

$P_{\max}$: Maximum heat dissipation (W)

$T_{\max}$: Maximum torque (N·m)

$N_{r\max}$: Maximum slip rotation speed (r/min)

N_i : Clutch input rotational speed (r/min)


$N_{\min}$: Minimum rotational speed (r/min)

The torque and slip rotation speed become maximum at the end of winding, and the heat dissipation (heat generation) at this time becomes the maximum.

(Note: In the taper tension control, the tension at the end of winding may decrease greatly compared with the tension at the start of winding. In this case, the heat dissipation may become maximum during winding, not at the end of winding.)

■ Introduction of selection tool

For the selection tool, consult your local Mitsubishi Electric representative.



* Note: The allowable torque control range varies depending on the model.
Please see the specifications section of each model for details.

Fig. 1 Powder clutch/brake capacity selection flow

■ Sample calculation

Winding or unwinding is performed in 2 modes, one is constant tension winding to wind up with constant tension, and the other is taper tension winding to wind up strongly at first and gently at the end. These modes can be realized by using the torque controllability or constant torque characteristics of the powder clutch/brake.

There are 3 ways to realize them: unwinding side brake, idling roll clutch/brake, and winding side clutch.

The torque controllable range is from idling torque to rated torque. Since the idling torque depends on the model, refer to the specifications of each model.

1. Unwinding powder brake (1)

What kind of powder brake should be used as the unwinding side brake with the film winding machine with the following specifications?

(1) Specifications

Tension	F: 100 N constant
Unwinding roll diameter	Maximum diameter D1: 660 mm Minimum diameter D2: 110 mm
Line speed	V: 170 m/min constant

(2) Calculation

(1) Torque

Suppose the brake torques required at the beginning and end of unwinding at tension 100 N are T₁ and T₂.

$$T_1 = \frac{D_1}{2} \times F = \frac{660 \times 10^{-3}}{2} \times 100 = 33 \text{ N} \cdot \text{m}$$

$$T_2 = \frac{D_2}{2} \times F = \frac{110 \times 10^{-3}}{2} \times 100 = 5.5 \text{ N} \cdot \text{m}$$

(2) Rotation speed

Suppose the slip rotation speeds of the brake at the beginning and end of unwinding at a line speed of 170 m/min are N₁ and N₂.

$$N_1 = \frac{V}{\pi D_1} = \frac{170}{\pi \times 660 \times 10^{-3}} = 82 \text{ r/min}$$

$$N_2 = \frac{V}{\pi D_2} = \frac{170}{\pi \times 110 \times 10^{-3}} = 492 \text{ r/min}$$

(3) Heat dissipation

Heat dissipation P is:

$$\begin{aligned} P &= 0.105 \times T \times N_r = 0.105 \times \frac{DF}{2} \times \frac{V}{\pi D} \\ &= 0.0167 \times F \times V = 0.0167 \times 100 \times 170 \\ &= 284 \text{ W} \end{aligned}$$

As shown above, the continuous heat dissipation of the unwinding side brake at constant line speed and constant tension becomes constant.

(4) Selection

In view of the torque (T₁, T₂) and heat dissipation (P), the ZA-5Y1 (allowable continuous heat dissipation approx. 290 W at rated torque 50 N·m and input rotation speed 82 r/min) can be used with natural cooling.

The unwinding reel and brake shaft are directly connected, and the torque usage range is 66 to 111% of the rating.

Reference:

The allowable continuous heat dissipation of natural cooling varies depending on the rotation speed of the brake, so decide whether to use one while the brake is at low rotation (N₁) when the allowable continuous heat dissipation becomes small.

2. Unwinding powder brake (2)

Next is an example of changing the gear ratio according to the tension when the torque control range is wide.

(1) Specifications

Tension	F: 130 to 520 N
Unwinding roll diameter	D: 100 to 900 mm
Line speed	V: 100 m/min constant
Manual control	

(2) Calculation

(1) As in the previous example, calculate the torque (T), rotation speed (N), and heat dissipation (P) of the unwinding reel.

$$\begin{aligned} T &= \frac{D}{2} \times F = \frac{(0.1 \text{ to } 0.9)}{2} \times (130 \text{ to } 520) \\ &= 6.5 \text{ to } 234 \text{ N} \cdot \text{m} \end{aligned}$$

$$\begin{aligned} N &= \frac{V}{\pi D} = \frac{100}{\pi \times (0.1 \text{ to } 0.9)} \\ &= 35.4 \text{ to } 318 \text{ r/min} \end{aligned}$$

$$\begin{aligned} P &= 0.0167 \times F \times V = 0.0167 \times 520 \times 100 \\ &= 869 \text{ W (Max.)} \end{aligned}$$

Based on the above calculations, the ZKB-10HBN (thermoblock type) is used.

(2) Here, suppose the torque of 234 N·m is 100%, the torque obtained above is 2.8% with 6.5 N·m, and it is out of the control range (5 to 100%) in manual control.

Therefore, it is necessary to change the gear ratio according to the tension and set it to the appropriate torque range. The branch value (F_m) of tension is determined by the following formula.

$$\begin{aligned} F_m &= \sqrt{\text{Tension ratio} \times F_{\min}} \\ &= \sqrt{\frac{520}{130}} \times 130 = 260 \text{ N} \end{aligned}$$

(3) When tension is 130 to 260 N

Unwinding reel

$$\begin{aligned} T_{bo} &= \frac{(0.1 \text{ to } 0.9)}{2} \times (130 \text{ to } 260) \\ &= 6.5 \text{ to } 117 \text{ N} \cdot \text{m} \end{aligned}$$

$$N_{bo} = N = 35.4 \text{ to } 318 \text{ r/min}$$

Brake shaft (1.17 times increase in speed)

$$\begin{aligned} T_{br} &= T_{bo} \times \frac{1}{1.17} = 5.6 \text{ to } 100 \text{ N} \cdot \text{m} \\ &\quad (5.6 \text{ to } 100\%) \end{aligned}$$

$$N_{br} = N_{bo} \times 1.17 = 41.4 \text{ to } 372 \text{ r/min}$$

$$P = 0.0167 \times F \times V = 434 \text{ W (Max.)}$$

(4) When tension is 260 to 520 N

Unwinding reel

$$T_{bo} = 13 \text{ to } 234 \text{ N}\cdot\text{m}$$

$$N_{bo} = 35.4 \text{ to } 318 \text{ r/min}$$


Brake shaft (2.34 times increase in speed)

$$T_{br} = 5.6 \text{ to } 100 \text{ N}\cdot\text{m}$$

$$N_{br} = 82.8 \text{ to } 744 \text{ r/min}$$

$$P = 869 \text{ W (maximum)}$$

(5) Structure example



★1 and ★2 are electromagnetic clutches etc.,

When $F = 130 \text{ to } 260 \text{ N}$

$$\star 1: \text{OFF } \star 2: \text{ON} \rightarrow \text{Gear ratio becomes } \frac{1}{1.17}$$


When $F = 260 \text{ to } 520 \text{ N}$

$$\star 1: \text{OFF } \star 2: \text{ON} \rightarrow \text{Gear ratio becomes } \frac{1}{2.34}$$

3. Winding side powder clutch

(1) Specifications

Tension	F: 180 N constant
Winding roll diameter	Minimum diameter D1: 90 mm Maximum diameter D2: 540 mm
Line speed	V: 120 m/min



(2) Calculation

(1) Torque

Suppose the clutch torques required at the beginning and end of winding at tension 180 N are T_1 and T_2 .

$$T_1 = \frac{D_1}{2} \times F = \frac{90 \times 10^{-3}}{2} \times 180 = 8.1 \text{ N}\cdot\text{m}$$

$$T_2 = \frac{D_2}{2} \times F = \frac{540 \times 10^{-3}}{2} \times 180 = 48.6 \text{ N}\cdot\text{m}$$

(2) Rotation speed

Suppose the rotation speeds at the beginning and end of winding at a line speed of 120 m/min are N_1 and N_2 (N_1 and N_2 are the rotation speeds of the winding reel, not the slip rotation speeds).

$$N_1 = \frac{V}{\pi D_1} = \frac{120}{\pi \times 90 \times 10^{-3}} = 425 \text{ r/min}$$

$$N_2 = \frac{V}{\pi D_2} = \frac{120}{\pi \times 540 \times 10^{-3}} = 71 \text{ r/min}$$

(3) Heat dissipation

If the input rotation speed N_0 of the clutch is made higher by 15 r/min* than the rotation speed N_1 necessary at the beginning of winding of the winding reel, the heat dissipation P_1 and P_2 of the clutch at the beginning and end of winding are as follows:

$$P_1 = 0.105 \times (440 - 425) \times 8.1 = 12.8 \text{ W}$$

$$P_2 = 0.105 \times (440 - 71) \times 48.6 = 1883 \text{ W}$$

As shown, when it is used as a winding clutch with constant tension, both the slip rotation speed and winding torque become maximum at the end of winding. Thus the heat dissipation also becomes maximum at the end of winding, and therefore the heat capacity of the clutch must be determined in the final state of winding. Based on the above calculation results, the model name is selected as follows.

Forced air cooling type:

ZKB-20BN (rated torque 200 N·m, allowable continuous heat dissipation 1900 W) can be used.

However, if it is directly connected to the winding reel, torque will be 5% or less of the rated torque at the beginning of winding, so use automatic control.

Examination of the unwinding side turns out as follows:

$$\begin{cases} N_1 = 425 \text{ r/min} \\ N_2 = 71 \text{ r/min} \end{cases} \quad \begin{cases} T_1 = 8.1 \text{ N}\cdot\text{m} \\ T_2 = 48.6 \text{ N}\cdot\text{m} \end{cases}$$

This is the same as the winding side. Heat dissipation P is:

$$\begin{aligned} P &= 0.105 \times T_1 \times N_1 = 0.105 \times T_2 \times N_2 \\ &= 0.0167 \times F \times V = 361 \text{ W} \end{aligned}$$

The above results show the following:

Forced air cooling type:

ZKB-5XN (rated torque 50 N·m, allowable continuous heat dissipation 700 W) can be used.

As is clear from the above calculation results, the torque operating ranges and the slip rotation speeds are not much different between the winding clutch and the unwinding brake, but the heat dissipations are significantly different. Note that, for this reason, the selected model will change. The heat dissipation on the unwinding side is constant regardless of the winding ratio (the ratio of the minimum diameter to the maximum diameter), but on the winding side the heat dissipation increases substantially in proportion to the winding ratio.

- * The clutch input rotation speed N_0 was increased by 15 r/min, but normally it should be approx. 10% higher. For the brake on the unwinding side in this example, ZA-5Y1 blower cooling, or ZKB-5HBN can be used.

4. Powder clutch for driving pinch roll

(1) Specifications

Tension F: 100 to 350 N
Roll diameter D: 200 mm
Line speed V: 45 to 90 m/min

When the decorative sheet is bonded to the plywood, the pinch roll B, with respect to the feed roll A, has a difference in circumferential speed due to a change in the rubber roll diameter by the pinch pressure conduction. To prevent the peripheral speed difference from causing roll B to slip, a powder clutch is put into the drive system of roll B to let the slipping occur in the clutch.

(2) Calculation

(1) Rotation speed of roll B

$$N = \frac{V}{\pi D} = \frac{45 \text{ to } 90}{\pi \times 200 \times 10^{-3}} = 72 \text{ to } 144 \text{ r/min}$$

(2) Roll driving torque

$$\begin{aligned} T &= \frac{D}{2} \times F = \frac{200 \times 10^{-3}}{2} \times (100 \text{ to } 350) \\ &= 10 \text{ to } 35 \text{ N}\cdot\text{m} \end{aligned}$$

(3) Heat dissipation

When the input rotation speed of the clutch is decided so that the slip rotation speed becomes 15 r/min when the line speed is 45 m/min, the maximum heat dissipation is as follows.

The input rotation speed N_0 of the clutch at 90 m/min is:

$$N_0 = 144 \times \left(\frac{72 + 15}{72} \right) \div 144 \times 1.2 = 173 \text{ r/min}$$

Therefore, the heat dissipation is:


$$P = 0.105 \times (173 - 144) \times 35 = 107 \text{ W}$$

Based on the above calculation results, use ZKB-2.5BN (rated torque 25 N·m, heat dissipation 160 W at 200 r/min) where the speed has been doubled from the roll B shaft. In this case, the operating range of the torque becomes 5 to 17.5 N·m, and the input rotational speed N'_0 of the clutch will be enough if it is:

$$N'_0 = 288 \times \left(\frac{144 + 15}{144} \right) \div 318 \text{ r/min}$$

The heat dissipation at this time is:

$$P = 0.105 \times (318 - 288) \times 17.5 = 55 \text{ W}$$



Powder clutch/brake specification contact sheet

- For unwinding/winding (Note) Circle either one.

Customer name	Machine name	Delivery	Quantity
---------------	--------------	----------	----------

Configuration

① to ⑩: Driven rolls

Unwinding roll

Tension detector

M

Tension detector

Winding motor

Powder clutch

Gear ratio: $R=d_1/d_2$

Reduction gear efficiency: η

Powder brake

Material

Unwinding roll

Winding width

Flange

Winding core

Gear ratio: $R=d_1/d_2$

Please fill the items indicated with * without fail.

Operational tension *	Minimum $F_{min} =$ _____ N	Maximum $F_{max} =$ _____ N
Reel diameter *	Minimum $D_{min} =$ _____ m	Maximum $D_{max} =$ _____ m
Line speed *	Minimum $V_{min} =$ _____ m/min	Maximum $V_{max} =$ _____ m/min
Acceleration/deceleration time	Maximum $t_{min} =$ _____ sec (0→ V_{max} , V_{max} →0)	
Reel mass	Weight of material $W_m =$ _____ kg	Winding width $L_m =$ _____ mm
	Weight of reel core $W_c =$ _____ kg	
	Weight of flange $W_f =$ _____ kg	
Operation cycle	Time required to complete one roll _____ min Interval _____ min	
Material	Type _____ Width _____ mm Thickness _____ μ m	
Environmental condition	Temperature _____ $^{\circ}$ C Humidity _____ % Vibration _____ m/s^2	
Forced cooling method	Air source Yes/No	
Type of control	(A) Manual (B) Open-loop control (C) Feedback control	
Type of control	(A) Constant tension (B) Taper ratio (Minimum: _____)% (Maximum: _____)%	
Turret	(A) Yes (B) No	
Auto paster	(A) Yes (B) No	
Reel diameter detector	(A) Required (B) Not required (For external taper control)	

Note 1. Attach a power system diagram if one is available.

Note 2. If the inertia of the driven roll has a large effect, enter the weight in the blank.

■ Powder clutch/brake specification contact sheet

● For intermediate shaft

Customer name	Machine name	Delivery	Quantity
---------------	--------------	----------	----------

Configuration

Please fill the items indicated with * without fail.

Operational tension *	Inside F1 min= _____ N On the side of roll (6) for out-feed Outside F2 min= _____ N On the side of roll (5) for out-feed	F1 max= _____ N On the side of roll (5) for in-feed F2 max= _____ N On the side of roll (6) for in-feed
------------------------------	---	--

Feed roll *	Feed roll diameter Do _____ m
--------------------	-------------------------------

Line speed *	Minimum Vmin = _____ m/min Maximum Vmax = _____ m/min
---------------------	--

Acceleration/deceleration time	Minimum tmin = _____ sec (0→Vmax, Vmax→0)
---------------------------------------	---

Mass of feed roll	Wd = _____ kg
--------------------------	---------------

Operation cycle	Time required to complete one reel _____ min Interval _____ min
------------------------	--

Material	Type _____ Width _____ mm Thickness _____ μm
-----------------	--

Environmental condition	Temperature _____ °C Humidity _____ % Vibration _____ m/s ²
--------------------------------	--

Forced cooling method	Air source Yes/No
------------------------------	---

Type of control	(A) Manual (B) Open-loop control (C) Feedback control
------------------------	---

Others	Set the efficiency of the reduction gears (d1/d2, d3/d4) to be η=0.9 to 1 and consider the mechanical loss torque of each roll to be negligible.
---------------	--

Find the clutch/brake models and gear ratio d1/d2 and d3/d4 based on the basic specifications above. However, the input rotation speed of clutch shall be set so that the rotation speed of the feed roll is 10% higher than that of the main shaft roll when the clutch is fully engaged. In addition, the bias torque, equivalent to 10% of the maximum tension, shall be applied to the clutch/brake, and the minimum slip rotation speed of the clutch shall be higher than the minimum operational rotation speed of the clutch. When the tension on the feeding side is constantly higher than that of the discharging side, no brake is required. On the contrary, when the tension on the feeding side is constantly lower than that of the discharging side, no clutch is required. However, when the difference between the feeding side tension and discharging side tension is small and the torque based on the difference above is smaller than the minimum control torque of the clutch and brake, both clutch and brake shall be used in combination.

Note 1. Attach a power system diagram if one is available.

Note 2. If the inertia of the driven roll has a large effect, enter the weight in the blank.

Usage precautions

1. Safety Precautions

Carefully read the "Safety Precautions" at the back of the manual, pay attention to safety and use the product correctly.

2. General items

(1) Do not attach the input shaft and the output shaft reversely.

For the powder clutch, the normal mounting method is to use the high-speed rotation side as the input side. (For the ZA type, the hollow shaft is on the output side, and for the ZKB type, the input/output shafts are indicated by the arrows on the external dimension drawing of this catalog and on the name plate.) Usage with the input and output mounted reversely in continuous idling is not recommended in view of the torque characteristics and powder life.

In addition, in principle, the clutch/brake should be used on the horizontal shaft; they cannot be used on the vertical shaft. When using them in the following conditions, contact us and state the conditions of use.

- (a) When used at an inclined angle
- (b) When the whole set revolves
- (c) In case of special specifications such as low-temperature specifications

(2) Be careful of installation of pulley, coupling, and shaft.

When fitting a pulley, coupling, or shaft to the product, be sure to use clearance fit and not to apply excessive force to the product. Applying impacts, etc. to the product may scratch the inside bearings and quickly cause damage.

(3) Be careful of wetness of the powder.

The performance becomes unstable if the powder becomes wet, so take great care not to allow water, oil etc. to enter inside. Especially, when installing the product close to the gearbox, oil may flow in through the shaft, so seal the shaft completely. In addition, the product is not hermetically sealed, so it cannot be used in environments where oil mist, oil, or water is directly applied.

(4) Be careful that the surface temperature does not exceed a limit temperature.

Control the maximum surface temperature by continuous operation under the conditions shown in the table below. Exceeding this value will greatly reduce the durability.

Limit of clutch/brake surface temperature (stator circumference)

Model	Limit temperature (approximate)
Natural cooling	100°C or lower
Thermoblock cooling	
Forced air cooling	70°C or lower

However, the ambient temperature is based on 30°C.

Consider the above limit temperature as a guide, and be sure to use the product within the allowable continuous heat dissipation.

(5) Be careful of the compressed air piping.

The powder clutch/brakes are not hermetically sealed. Especially with the ZA-A1 powder/clutch and ZA-Y1 powder brake, when compressed air flows into (passes thorough) the bearings, the air passes the powder gap in the product and may cause powder to leak outside. When the compressed air piping for the air chuck of the unwinding/winding reel is arranged so that it enters the penetration shaft of the powder clutch/brake, perform installation so as to prevent air leakage and make a device configuration that releases air in order to prevent air leakage from the joint.

3. Relationship between rated torque and rated current

- (1) Torque significantly exceeds the rated torque when the rated current is applied at the time of shipment (break-in operation) (refer to the standard torque characteristics for each model). This is because the torque is set to be high in anticipation of aged deterioration of the powder. Use the product without exceeding the rated torque.

- (2) Torque reduction occurs due to aged deterioration, but it is possible to adjust the torque by increasing the current. However, use the product without exceeding the rated current.

4. Torque

- (1) For the current vs. torque characteristics, the standard values of new products at 200 r/min are listed. As the powder deteriorates over time, this standard characteristic will change. Correct the change in torque characteristics with current.
- (2) Torque can be easily controlled by current, but note that torque may become unstable, especially when using large models (torque of 100 N·m or more) at high-speed rotation and at low current.
- (3) Note that when ON/OFF control is performed at high-speed rotation, it may take a considerable amount of time to reach the predetermined torque.
- (4) Torque variation near the rated current is approx. $\pm 10\%$ for each product. The variation between products is approx. $\pm 15\%$ of the standard torque characteristic. Therefore, when clutches and brakes are operated in parallel, it is recommended to design so that current can be individually adjusted.
- (5) The torque value shows hysteresis. Therefore, please be aware that an increase or decrease of the current will cause a difference in torque.
- (6) The idling torque described in the specifications column of each product is a representative measured value. The idling torque will change, depending on the mounting method, driving conditions, driving time, etc. Since there is variation among individual products, be sure to select the appropriate model by making allowance for this.

5. Lifespan

- (1) When the product is used in continuous slip for winding or unwinding, the lifespan of the powder varies depending on the usage conditions (relative slip speed, etc.), but in general, when it is used at the allowable continuous heat dissipation, the life of the powder, where the torque drops to the rated torque at the rated current, is approx. 5000 to 8000 hours. However, if it is used at the rated torque or lower, it can be used continuously, so the life will be extended. However, even at the same heat dissipation, when the slip rotation speed, that is, the relative rotation speed, is continuously at a relatively high level, the life time tends to be short, so make settings so that the relative rotation speed is as low as possible.
- (2) Using the product with allowance for allowable continuous heat dissipation can extend the life of the powder. For example, if the product is used at 50% of the allowable continuous heat dissipation, the service life may be approx. twice or more.
- (3) The ZKG and ZX series do not allow powder replacement, so the product needs to be replaced if the powder life is reached.

6. When operating at low speed (15 r/min or less)

When using the product in continuous operation such as tension control, it shows stable torque characteristics, but in intermittent operation involving idle rotation, the rise of torque may be slightly delayed immediately after voltage application. To avoid this, use the product as follows.

- (1) Even after completion of unwinding, keep applying weak excitation (5 to 10% of rated current) so that the powder does not fall off from the working surface.
- (2) Increase the speed so that the minimum rotation speed becomes 15 r/min or higher. However, be aware that accurate torque control may not be possible due to mechanical loss, etc. of the speed increasing mechanism if the speed increasing rate is large.
- (3) The ZKB-N, ZKG, and ZX series can be used from approx. 5 r/min.

7. Precaution Be sure to perform break-in driving


(1) What is break-in driving?

Since the powder inside the powder clutch/brake is unevenly distributed due to shock during transportation, break-in operation must be performed before starting regular operation.

To obtain the intrinsic performance of the powder clutch/brake, it is important that the powder is evenly distributed within the powder gap.

If the powder is unevenly distributed, the torque may decrease, fluctuate, become fixed, etc., preventing the product from demonstrating its intrinsic performance.

Break-in can uniformly distribute the unevenly distributed powder within the powder gap and generate a stable torque proportional to the exciting current.



(2) Break-in driving procedure

This is an example of an effective way to break in if the regular break-in is difficult.

Note: In either case, be careful not to cause the surface temperature of the clutch/brake to exceed the limit shown in the instruction manual or catalog.

[Reference] Regular break-in condition

- In the case of a clutch, secure it to prevent the output shaft from rotating.
(This step is unnecessary when the load torque is large.)
- Rotate the input shaft at approx. 200 r/min for approx. 1 minute.
- While rotating, set the exciting current to 1/4 to 3/4 of the rated value and excite it approx. 10 times in the cycle of ON for 5 seconds and OFF for 10 seconds.
If the uneven distribution of the powder is large and it is difficult to carry out break-in, repeat approx. 10 times in the cycle of ON for 5 seconds and OFF for 10 seconds at the rated excitation.

1. When the rotation speed of the input shaft cannot be set to approx. 200 r/min

Set the exciting current ON time as follows. Calculate the time until the number of revolutions of the input shaft reaches approx. 20 times.

(Example) In the case of 30 r/min

$$60 \text{ seconds} \times \frac{1}{30 \text{ r/min}} \times 20 \text{ times} = 40 \text{ seconds}$$

Therefore, turn ON for 40 seconds, turn OFF for 10 seconds, and repeat it approx. 10 times.

In some cases, it may be effective to repeat ON for 2 seconds and OFF for 0.5 second at the rated excitation.

2. When the output shaft cannot be fixed in the case of a clutch

- Increase the load to make it as difficult as possible for the output shaft to rotate.
- Set the exciting current to approx. 1/8 to 1/4 of the rating.
- Set the ON time as follows. Calculate the time until the relative rotation of the input shaft and output shaft reaches approx. 20 times in total.

(Example) In the case of input shaft 300 r/min and output shaft 280 r/min

Relative rotation speed $300 - 280 = 20 \text{ r/min}$

$$60 \text{ seconds} \times \frac{1}{20 \text{ r/min}} \times 20 \text{ times} = 60 \text{ seconds}$$

Therefore, turn ON for 60 seconds, turn OFF for 10 seconds, and repeat it approx. 10 times.

Even if the break-in is carried out in the above manner, the effect is slightly inferior to the regular case, but the break-in will be gradually completed during normal operation.

(3) Effect of break-in driving

Figures 1 and 2 are examples of torque measurements made when the exciting current is turned ON and OFF and when it is kept ON.

When the exciting current is turned ON and OFF, the torque becomes higher every time the current is turned ON and OFF, which verifies the effect of break-in. On the other hand, if the exciting current remains ON, the figure shows that the torque becomes saturated in the low state.




Fig. 1 Measurement example when tuning the exciting current ON and OFF. (ZKB-2.5XN powder brake)

Fig. 2 Measurement example when maintaining the exciting current ON. (ZKB-2.5XN powder brake)

* In the following cases, break-in is insufficient.

- Torque output remains low.
- Torque does not stabilize.
- Noise, pulsation of torque, or stuck at startup occurs.

Usage precautions

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector

Common Item

8. For forced air cooling

- (1) Install an air filter.
Generally, compressed air used as cooling air contains oil and moisture, so be sure to use clean dry air passed through an air filter (complete oil removal type).
(If compressed air not passed through an air filter is used, the powder becomes moist due to moisture and oil content and the performance drops sharply.)
- (2) If the piping is long and it is branch piping, check if the air flow rate near the clutch/brake suction pipe is more than the specified amount.

9. Thermoblock cooling type

- (1) An axial flow fan (blower) is provided. If the performance of this axial flow fan decreases, heat dissipation will be worse and the allowable continuous heat dissipation rate will be reduced, so install the fan with a clearance around it.
Especially when the surrounding environment is bad and there is a possibility of foreign matter adhering to the guard of the axial flow fan, clean it periodically.
- (2) Since a thermal switch for detecting the temperature is provided on the side of the stator, be sure to connect it to an alarm device for alarm detection.

10. Selection

- (1) Even within the allowable continuous heat dissipation, products cannot be used exceeding the rated torque.
- (2) When the control range of tension is wide, multiple clutches may be installed and switched over during operation. In this case, use an electromagnetic clutch to disconnect the unused clutch to prevent the output side from being forcibly idled.
- (3) When the gear ratio is too large, accurate control may not be possible due to the influence of mechanical loss. A gear ratio of 5 or less is recommended (especially in the low torque region).

11. Abnormal torque at startup

- (1) Depending on the operation pattern (turning on the coil current at rotation stop and applying rotation to the input shaft, or starting rotation at the same time as turning on the coil current), a temporarily higher torque (peak torque) than specified may be generated at startup.
Especially when vibration is added while the current is off, powder tends to be unevenly distributed, so this tendency appears remarkably. To counter this problem, keep supplying weak exciting current to the coil of the clutch/brake even while it is stopped. This makes the problem less likely to occur.
- (2) Peak torque may occur similarly when the powder is wet. In this case, however, the product may need to be replaced.

12. Others

- (1) Note that at high altitude the allowable continuous heat dissipation will be lowered due to atmospheric pressure. This specification applies to an altitude of 1000 m or less.
- (2) The protection degree is IP00. Therefore, the powder clutch itself may emit oxidized powder or fine powder, so it cannot be used where dust is completely prohibited.
- (3) The powder clutch/brake does not generate coupling sound or braking sound, unlike friction plate type clutches/brakes. However, it generates friction sound because torque is generated by the friction force of powder connected by electromagnetic force. Normally, the friction sound is of a level that is not a problem in ordinary machines, but it may become large due to the influence of internal powder distribution (usually, the sound will be reduced after break-in and operation for some time).
Also, friction of the powder generates minute vibration. The vibration could resonate with the machine such as in a roll and could cause a loud noise.
- (4) There is no problem at the vibration levels of general printing machines, paper machines, packaging machines, etc. without abnormal vibration, but it cannot be used on machines with impact force.
- (5) When a voltage is applied to the clutch/brake, a magnetic flux is generated, and the installation shaft, etc. are magnetized by this flux. If this magnetization becomes a problem, installation with nonmagnetic materials is recommended, but it cannot be completely eliminated. Note that the protruding shafts of models such as the ZKB are also magnetized.
- (6) Lead wire length varies by approx. $\pm 10\%$.
(Example: Lead wire length 200 is 200 ± 20 mm.)
- (7) Operating temperature and humidity of clutch/brake
Ambient temperature: 0 to 40°C
Relative humidity: 30 to 90%

13. Allowable shaft load

- Bearing load is determined based on a fatigue life of 15000 hours.
- Thrust load is not permitted in principle.

(1) ZKB series

There are the following 2 methods of connecting the input and output of the ZKB type powder clutch/brake:


- Connection method using couplings
- Connection method using pulleys

In the case of connection using couplings in (a), our policy is to use elastic couplings, so the shaft radial load never becomes a problem.

However, in the case of pulley connection in (b), the product must be used by restricting the shaft radial load based on the shaft strength and bearing load capacity.

Table 1 Allowable shaft load (radial load) of ZKB series

Model name	Allowable shaft load (N)			
	300 r/min	500 r/min	1000 r/min	1800 r/min
ZKB-0.06	140	140	125	120
ZKB-0.3	280	280	245	240
ZKB-0.6	330	330	260	215
ZKB-1.2	360	325	255	210
ZKB-2.5	550	460	365	300
ZKB-5	975	975	770	635
ZKB-10	2090	1760	1400	1150
ZKB-20	2600	2190	1740	1430



- Natural cooling, forced air cooling, and water cooling clutches and brakes have the same values as long as they have the same torque capacities.
- The table indicates allowable load values of the shaft strength or bearing radial load, whichever is smaller.
- The load application point is based on the shaft end face. Note that the permissible value will be small if the point of application is outside the end face.
- Calculate the shaft load F by the following formula.

$$F = \frac{2T}{D} \times K(N)$$

T: Transmission torque (N·m)

D: Pulley diameter (m)

K: Load factor (timing belt 1.5, V belt 2.5, sprocket 1.5)

(2) ZKG series


Table 2 Allowable shaft load (radial load) of ZKG series

Model name	Allowable shaft load (N)			
	300 r/min	500 r/min	1000 r/min	1800 r/min
ZKG-5AN	30	30	30	30
ZKG-10AN	75	75	75	75
ZKG-20AN	120	120	120	120
ZKG-50AN	210	210	210	210
ZKG-100AN	240	240	240	240
ZKG-5YN	30	30	30	30
ZKG-10YN	75	75	75	75
ZKG-20YN	120	120	120	120
ZKG-50YN	450	400	340	280

Note 1. Since both shafts of each ZKG type powder clutch have the same configuration, the allowable shaft loads are the same.

Note 2. The load point is based on the shaft end face.

Note 3. Note that when the load application point is outside the shaft end face, the allowable value becomes smaller.



(3) ZA series


Table 3 Allowable shaft load (radial load) of ZA series

Model name	L (mm)	Allowable shaft load (N)			
		300r/min	500r/min	1000r/min	1800r/min
ZA-0.6A1	-	560	470	375	310
ZA-1.2A1	-	1080	910	720	590
ZA-2.5A1	-	1120	950	750	620
ZA-5A1	-	1790	1510	1190	980
ZA-10A1	-	1930	1630	1290	1060
ZA-20A1	-	4430	3740	2960	-
ZA-0.6Y	28	305	260	205	170
ZA-1.2Y1	32	340	290	230	185
ZA-2.5Y1	44.5	425	360	285	235
ZA-5Y1	58	880	760	600	500

Note 1. The load application point is based on the position indicated by "F" in the above figure.

Note that the permissible value will be small if the point of application is outside the above figure.

Note 2. In principle, pulleys cannot be directly applied to ZA-10Y1 to 20Y1.




(4) ZX series

Table 4 Allowable shaft load (radial load) of ZX series

Model name	L (mm)	Allowable shaft load (N)		
		100 r/min	200 r/min	400 r/min
ZX-0.3YN-24	24	1000	795	630
ZX-0.6YN-24	28	1305	1035	820
ZX-1.2YN-24	32	1485	1180	935

Note 1. The load application point is based on the position indicated by "F" in the figure.

Note 2. Note that when the load application point is outside the "F" position, the allowable value becomes smaller.



The background of the left half of the page features a large, faint clock face. Overlaid on the clock are several digital numbers in a 7-segment font, including '1', '25', '04', '19', '33', '05', and '7.86'.

Tension Controller


- Tension Controller
- Clutch Amplifier
- Tension Meter/
Tension Amplifier
- Tension Detector

Table of Contents

Tension Controller

Product Organization	B-3
Tension Controller	
LE7-40GU-L tension controller	B-4
LE-10WTA-CCL/LD-10WTB-CCL tension controller	B-16
LD-30FTA tension controller	B-21
LD-05TL tension controller	B-27
Clutch Amplifier	
LE-50PAU power amplifier	B-29
LD-40PSU power supply unit	B-31
LD-10PAU power amplifier.....	B-33
Tension Meter/Tension Amplifier	
LM7-1LG/LM7-2LG tension meter	B-37
LM-10WA-CCL tension meter	B-41
LM-10PD tension meter	B-46
LM-10TA tension amplifier	B-48
Tension Detector	
LX-TD tension detector	B-50
LX7-F tension detector	B-54

Product Organization (are products covered in this chapter)



Note: AC servo motors and vector control motors are covered under torque controllable products.

*1: LE-10WTA-CCL, LD-10WTB-CCL, LM7-1LG, LM7-2LG, LM-10WA-CCL, LM-10WA-TAD, LD-10WTB-DCA, LD-10PAU-B, LE7-40GU-L, LE7-DCA and LE7-CCL comply with CE marking.
For details, refer to the instruction manual.

*2: Order production will begin in April 2024.

LE7-40GU-L tension controller

Feedback control

Open-loop control

The LE7-40GU-L tension controller is used in combination with a tension detector to perform feedback control of the material tension during unwinding, intermediate shaft, and winding of long materials.

Such actuators as powder clutches/brakes, servo motors (torque mode), and air clutches/brakes can be used with these controllers, and they come with a built-in clutch amplifier and auxiliary power supply for clutches and brakes that operate on 24 V DC.

Features

● Abundant tension control functions

- Target tension can be controlled in accordance with the material and reel diameter using the taper function.
- Inertia compensation can reduce torque fluctuations due to acceleration and deceleration.
- Mechanical loss correction can reduce the effect of torque due to mechanical loss.
- Torque output can be corrected in accordance with each model of Mitsubishi Electric powder clutches/brakes.

● Extended functions by the LE7-DCA reel diameter calculation option

Sophisticated tension control using reel diameter, measurement length and line speed information is achieved by connecting the LE7-DCA reel diameter calculation option (sold separately).

* For details, refer to the section on the LE7-DCA reel diameter calculation option.

● Intuitive operation and multilingual display

- Liquid crystal touch panel is adopted. Intuitive setting of numerical values is possible through the touch panel and dial operation.
- The buttons are designed with graphic symbols for easy understanding.
- The liquid crystal touch panel can be switched between English, Japanese, and Chinese (simplified).


● Compatible with various FA networks

- Equipped with the Ethernet/RS-485 communication port as standard, it supports various communication protocols such as CC-Link IE Field Network Basic and MODBUS/TCP.
- CC-Link Ver. 2 communication can be supported by using the LE7-CCL network option (sold separately).
- Backup/restore of the product and batch management of parameters are possible by using the tension controller setting sheet for LE7-40GU-L.
- * To use the tension controller setting sheet for LE7-40GU-L, MX Component (sold separately) and Microsoft Excel® must be installed. For the operating environment, refer to the instruction manual.

● Compliance with standards

- EN standard: EC directive/CE marking compliant
- * For details, refer to the instruction manual.






(1) Value setting dial	Dial to set various setting values. Simultaneous pressing with the key locking key prohibits all panel operations.
(2) Touch panel.....	Touch panel for changing screens and setting various setting values. Displays various set values, setting items, control status etc.
(3) LCD display (monochrome)	Dot matrix LCD display.
(4) Monitor display (red)	Displays the tension, reel diameter, and output values.
(5) Monitor display switching key	Switches among the items to be displayed on the monitor display.
(6) Monitor display unit indicator LED (red)	Displays the unit for items displayed on the monitor display.
(7) Automatic control mode key	Selects the automatic control mode.
(8) Automatic control mode status indicator LED (green) ...	Displays the automatic control mode status.
(9) Manual control mode key.....	Selects the manual control mode.
(10) Manual control mode status indicator LED (green)	Displays the manual control mode status.
(11) Output ON/OFF key	Selects control output ON/OFF.
(12) Output ON/OFF status indicator LED (green)	Displays the control output status.
(13) Key locking key	Disables other keys to prevent accidental changes to the setting values.
(14) Key locking status indicator LED (green)	Displays whether the changing of various settings is prohibited or not.
(15) Menu switching key	Reads the data stored in the menu.
(16) Power supply key	Selects between power standby and ON.
(17) Power status indicator LED (green).....	OFF: Off (No AC power supply) Flashing: Standby (AC power supply supplied + power supply key OFF) ON: On (AC power supply provided + power supply key ON)

- Sample display switching

- Example of operation mode screen



Set the target tension in machine operation.


- Example of adjustment mode screen




Set up the tension full scale.

Externally connected devices


Some of the devices that can be connected to the input/output terminals of this model of tension controller include the following. Tension detector, actuator, and some of the signal input switches are essential to the system; other components are connected as necessary.



Outline dimensions (mm)



• Panel cutting dimensions for mounting on panel surfaces



- Accessory:
- 2 mounting brackets
 - Screw (M4x10) 4 screws
 - Screw (M4x6) 2 screws
 - Dust proof protection sheet 1 sheet
- Exterior color: Munsell N1.5 equivalent

Specifications

● General specifications

Item	Specifications				
Operating ambient temperature	0 to +40°C				
Storage ambient temperature	-20 to +60°C				
Operating ambient humidity	35 to 85% RH (no condensation)				
Storage ambient humidity	35 to 85% RH (no condensation)				
Vibration resistance*1		Frequency	Acceleration	Half amplitude	10 times in each of X, and Z directions (80 minutes in total)
	Panel mounting	5 to 8.4 Hz	-	1.75 mm	
		8.4 to 150 Hz	4.9 m/s ²	-	
	Floor mounting	5 to 8.4 Hz	-	3.50 mm	
		8.4 to 150 Hz	9.8 m/s ²	-	
Impact resistance*1	147 m/s ² , action time 11 ms, 3 times in each of X, Y and Z bi-directions with half-sine pulse				
Noise tolerance	Noise voltage: 1000 Vp-p, Noise width: 1 μs Using 30 to 100 Hz cycle noise simulator				
Withstand voltage	1500 V AC for 1 minute, measured between all terminals together*2 and the grounding terminal				
Insulation resistance	5 MΩ or more using 500 V DC insulation resistance tester: Measure across all terminals*2 and grounding terminal				
Grounding	Class D grounding (100 Ω or less, common grounding with strong power field not possible)				
Operating atmosphere	Free of corrosive, flammable or conductive gases, and low levels of dust				
Installation place	In the control panel				

*1: The criterion is shown in IEC 61131-2.


*2: SLD terminal is excluded.

● Basic specifications

Item	Specifications	
Outline dimensions	105(H) × 170(W) × 125(D) mm	
Weight	Approx. 1.0 kg	
Installation method	Panel mounting, floor mounting	
Wiring	Power input terminal block	Spring clamp 24 to 16 AWG (0.2 to 1.5 mm ²) terminal block, not detachable
	Powder clutch/brake Output terminal block	Spring clamp 24 to 16 AWG (0.2 to 1.5 mm ²) terminal block, not detachable
	Signal I/O terminal block	Spring clamp 24 to 16 AWG (0.2 to 1.5 mm ²) terminal block, detachable
Power supply	Input	100 to 240 V AC
	Output	For tension detector 5 V DC
		For contact input 24 V DC
		For variable resistor 5 V DC
Display	LCD	320 × 128 dots TFT monochrome
	7-segment LED (for monitor)	4 digits (1 set)
	Unit display LED	4 types (1 set)
	Status display LED	6 points
Operation	Touch panel	Analog resistance film type
	Jog dial	With push ON switch
	Key switch	8 points
Contact signal	Input	General-purpose, 6 points, sink/source selectable
	Output	General-purpose, 2 points
Analog signal	Input	General-purpose, 3 points
	Output	General-purpose, 2 points
Tension Detector Input		For LX type tension detector or for strain gauge (range switching)
Control output	Output for 24 V DC clutch/brake	0 to 24 V DC, rated 2.7 A for control, constant voltage/constant current control selectable
		For pre-drive/old reel stop. Total 0 to 24 V DC control is 2.7 A or less.
	Voltage output for servo amplifier and inverter	±2.7 V DC, ±5 V DC, ±8 V DC, ±10 V DC, selectable
		For pre-drive/old reel stop. ±2.7 V DC, ±5 V DC, ±8 V DC, ±10 V DC, selectable
	Current output for electro-pneumatic converter	0 to 20 mA DC, 4 to 20 mA DC, selectable
Communication	Ethernet communication	CC-Link IE Field Network Basic, SLMP, MODBUS/TCP (slave), GT Designer3
	USB communication	Personal computer communication (GT Designer3 and data transfer tools)
	RS-485 communication*1	N:N networks, MODBUS/RTU, and ASCII (slave)
Optional components	Extension option	LE7-DCA type reel diameter calculation option and LE7-CCL type network option*1
	External memory cassette	LD-8 EEPROM type EEPROM cassette

*1: When connecting to CC-Link by using LE7-CCL, RS-485 communication cannot be used.

External connection



Terminal layout

- Powder clutch/brake output signal terminal block (CN2)

S2	S1	PN	PP
----	----	----	----

- Power terminal block (CN1)

⏏	NC	N	L
---	----	---	---

- Signal terminal block 1 (CN3)

0 V	S/S	24 V	DI6	DI5	DI4	DI3	DI2	DI1	NC	AO2	AO1	AI2	5 V	SLD	SLD	WHL	GRL	BLK	RED
DOC	DO2	DO1	NC	SN	NRO	SN	SA	EAN	EAP	AOC	AIC	AI3	AI1	⏏	SLD	WHR	GRR	BLK	RED

- Signal terminal block 2 (CN4)

SG	RDA	SDA	NC	NC	NC	SNCR	Y3	Y2	Y1
RDB	SDB	NC	NC	NC	PDRV	MEM	LRST	DRST	BWD

*** : Input system terminal *** : Output system terminal

LE7-DCA reel diameter calculation option

The reel diameter calculation option LE7-DCA is connected to the LE7-40GU-L tension controller, and is used for detecting the reel diameter in a non-contact method by calculating the ratio of reel shaft pulses and measuring pulses. In addition, the line speed can be detected and the length can be measured so that the reel shaft rotational speed command and timing detection signal can be output based on the reel diameter information. (This product cannot be used alone.)

Features


Connecting to the LE7-40GU-L tension controller enables advanced tension control such as open-loop control and feedforward/feedback combined control.

- Constant slip control of the powder clutch possible for winding


- When winding with an inverter and a powder clutch, performing constant slip control of the powder clutch using the reel shaft rotation speed signal greatly reduces heat dissipation. It has various advantages compared with using the powder clutch at a fixed input rotation speed.
- The selection of a powder clutch with a smaller rated torque may be possible.
- The life of the powder clutch may be significantly extended.

- Timing detection of reel diameter and length measurement is possible.


3 contact points are provided for connection to various timing detectors.



Outline dimensions (mm)



• Mounting to the LE7-40GU-L tension controller



Specifications

● Basic specifications

Item		Specifications
Outline dimensions		50(H) × 68(W) × 35(D) mm
Weight		Approx. 0.2 kg
Power supply	Input	No input (supplied from LE7-40GU-L)
	Output	12 V DC for encoder 12 V DC for proximity switch
Input	Reel shaft pulse input	Input for reel shaft pulse sensor, 2 points
	Measuring pulse input	Input for measuring pulse sensor
	Contact input*1	Reverse rotation/forward rotation, reel diameter reset, measurement length/residual length reset, memory hold, 5 points for pre-drive
Output	Contact output*1	Timing detection, 3 points For reel diameter, measurement length/remaining length, switchable
		Peripheral speed synchronization

*1: LE7-40GU-L input/output signals are used for the contact input and contact output. Refer to the following for the input/output specifications.
LE7-40GU-L APPLICATION MANUAL (SH-170022ENG)

● External specifications

Item	Specifications
Target line velocity	V = 0.1 to 1,000 m/min
Acceleration	a = V/t = 1 to 50 m/min/sec t = acceleration/deceleration time
Reel diameter	D = 0 to 2,000 mmφ
Material thickness	T = 0.1 μm to 10 mm
Measurement length/remaining length	0 to 65,000 m
Reel shaft rotational speed	N = 0 to 3,600 r/min
Measuring pulse frequency	1.5 Hz to 30 kHz
Reel shaft pulse frequency	0 to 200 Hz

● I/O specifications

Item	Terminal names	Specifications	
Power output	12 V	Pulse sensor power	- The rated voltage: 12 V DC - Voltage range: 11.4 to 12.6 V DC - Current value: 130 mA or less - Total of measuring pulse sensor and reel shaft pulse sensor × 2
		Pulse input power	- The rated voltage: 12 V DC - Voltage range: 11.4 to 12.6 V DC - Current value: 21 mA or less
	0 V	0 V	
Pulse input	SPL	Measuring pulse input	- ON/OFF time width = 15 μsec or more each - Frequency = 30 kHz or less 1 pulse per measuring roll circumference 1mm*1
	SPRA	Reel shaft pulse input (A-axis)	11.4 to 12.6 V DC - ON current = approx. 7 mA - Sink/source input
	SPRB	Reel shaft pulse input (B-axis)	
	SPS/S	Pulse input sink/source switching	
	SLD	For shield connection	

*1: Based on 1 pulse per 1 mm of measuring roll circumference. Note that this can be compensated in the range of 90 to 180% using the electronic gear function.

*2: Based on 1 pulse per reel shaft rotation. Note that if the material is thick, the reel diameter calculation resolution can be increased by increasing the number of pulses per rotation to 2, 4, 8 or 16 using the parameters.

● Pulse input specification

Item			Specifications
Voltage output	Pulse sensor power		• The rated voltage: 12 V DC • Voltage range: 11.4 to 12.6 V DC • Current value: 130 mA or less*³
	Pulse input power		• The rated voltage: 12 V DC • Voltage range: 11.4 to 12.6 V DC • Current value: 21 mA or less*⁴
Pulse input	Connection shape		Terminal block
	Input format		Sink/source input switchable
	Input signal voltage		12 V DC
	Input signal current		7 mA
	Input response frequency	Measuring pulse input	30 kHz or less
		Reel shaft pulse input (reel A, reel B)	200 Hz or less
	ON/OFF time width	Measuring pulse input	15 μs or more
		Reel shaft pulse input (reel A, reel B)	0.5 μs or more
	Number of pulses	Measuring pulse input	1 pulse per measuring roll circumference 1 mm* ¹
		Reel shaft pulse input (reel A, reel B)	1 pulse per reel shaft rotation* ²
	Input signal format		Sink: NPN open collector Source: PNP open collector

*1: Based on 1 pulse per 1 mm of measuring roll circumference. Note that this can be compensated in the range of 90 to 180% using the electronic gear function.

*2: Based on 1 pulse per reel shaft rotation. Note that if the material is thick, the reel diameter calculation resolution can be increased by increasing the number of pulses per rotation to 2, 4, 8 or 16 using the parameters.

*3: The total current consumption of the measuring pulse sensor and reel shaft pulse sensors (reels A and B) should be 12 V DC, 130 mA or less.

*4: The input current for the measuring pulse input and reel shaft pulse input (reels A and B) is 12 V DC, 7 mA/1 point.


● Available sensor

Item	Reel shaft pulse sensor (reel A, reel B)	Measuring pulse sensor
Power supply voltage	12 V DC ±10%	12 V DC ±10%
Current consumption	20 mA or less	90 mA or less
Output format	NPN open collector output PNP open collector output	NPN open collector output PNP open collector output
Output capacity	Applied voltage = 20 V or more Sink/source current = 10 mA or more	Applied voltage = 20 V or more Sink/source current = 10 mA or more
Recommended part* ¹	OMRON E2E-X□E1 proximity switch TL-Q□MC1 proximity switch	OMRON E6A2 rotary encoder E6B2 rotary encoder KOYO ELECTRONICS TRD-J□-RZ rotary encoder


*1: Supply power to the measuring pulse sensor from the 12 V external power supply.

External connection

● Sink input wiring



● Source input wiring



Precautions

- When performing sink input wiring, short the SPS/S terminal and 12 V terminal.
- Do not wire the pulse input sink/source switching terminal (SPS/S) and LE7-40GU-L sink/source switching terminal (S/S) to a common terminal.
- Do not supply power to the 12 V and 0 V terminals from outside.

Precautions

- When performing source input wiring, short the SPS/S terminal and 0 V terminal.
- Do not wire the pulse input sink/source switching terminal (SPS/S) and LE7-40GU-L sink/source switching terminal (S/S) to a common terminal.
- Do not supply power to the 12 V and 0 V terminals from outside.

● Terminal layout

NC	NC	0V	0V	SPRA	12V	SLD	SLD	SPL	12V
NC	NC	0V	0V	SPS/S	12V	⏏	SLD	SPRB	12V


LE7-CCL network option

The LE7-CCL network option is an extension option for connecting to the LE7-40GU-L tension controller and serving as a remote device station of CC-Link Ver. 1.10/Ver. 2.00.


(This product cannot be used alone.)

Features


- Connects to the LE7-40GU-L tension controller to act as a remote device station for CC-Link V2.
- Can be built into the main unit, enabling more compact, faster installation.



Outline dimensions (mm)



- Mounting to the LE7-40GU-L tension controller



Specifications

● Basic specifications


Item		Specifications
Outline dimensions		50(H) × 68(W) × 38(D) mm
Weight		Approx. 0.2 kg
Power supply	Input	No input (supplied from LE7-40GU-L)
Communication		CC-Link Ver. 1.10/Ver. 2.00 remote device station

● Communication specifications

Item		Specifications
CC-Link supported version		Ver. 2.00 (Ver. 1.10 also supported)
Station type		Remote device station
Station No.		1 to 64*
Transmission speed		156 Kbps/625 Kbps/2.5 Mbps/5 Mbps/10 Mbps
Transmission distance		According to the CC-Link specifications. For details, refer to the manual of the master station.
Number of occupied stations		2 or 4
Setting items		Station number, Communication speed, number of occupied stations, and version setting
Transmission topology		Bus (RS-458)
Transmission format		HDLC compliant
Transmission cable		Cables dedicated to CC-Link (Ver. 1.10 compatible)

*: When the number of occupied stations is two, the maximum start station number is 63. When the number of occupied stations is four, the maximum start station number is 61.

● External connection



● Terminal layout

⏏	SLD	SLD	NC	DG	DB	DA	DG	DB	DA
---	-----	-----	----	----	----	----	----	----	----

Powder Clutch/Brake



Tension Controller

Clutch Amplifier

- Tension Meter/Tension Amplifier



Tension Detector



Common Item

LE-10WTA-CCL/LD-10WTB-CCL tension controller

Feedback control

Open-loop control

The LE-10WTA-CCL and LD-10WTB-CCL tension controllers offer various methods of tension control in combination with the tension detector input adapter and reel diameter calculation adapter connected to the main unit.



Features

● Highly advanced tension control

- Perform feedback control or open-loop control in accordance with the connected adapter. Highly precise tension controls with high response and stability are achieved by feedforward/feedback complex control brought by the combination of feedback control and open-loop control.
- Sophisticated tension control is achieved using the polygonal line taper function and inertia compensation gain automatic calculation based on the reel diameter data from the reel diameter calculation adapter and on the line speed/line acceleration data.
- The polygonal line taper function allows the setting of up to 8 points to enable detailed taper control in accordance with the material and reel diameter.

● Compliance with standards

- EN standard: EC directive/CE marking (EMC directive) compliant
- * For details, refer to the instruction manual.



● Tension control for up to 2 shafts

Tension control can be executed for up to 2 shafts when the optional adapter is installed.


● Diverse communication functions

- Because it comes with built-in CC-Link V2 remote device station functionality, it is possible to access the settings, monitor functionality, and correct the tension, including zero adjustment and span adjustment, over the CC-Link using a PLC, such as a master station.
- By connecting the optional LM-10WA-USB USB interface, you can use MX Sheet (Microsoft® Excel® support tool) to read tension values and write setting values through the PC.

● Improved support for motor control


Compatible with the input specifications of the inverter and servo amplifier to facilitate motor control.

The reel rotation speed output can be used as the speed limit when the LD-10WTB-DCA reel diameter calculation adapter is connected.




● Manipulation and display of settings from the panel using the graphic operation terminal for setting and monitoring


By connecting our GOT2000 series monitor display and installing the tension controller inside the panel, it is possible to change and monitor the settings through the display on the board surface.



Setting/monitoring display screen example




GOT connection




*3: GT21-C□□□R4-8P5 cannot be used.

Externally connected devices



The LE-10WTA-CCL is supplied with one tension detector input adapter as an accessory.
The LD-10WTB-CCL is supplied with one reel diameter calculation adapter as an accessory.

Outline dimensions (mm)



Exterior color: Munsell 0.08 GY/7.64/0.81 equivalent

Exterior color: Munsell 0.08 GY/7.64/0.81 equivalent

Specifications

● General specifications

Item		Specifications				
Operating ambient temperature		-5 to +55°C				
Storage ambient temperature		-25 to +75°C				
Operating ambient humidity		35 to 85% RH (no condensation)				
Vibration resistance		Installation	Frequency	Acceleration	Half amplitude	X, Y, Z 10 times in each direction (total 80 minutes each)
		DIN rail installation	10 to 57 Hz	–	0.035 mm	
			57 to 150 Hz	4.9 m/s ²	–	
		Direct installation	10 to 57 Hz	–	0.075 mm	
			57 to 150 Hz	9.8 m/s ²	–	
Impact resistance		98 m/s ² ... 3 times each in 3 axial directions				
Power noise withstand level		Noise voltage: 500 Vp-p, noise width 1 μs Measured by a noise simulator with frequency range of 30 to 100 Hz				
Withstand voltage		500 V AC for 1 minute ... (between all terminals together and the grounding terminal)				
Insulation resistance		5 MΩ or more when measured with 500 V DC insulation resistance tester ... (between all terminals together and the grounding terminal)				
Grounding		Class D grounding (100 Ω or less, common grounding with strong power field not possible)				
Operating environment		Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.				
Weight	LE-10WTA-CCL	Approx. 370 g				
	LD-10WTB-CCL	Approx. 380 g				
Installation method		DIN rail, wall surface, panel inside installation				

● Function specifications

Item		Specifications				
Power supply		24 V DC +20% -15%, power consumption 20 W, inrush current 20 A, 2 ms				
Input	Contact input	General-purpose contact input: 7 points				
	Analog input (voltage)	General-purpose analog input: 4 points				
Output	Power for variable resistor	5 V power for variable resistor				
	Contact output	General-purpose contact output: 3 points				
	Analog output (voltage)	General-purpose analog output: 4 points				
	Analog output (current)	General-purpose analog output: 2 points * In conjunction with analog output (voltage)				
Communication	GOT connection	RS-422 9P round DIN connector * Connection cable: GT10-C□□□R4-8P□				
	Serial communications	• RS-485: N:N networks, parallel link (FX3U, FX3UC, FX2N, FX2NC), MODBUS (RTU), MODBUS (ASCII) • USB: PC (MX Sheet) * Only when the communication interface (option) is connected. CC-Link and RS-485 communications cannot be used simultaneously.				
	CC-Link	Can be connected as a remote device station.				
	External memory	LD-8 EEPROM (option)				

[LM-10WA-TAD tension detector input adapter]


Item		Specifications				
Input	Compatible tension sensor	LX-TD/LX7-F tension detector, strain gauge (2 mV/V)				
	Power supply for tension sensor	+5 V DC, 20 mA				
Output	Tension lower limit contact output	Open collector output, 0.1 A (resistive load), 30 V DC or less				
	Tension upper limit contact input					
Weight		Approx. 80 g				

[LD-10WTB-DCA reel diameter calculation adapter]

Item		Specifications				
Input	Measuring pulse input	Frequency: 30 kHz or less				
	Reel shaft pulse input	Frequency: 200 Hz or less				
	Reel diameter reset input	ON current: Approx. 7 mA				
	Memory hold input					
Output	Encoder power supply	12 V DC ±0.5 V 90 mA or less				
	Proximity switch	12 V DC ±0.5 V 20 mA or less				
	Timing detection output 1 to 2	Open collector output, 0.1 A (resistive load), 30 V DC or less				
Weight		Approx. 90 g				


External connection

Main unit




LM-10WA-TAD

tension detector input adapter



LD-10WTB-DCA

reel diameter calculation adapter



LD-30FTA tension controller

Order production
from April 2024

End of September 2025
Scheduled completion
of production

Open-loop control

The LD-30FTA tension controller is an open-loop controller that operates on an integrated thickness monitoring method. This method first sets the initial diameter and material thickness to the control device and calculates the current reel diameter by subtracting (when unwinding) the material thickness from or adds (when winding) to the initial diameter every rotation of the winding reel shaft.

(A proximity sensor for rotation detection is attached in advance to the winding reel shaft.)

The calculation result is used to generate a voltage output of 0 to 24 V to the powder clutch/brake as an actuator and to generate a command voltage of 0 to 5 V to the servo amplifier.


Features

- Easy control and adjustment of tension with simple operation
 - Automatic control is possible by setting only the tension, material thickness, and initial diameter.
 - Supports a wide range from 100 V to 240 V AC.
 - A wide range of material thickness and initial diameter can be set.
 - Backup power function that stores the current reel diameter even if the power is turned off.
 - Supports various types of actuators such as an AC servo.
- Advanced function mode for various applications
 - Winding taper control is also possible.
 - Inertia compensation function during acceleration/deceleration.
 - Function for correction of torque nonlinearity of clutch/brake.
 - Mechanical loss correction function.
- Ease of use
 - Display of functions in Japanese, English, and pictograms.
 - Numerical value setting by dial operation.
 - High-function/easy mode switching function with built-in DIP switch.
 - 8 types of setting value storage function by menu
Up to 8 types of specific operation constants (such as material thickness, initial diameter, and taper ratio) can be stored.
 - Key locking key for prohibiting erroneous operation and display of invalid function.
- Ultrasonic sensor and touch lever input


Installing an optional analog input board (LD-30FTA-1AD) enables input from an ultrasonic sensor and touch lever. This eliminates the need for setting the material thickness and initial diameter for each material.



Panel screen configuration



Outline dimensions (mm)




Accessories: Main unit mounting plate: 1 pair


Body/mounting foot fixing screws (M4 × 10): 4 pieces

Exterior color: Munsell 7.5 GY 7.5/1

Panel cut dimensions



LD-30FTA-1AD option board (separately provided with a spacer)




Specifications

Item		Specifications	
Power supply	Input	100 to 240 V AC (-15 to +10%), 50/60 Hz, Power consumption: 300 VA, Power supply fuse: 250 V 8 A built-in, Inrush current: 50 A 10 ms	
	Output	Sensor power supply..... 12 V DC, 100 mA or less	
Pulse signal	Input	Reel shaft pulse.....Open collector signal: 12 V DC, 7 mA, Response frequency: 300 Hz or less 1, 2, 4, or 8 pulses can be set per rotation of reel shaft.	
Contact signal	Input	Run/stop.....ON: Run, OFF: Stop Output remote.....ON: Output generation, OFF: Output stop Reel diameter reset.....Reset to initial diameter during ON. Acceleration gain.....Acceleration gain is valid during ON. Forward/reverse.....ON: Reverse rotation, OFF: Forward rotation Deceleration gain.....Deceleration gain is valid during ON.	12 V DC, 7 mA/1 point Internal power feeding
Analog signal	Input	External reel diameter input0 to 10 V (when an LD-30FTA-1AD type option board is used) Ultrasonic sensor, touch lever potentiometer, etc.	
	Output	Clutch amplifier output24 V DC, 3 A (0%, -20%) or less Control signal output.....0 to 5 V DC, 5 mA or less, Load resistance: 1 kΩ or more	
Weight		Approx. 3.5 kg	
Installation method		Floor surface, wall surface, and panel mounting	
Environmental specifications	Operating ambient temperature	0 to 40°C	
	Operating ambient humidity	35 to 85% RH (no condensation)	
	Vibration resistance	10 to 55 Hz, 0.5 mm (up to 4.9 m/s ²), 2 hours each in 3 axial directions	
	Impact resistance	98 m/s ² 3 times each in 3 axial directions	
	Power noise withstand level	Noise voltage 1000 Vp-p, using a noise simulator with noise width of 1 μs and frequency of 30 to 100 Hz	
	Withstand voltage	1500 V AC for 1 minute (between all terminals together and the grounding terminal)	
	Insulation resistance	500 V DC, 5 MΩ or more when measured with insulation resistance tester	
	Grounding	Class D grounding, grounding resistance 100 Ω or less	
Major functions		Reel diameter detection.....Integrated thickness calculation method, external analog signal (ultrasonic sensor, etc.) Tension control.....Constant tension control, taper control (straight line) Control function.....Stop timer, stop gain, stop bias, acceleration/deceleration gain, mechanical loss correction, weak excitation function torque Nonlinear correction.....Polygonal line approximation corrections in 5 steps. Setting by correction number input for each clutch/brake.	


Parameter list

Setting item	Setting item		Initial value	Unit	Function mode
	Minimum	Maximum			
Tension setting	0	100	-	%	Easy/high-function
Material thickness setting	1/0.1	9,999/999.9	50	μm	Easy/high-function
Initial diameter setting	1	2000	500	mm	Easy/high-function
Taper setting	0	100	100	%	High-function
Stop timer setting	0.0	100.0	0.0	sec	High-function
Stop gain setting	5	400	100	%	High-function
Stop bias setting	0	50	0	%	High-function
Deceleration gain setting	5	400	100	%	High-function
Acceleration gain setting	5	400	100	%	High-function
Mechanical loss setting	0	50	0	%	High-function
Weak excitation setting	0	50	0	%	High-function
Setting the number of reel shaft pulses	1, 2, 4, 8		1	-	High-function
Nonlinear correction setting	0	200	0	-	High-function
Minimum diameter setting	1	Maximum diameter setting value	100	mm	Easy/high-function
Maximum diameter setting	Minimum diameter setting value	2000	500	mm	Easy/high-function

External connection



Terminal layout




LSA, LSB, and LSG are not used.

Application examples

● Using a proximity switch

This is a control example of the winding part for intermittent feed to enable punching with the material feed stopped.
In spite of intermittent feed, the take-up motor is continuously rotating and the clutch continues to apply tension while slipping.



Reel diameter $D = \phi 92 \rightarrow \phi 500$ mm
Material Paper (thickness 200 μ m)

Other possible uses

- Hot stamping
- Screen-printing

1. DIP switch setting (required only at initial setting; not required during normal operation)

	1	2	3	4	5	6	7	8
ON	Unwinding	$\times 1$	Disabled	Disabled		Normal	Easy	Run
DIP switch	Control reel	Thickness unit	Reel diameter input	Output remote	(Unavailable)	Memory initialization	Function mode	Operation mode
OFF	Wind	$\times 0.1$	Enabled	Enabled		Initial-ization	High-function	Adjust-ment

(Initial setting status)

	1	2	3	4	5	6	7	8
ON	Unwinding	$\times 1$	Disabled	Disabled		Normal	Easy	Run
DIP switch	Control reel	Thickness unit	Reel diameter input	Output remote	(Unavailable)	Memory initialization	Function mode	Operation mode
OFF	Wind	$\times 0.1$	Enabled	Enabled		Initial-ization	High-function	Adjust-ment

* For normal operation, set the DIP switch for the operation mode to [Run].

2. Maximum diameter setting

(Required only at initial setting; not required during normal operation)

- (1) Select the maximum diameter with the setting switching key (8) and enter “ $\phi 500$ ” with the pulser.
- (2) Set the operation mode of the DIP switch to “RUN,” and turn the power off and turn it on again.

3. Setting procedure

(Setting is required only when the material is changed.)

- (1) Press the “Material thickness Setting” key (7), and enter the material thickness “200 μ m” with the pulser.
- (2) Press the “Initial setting” key (6), and enter the reel diameter “ $\phi 92$ ” with the pulser.
- (3) Press the “Reel diameter initialization” key (3).

4. Test run procedures

(Required only at initial setting; not required during normal operation)

- (1) Press the “Manual Mode Selection” key, and turn on the output ON/OFF switch.
- (2) Check the functions of the connected devices such as the motor and PLC.

5. Automatic operation procedure

- (1) Press the “Automatic Control Mode Selection” key.
- (2) Adjust the tension with the tension-setting variable resistor.

- Maximum reel diameter display



- Reel diameter display



- Material thickness display




- Reel diameter display



● Using an ultrasonic sensor

Winding laminating film for the upper and lower sides of the base material. Tension is kept constant at the laminating area to prevent warps and wrinkles, and to improve bonding during lamination. An open-loop type tension controller is used because there is no space for a tension detector. The reel diameter is detected by the ultrasonic sensor, so the initial diameter and wire diameter do not need to be set.



1. DIP switch setting (required only at initial setting; not required during normal operation)

	1	2	3	4	5	6	7	8
ON	Unwinding	$\times 1$	Disabled	Disabled		Normal	Easy	Run
DIP switch	Control reel	Thickness unit	Reel diameter input	Output remote	(Unavailable)	Memory initialization	Function mode	Operation mode
OFF	Wind	$\times 0.1$	Enabled	Enabled		Initial-ization	High-function	Adjust-ment

(Initial setting status)

	1	2	3	4	5	6	7	8
ON	Unwinding	$\times 1$	Disabled	Disabled		Normal	Easy	Run
DIP switch	Control reel	Thickness unit	Reel diameter input	Output remote	(Unavailable)	Memory initialization	Function mode	Operation mode
OFF	Wind	$\times 0.1$	Enabled	Enabled		Initial-ization	High-function	Adjust-ment

* For normal operation, set the DIP switch for the operation mode to [Run].

2. Teaching operation

(Required only at initial setting; not required during normal operation)

- (1) Select the minimum diameter with the setting switch key, set the minimum diameter "φ75" with the pulser, install the smallest diameter winding reel (φ75), and press the reel diameter initialization key.
- (2) Select the maximum diameter with the setting switch key, set the maximum diameter "φ450" with the pulser, install the maximum diameter winding reel, and press the reel diameter initialization key.
- (3) Set the operation mode of the DIP switch to "RUN," and turn the power off and turn it on again.

3. Manual operation procedures



(Required only at initial setting; not required during normal operation)

- (1) Press the "Manual Mode Selection" key, and turn on the output ON/OFF switch.
- (2) Check the functions of the connected devices such as the motor and PLC.


4. Automatic operation procedure

- (1) Press the "Automatic Control Mode Selection" key.
- (2) Adjust the tension with the tension-setting variable resistor.

● Minimum diameter display



● Maximum diameter display



LD-05TL tension controller

Order production
from April 2024

End of September 2025
Scheduled completion
of production

Open-loop control

The LD-05TL tension controller receives power from the 24 V DC general-purpose stabilized power supply and controls unwinding/winding tension by inputting an analog system reel diameter signal such as a potentiometer linked with the touch lever. Since the reel diameter signal processing block and the constant current (constant voltage) amplifier block are separated, it can be used only as an amplifier. This controller is used in combination with a powder clutch/brake of 24 V DC, 0.5 A or less.

Features

- Tension control using the touch lever

Tension control is enabled with the touch lever using the potentiometer. Automatic operation is enabled by only tension setting with the external variable resistor.

- Usable as a clutch amplifier such as for powder clutch/brake


This controller can be used as a clutch amplifier such as for powder clutch/brake by using a PLC or other kind of controller.

- Stable output characteristics against temperature fluctuation


Stable torque can be obtained by constant current control.
(Constant voltage control is also usable.)

- Not loose when stopped

The external contact signal enables inertia compensation such as powering up, powering down, and powering addition.



Outline dimensions (mm)



Exterior color: Munsell 0.08GY 7.64/0.81

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector

Common Item


Specifications

Item		Specifications	
Power supply		24 V DC ±15%	
Analog signal	Input	Reel diameter signal····· Input one of the following voltage signals between the minimum diameter and maximum diameter. 0 to 5 V Internal resistance: 50 kΩ 0 to 8 V Internal resistance: 80 kΩ 0 to 10 V Internal resistance: 100 kΩ Tension setting signal····· 0 to 5 V Internal resistance: 190 kΩ	
	Output	Control output ·········· For the tension setting signal 0 to 5 V Current output··········· 0 to 0.5 A DC (in constant current control mode) Voltage output··········· 0 to 22 V DC (in constant voltage control mode)	
Contact signal	Input	Output correction signal • For powering up········· Output multiplication of Approx. 100% to 500% • For powering down······· Output multiplication of Approx. 0% to 100% • For powering addition····· Approx. 0 to 0.1 A (in constant current control mode) Output addition of Approx. 0 to 4.4 V (in constant current control mode) Constant voltage/constant current switching signal	24 V DC, 7 mA
	Output	Reel diameter detection output • ON when reel diameter equals or underruns the set value. Open collector output: 30 V DC, 0.2 A or less	
Weight		Approx. 220 g	
Installation method		Installed on wall with two M4 screws or installed on DIN rail (width: 35 mm)	
Environmental specifications	Operating ambient temperature	0 to 55°C	
	Operating ambient humidity	35 to 85% RH or less (no condensation)	
	Vibration resistance	10 to 55 Hz, 0.5 mm (up to 19.6 m/s ²), 2 hours each in 3 axial directions	
	Operating environment	Free from corrosive and flammable gases as well as dust. Free from rain and water drops.	


Note: Since the maximum output voltage of this product is approx. 20.5 V (85% of the rated voltage) or more when the power supply voltage is 24 V, and approx. 17.5 V (72% of rated voltage) or more when the power supply voltage is 20.4 V (24 V - 15%), select a clutch or brake with a sufficient torque margin.

External connection

- For control with a potentiometer attached to the touch lever



- For control with an external analog voltage signal as a clutch amplifier



LE-50PAU power amplifier

The LE-50PAU power amplifier is used for controlling exciting current such as for a powder clutch/brake. It is thus used as a clutch amplifier for a tension controller not incorporating a clutch amplifier or for controlling with the constant current control method.

Features

● Constant current/constant voltage control method

Both constant-current and constant-voltage control are supported (setting is switched with the built-in DIP switch). Constant-current control can eliminate the effects of torque fluctuations that are caused by a rise in powder clutch/brake coil temperature and enable more stable tension control. In a system with multiple powder clutches/brakes that are connected in parallel in which the current is distributed by a variable resistor, constant-voltage control allows easier adjustment than constant-current control.

● Nonlinear correction function of torque characteristics

The powder clutch/brake's non-linear transmission torque to exciting current characteristic is compensated in five stages. Fluctuation of tension caused by the change in reel diameter can be minimized.

● Variable input signal level setting



The input signal voltage level can be set to 0 to 5 V, 0 to 8 V, or 0 to Vmax (Vmax can be set to a level between 0.5 and 8 V).

● Built-in setting display function

4-digit LED display, 4 push buttons, and 10-position dipswitches allow for easy setting of input signal level, output full-scale value, and nonlinearity compensation data. Inertia compensation or output can also be displayed during control.



Outline dimensions (mm)




Exterior color: Munsell 7.5 GY 7.5/1

Specifications

Item		Specifications		
Power supply	Input	100 to 240 V AC (-15 to +10%), 50/60 Hz, Power consumption: 400 VA, Power supply fuse: 250 V 8 A built-in, Inrush current: 50 A 10 ms		
	Output	Power for variable resistor:..... 8 V DC Variable resistor resistance: 500 Ω to 2 kΩ Reel shaft sensor power supply 12 V DC, 15 mA or less		
Contact signal	Input	Start.....When turned off, the stop timer activates to perform inertia compensation operation. Output remote ON: Output generation, OFF: Output stop Auxiliary output ON/OFF ON: Auxiliary output occurrence	12 V DC 5 mA/1 point Internal power feeding	
Analog Signal	Input	Control signal 0 to 8 V, Internal resistance: 22 kΩ		
	Output	Power amplifier output 24 V DC, 4 A or less Auxiliary output:..... 10 V DC, 2 A or less, within 30 seconds, Load resistance: 6 Ω or more/75°C		
Weight		Approx. 2.5 kg		
Installation method		Wall-mounted		
Environmental specifications	Operating ambient temperature		0 to 55°C	
	Operating ambient humidity		35 to 85% RH (no condensation)	
	Vibration resistance		10 to 55 Hz, 0.5 mm (up to 19.6 m/s ²), 2 hours each in 3 axial directions	
	Impact resistance		98 m/s ² 3 times each in 3 axial directions	
	Power noise withstand level		Noise voltage 1000 Vp-p, using a noise simulator with noise width of 1 μs and frequency of 30 to 100 Hz	
	Withstand voltage		1500 V AC for 1 minute	Between all terminals together and the grounding terminal
	Insulation resistance		500 V DC, 5 MΩ or more when measured with insulation resistance tester	
	Grounding		Class D grounding, grounding resistance 100 Ω or less	
	Operating environment		Environment must be free of corrosive gases, flammable gases as well as conductive dust, and must have low levels of dust. Free from rain and water drops.	

External connection



Terminal layout

			SET	SP	SN	ST	SC	PL	12 V		S2	S1
L	N		SN	SG	RS	SN	RC	SN		PN	PP	

LD-40PSU power supply unit

Order production
from April 2024

End of September 2025
Scheduled completion
of production

The LD-40PSU power supply unit is a constant voltage control type clutch amplifier for a powder clutch/brake that varies the voltage based on the variable resistor on the panel surface, signal voltage from the outside, external variable resistor, etc.

Features

- External control signal (remote ON/OFF)

With an external signal of 0 to 5 V, output voltage can be controlled remotely in the range of 0 to 24 V.

- Output ON/OFF function

Output can be turned on or off with the buttons on the panel or by using the external remote contact signal (RC signal).

- Inertia compensation function

In the manual tension control mode, stop timer operation and inertia compensated output in response to the RC signal are possible.

- Load short-circuit protection/warning


The short-circuit protection circuit is triggered by a load short-circuiting. The LED on the panel turns on when the circuit is triggered.

- 2-level output setting

This device can be set to supply 2 different levels of output voltage: one with and the other without RC input. The one without the RC input can be set to provide weak excitation, etc.




Outline dimensions (mm)



Mounting screw hole dimensions
for floor mounting



Panel cut dimension
for panel mounting




Accessory: A pair of mounting plates
4 screws (M4 x 10)

Exterior color: Munsell 7.5 GY 7.5/1 equivalent

Specifications

Item		Terminal name	Specifications
Power supply		L/N	100 to 240 V AC (+10%, -15%), 50/60 Hz Power consumption: 200 VA (at 24 V DC, 3.8 A)
Output	Clutch amplifier output	PP/PN	24 V DC 3.8 A (0%, -15%) or less
	Power for variable resistor	+5 V/SN	5 V DC, 10 mA or less, External variable resistor: 0.5 to 2 k Ω
Input	Analog signal	SP/SN	Control input signal: 0 to 5 V DC
	Contact signal	RC/SN	Remote output ON/OFF, 12 V DC/mA internal power feeding
Weight		Approx. 3 kg	
Environmental specifications	Ambient temperature	-5 to +55°C	
	Ambient humidity	35 to 85% RH (no condensation)	
	Vibration resistance	10 to 55 Hz, 0.5 mm (up to 4.9 m/s ²), 2 hours each in 3 axial directions	
	Impact resistance	98 m/s ² 3 times each in 3 axial directions	
	Power noise withstand level	Noise voltage 1000 Vp-p, using a noise simulator with noise width of 1 μ s and frequency of 30 to 100 Hz	
	Withstand voltage	1500 V AC for 1 minute Measure between all terminals together (excluding grounding terminal) and the ground terminal, and between all terminals together (excluding grounding terminal) and the mounting bracket.	
	Insulation resistance	5 M Ω or more when measured with 500 V DC insulation resistance tester (between all terminals together and the grounding terminal)	
	Grounding	Class D grounding (100 Ω or less, common grounding with strong power field not possible)	
	Operating environment	Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.	

External connection



● Terminal layout

L	•	N	•		SG	RC	SN	SP	+5V	PN	PP
---	---	---	---	--	----	----	----	----	-----	----	----

LD-10PAU power amplifier

The LD-10PAU-□ power amplifier is used for a dedicated clutch for controlling the exciting current of 24 V DC of small powder clutches/brakes, which are used in devices that perform tension control such as wire, paper, or film manufacturing machines.

The constant-current control method achieves constant output current and constant generated torque even if the coil resistance changes due to fluctuations in the clutch/brake temperature to realize stable control with high precision.



Features

- Equipped with functions required in simultaneous multi-shaft control.

Small clutches/brakes are used not only for low tension single shaft control, but also for multiple-shaft simultaneous control using multiple units on one machine. This power amplifier compensates for the mechanical friction of each shaft and the difference in clutch/brake characteristics, which are problems caused in such control, and achieves stable control.

Space-saving installation by left/right close attachment to the DIN rails.

- 16 types of output torque command and inertia compensation gain can be registered and switched

Sixteen types of output torque command value and inertia compensation gain value can be stored in the internal memory. Registration memory can be externally switched from the external digital binary ON/OFF signal, the FX PLC (only LD-10PAU-B compatible) connected to RS-485, or the display (GT2103).

- Allows selection of the output current command to suit the purpose of use.

- (1) Analog input (0 to 5 V, 0 to 10 V)
- (2) Digital binary ON/OFF signal input (8 bits + Strobe)
- (3) Key input from the surface → Internal memory (16 types can be set)
- (4) Input from the graphic operation terminal → Internal memory (16 types can be set)
- (5) Input from the PLC (through RS-485 communication) → Internal memory (16 types can be set, supported only in the LD-10PAU-B)

- Incorporates a correction function for the nonlinear torque characteristics of clutches and brakes.




A nonlinear correction function corresponding to the current-torque characteristics of Mitsubishi Electric clutches and brakes is built in. The rated current and nonlinear correction initial value can be set simply by setting the model number of the clutch/brake to be connected.

- Mitsubishi Electric display available for setting/monitoring

Mitsubishi Electric monitor display (GT 2103) can be connected.
(Connection cable: GT10-C□□□R4-8P□)

For the sample screen data for the GOT, consult your local Mitsubishi Electric representative.

In addition, the screen creation software (GT Designer2 or GT Designer3) can be used to customize the screen and create an original-design screen.



- Can change absence/presence of the output cushion operation using the external contact input

The output current can be cushioned and turned on and off as a countermeasure against residual torque ripple in hysteresis clutches and brakes.

- Equipped with open-loop control mode using analog reel diameter signal

Open-loop control is available using the analog reel diameter signal by selecting the tension controller mode.


The tension can be controlled using the reel diameter signal sent from the potentiometer or ultrasonic sensor attached to the touch lever.

- The system including clutches and brakes can be totally controlled when a PLC is connected


The LD-10PAU-B incorporating RS-485 communication can give output commands to the clutch amplifier and monitor the status when the FX series PLC (with N:N network function) is connected. This function makes it easy to control the clutch/brake including overall control of the device and to perform program development in multiple-shaft simultaneous control.

- Easy setup of multiple clutch amplifiers using the memory cassette

Various settings can be copied and read when the optional memory cassette is attached. Various settings can be automatically backed up at the time of startup when the memory cassette is attached.




Parts names and terminal signal information




Outline dimensions (mm)

● LD-10PAU-A



● LD-10PAU-B




* When using the GOT display communication connector (CN5) and digital input connector (CN1), secure a space of 50 mm or more on top of the main unit.

Specifications

Item		Specifications				
Power supply	Input	24 to 29 V DC, power consumption: 40 VA, inrush current: 30 A 1 ms, allowable momentary power failure time: 5 ms				
	Output	Service power supply for external control: 5 V DC (external resistance of 0.5 to 2 kΩ), 10 mA or less				
Contact signal	Input	Control output remote ON/OFF (ON: Output OFF, OFF: Output ON)			ON current =	
		Output cushion operation ON/OFF (ON: Cushion disabled/OFF: Cushion enabled)			Approx. 5 mA	
		Inertia compensation gain Enable/Disable				
	Output	Digital input (12-pin connector) Parallel torque setting or external torque selection (low-order 4 bits), inertia compensation gain selection (high-order 4 bits) Memory value selection			ON current =	
			Approx. 5 mA			
Analog Signal	Input	Torque (tension) setting Input resistance: 36 kΩ			0 to 5 V, 0 to 10 V switching, with	
		Select from “output inertia compensation gain setting, inter-shaft correction gain setting, reel diameter input.” Input resistance: 36 kΩ			250 Ω external resistor 4 to 20 mA supported	
	Output	Output%monitor output 0 to 2 V, 0 to 5 V, 0 to 10 V switching, Load resistance: 1 kΩ or more				
Control output		Powder clutch/brake for 24 V DC system, 24 V DC, 0 to 1.0 A				
Weight		300 g				
Installation method		DIN rail, floor surface, wall surface mounting				
Environmental specifications	Operating ambient temperature	-5 to +55° C				
	Operating ambient humidity	35 to 85% RH (no condensation)				
	Storage temperature range	-25 to +75° C				
	Vibration resistance	DIN rail installation	Frequency	Acceleration	Half amplitude	10 times each in 3 axial directions (total 80 minutes each)
			10 to 57 Hz	—	0.035 mm	
		Direct installation	57 to 150 Hz	4.9 m/s ²	—	
			10 to 57 Hz	—	0.075 mm	
		57 to 150 Hz	9.8 m/s ²	—		
		Impact resistance	98 m/s ² 3 times each in 3 axial directions			
	Power noise withstand level	Noise tolerance 500 Vp-p, using a noise simulator with noise width of 1 μs and frequency of 30 to 100 Hz				
	Withstand voltage	500 V AC for 1 minute (between all terminals together and the grounding terminal)				
	Insulation resistance	5 MΩ or more when measured with 500 V DC insulation resistance tester (between all terminals together and the grounding terminal)				
	Grounding	Class D grounding (100 Ω or less, common grounding with strong power field not possible)				
Operating environment	Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.					


External connection



Precaution

1. Connect a fuse (2 A) to the outside for protection from short-circuit between 24 V and GND of CN1.
2. When a short circuit occurs between PP and PN, output is shut down for product protection.
3. When shutting off the control output externally by using relays or switches, the short-circuit protection circuit is activated by back EMF. So, provide a commutation circuit between PP and PN.

(Example) Switching of 2-shaft clutch/brake



● Terminal layout

⏏	DIC	CUS	SN	SP2	MON	OCN	PN
24G	24V	REM	GAN	+5V	SP1	OCP	PP

LM7-1LG/LM7-2LG tension meter

This tension meter is capable of displaying and outputting signals for tension detected by LX tension detectors and strain gauge sensors to external devices. Quick detection of fluctuations in tension is also possible using CC-Link IE TSN communication, ensuring highly accurate tension control.

Features

● CC-Link IE TSN support

- CC-Link IE TSN Class B/A is supported.
CC-Link IE TSN communication enables high-frequency tension acquisition at a maximum of 1 ms/axis cycle*, enabling quick detection of tension fluctuations even during acceleration and deceleration when tension fluctuations tend to be large.
- * When connected to a CC-Link IE TSN Class B-compliant master device via the LM7-1LG.

● SLMP communication support

- Tension data and various control information can be read from other devices that support SLMP communication.

● PC-based data management

- A CC-link IE TSN configuration tool (free) is available to set, duplicate, and save parameters, helping to reduce startup and maintenance costs.

● Compatible with a wide range of tension detectors



- Connection to not only Mitsubishi Electric LX tension detectors but also strain gauge load cells (applied voltage: 10 V DC) is possible, allowing users to select the sensor that best suits the application.

● Available in 1- and 2-shaft tension detectors

- Choose from the LM7-1LG (with a single tension detection shaft) or the LM7-2LG (with dual tension detection shafts) for use in various applications according to the equipment configuration.



Parts names



Specifications

● General specifications

Item	Specifications				
Operating ambient temperature	0 to 55°C (no freezing)				
Storage ambient temperature	-25 to +75°C (no freezing)				
Operating ambient humidity	5 to 95% RH (no condensation)				
Storage ambient humidity	5 to 95% RH (no condensation)				
Vibration resistance*1	Installation method	Frequency	Acceleration	Half amplitude	Sweep count
	Panel mounting	5 to 8.4 Hz	—	1.75 mm	10 times in each of X, Y, and Z directions (total 80 minutes each)
		8.4 to 150 Hz	4.9 m/s ²	—	
Impact resistance*1	147 m/s ² , action time 11 ms, 3 times in each of X, Y, and Z bi-directions with half-sine pulse				
Noise tolerance	Noise voltage 1000 Vp-p, using a noise simulator with noise width of 1 μs and frequency of 30 to 100 Hz				
Withstand voltage	500 V AC for 1 minute (between all terminals together and the grounding terminal)				
Insulation resistance	10 MΩ or more using 500 V DC insulation resistance tester				
Grounding	Class D grounding (grounding resistance: 100 Ω or less) <common grounding with strong power field not possible>				
Operating environment	Environment must be free of corrosive or flammable gases, and must have low levels of conductive dust				
Operating altitude*2	0 to 2000 m				
Installation place	In control panel*3				
Overvoltage category*4	II or lower				
Pollution degree*5	2 or lower				
Weight	Approx. 0.4 kg				

*1: The criterion is shown in IEC 61131-2.

*2: Cannot be used in environments with pressure above atmospheric pressure. If used, there is a risk of failure.

*3: The tension controller is designed for installation in indoor-equivalent environments.

*4: Indicates the distribution section to which the device is expected to be connected, ranging from the public power distribution network to the on-site machinery. The category applies to devices powered from fixed installations, etc. The surge voltage withstand capability of devices rated up to 300 V is 2500 V.

*5: This indicator shows the degree of dielectric material presence in the environment where the device is used. Pollution degree 2 indicates that only non-conductive pollution is present. However, the environment may experience temporary conductivity due to incidental condensation.

● Power supply specifications

Item	Specifications
Power supply voltage	24 V DC
Voltage fluctuation range	+20%, -15%
Permissible momentary power outage duration	5 ms or less
Inrush current	Within 90 A, 400 μs
Current consumption	LM7-1LG: 350 mA LM7-2LG: 460 mA

● Sensor connection specifications

Item		Specifications					
Sensor power supply	Power supply voltage	5 V DC ±4%, 10 V DC ±4%					
	Output current	60 mA/shaft					
Number of shafts to measure		LM7-1LG: 1 LM7-2LG: 2					
Number of sensor input points		2 points/shaft					
Update interval*1		1 ms/shaft					
I/O characteristics*2, resolution		Sensor input type	Sensor rated output	Input range (Sensor input practical range)	Digital output value		Resolution
					Tension value*3	Tension input voltage value	
		LX tension detector manufactured by Mitsubishi Electric	±150 mV	-200 to 200 mV	0 to full scale tension	-20000 to 20000	10 μV
		Distortion gauge sensor (sensor power supply: 10 V DC)	±2.1 mV/V or less	-23.0 to 23.0 mV	0 to full scale tension	-23000 to 23000	1 μV
Accuracy*4	Non linearity (ambient temperature 25°C)	Within ±0.5% (±200 mV range: ±200 digits, ±23 mV range: ±230 digits)					
	Temperature drift (ambient temperature 0 to 55°C)	Within ±0.01%/°C (±200 mV range: ±4 digits/°C, ±23 mV range: ±5 digit/°C)					
Absolute maximum input		±7.0 V					

*1: The update interval refers to the cycle at which the CC-Link IE TSN remote registers corresponding to tension values (total/left/right tension) and input voltage values (left/right tension) are updated.

*2: For details on input/output characteristics, refer to the product manual.

*3: Digital output value based on the settings for tension decimal point and tension unit.

*4: The accuracy relative to the full scale of the digital output value (tension input voltage) (±200 mV range: 40000 digits, ±23 mV range: 46000 digits).

● Analog output specifications



Item	Specifications		
Number of output points	LM7-1LG: 3 points (voltage output and current output selectable at each point) LM7-2LG: 6 points (voltage output and current output selectable at each point)		
Function	Tension in total, on the left side, on the right side		
Update interval*1	10 ms		
Load resistance	Voltage: 1 k Ω to 1 M Ω , current: 500 Ω or less		
Output characteristics, resolution*2	Analog output range		Resolution
	Voltage	0 to 5 V	1.0 mV
		1 to 5 V	0.8 mV
		0 to 10 V	2.0 mV
	Current	0 to 20 mA	4.0 μ A
		4 to 20 mA	3.2 μ A
Accuracy*3	Ambient temperature 25 $\pm$ 5°C: Within $\pm$ 0.1% (voltage output: $\pm$ 10 mV, current output: $\pm$ 20 μ A) Ambient temperature 0 to 55°C: Within $\pm$ 0.2% (voltage output: $\pm$ 20 mV, current output: $\pm$ 40 μ A)		

*1: The interval at which 3 points of analog output are updated for LM7-1LG and 6 points for LM7-2LG.

*2: For details on analog output characteristics, refer to the product manual.

*3: The accuracy relative to the full scale of the analog output range (voltage output: 10 V, current output: 20 mA).

● Contact output specifications

Item	Specifications	
Number of output points	LM7-1LG: 1 point, LM7-2LG: 2 points	
Function	Total tension upper limit detection, total tension lower limit detection, and total tension upper/lower limit detection selectable	
Output format	Sink/source	
External power supply	5 to 30 V DC	
Maximum load	0.1 A/point	
Leakage current when open	0.1 mA or less at 30 V DC	
Voltage drop when ON	1.0 V or less	
Output response time	800 μ s or less	
Output wiring	Sink output wiring	Source output wiring
	 Output load driving power supply 5 to 30 V DC	 Output load driving power supply 5 to 30 V DC

● Ethernet communication specifications

Item	Specifications	
Data transmission speed	• 1 Gbps • 100 Mbps	
Communication mode	1000BASE-T 100BASE-TX	Full duplex
Interface	RJ45 connector (AUTO MDI/MDI-X)	
Maximum frame size	1518 bytes	
Maximum segment length	100 m*1	
Number of cascade stages	1000BASE-T 100BASE-TX	Please check with the manufacturer of the switching hubs to be used.
IP version	IPv4	

*1: For the maximum segment length (the distance between switching hubs), please check with the manufacturer of the switching hubs to be used.

● CC-Link IE TSN performance specifications


Item	Specifications	
Station type	Remote station	
Communication speed	• 1 Gbps • 100 Mbps	
CC-Link IE TSN Class	• CC-Link IE TSN Class B • CC-Link IE TSN Class A	
CC-Link IE TSN protocol version	CC-Link IE TSN protocol version 2.0	
Maximum response time for time-managed polling (for CC-Link IE TSN Class A)	512 μ s	
Transmission topology	Line connection, star connection, a mix of star and line connections, ring connection*1	
Multicast filter	Supported	

*1: Ring connection is only available for CC-Link IE TSN Class B.

● SLMP performance specifications

Item	Specifications
Supported frames	3E frame, 4E frame, station number extension frame
TCP IP/UDP IP	UDP IP
Code	Binary code
Port number	45239

External connection




*1: Two terminals are provided for both [24V] and [24G], and power can be supplied by connecting one side to another device (cross-wiring). However, the total current consumption of connected devices, including this product, should not exceed 1.5 A.

*2: Please ground the earth terminal and FG terminal independently since they are not connected internally within the product.

*3: Used only by LM7-2LG.

Outline dimensions (mm)



Exterior color: Munsell N1.5 equivalent
Accessories: mounting brackets/screws (2 each)

LM-10WA-CCL tension meter

This tension meter features flexible expandability, and supports centralized control using a network and communication for systems requiring multiple tension controls in machines that process and manufacture not only general materials such as films, metallic foils, paper, foods and electric wires but also special films and metallic foils used in lithium ion batteries, solar batteries, LCD panels, etc.

Features

- Allows detector inputs for up to 4 shafts



The LM-10WA-CCL tension meter is supplied together with one LM-10WA-TAD tension detector input adapter.

Adding a tension detector input adapter (option) enables inputs from the tension detectors of up to 4 shafts.


- Compliance with standards

EN standard: EC directive/CE marking (EMC directive) compliant

* For details, refer to the instruction manual.




- Easy display and tension meter operation setting also enabled with internal display



- Connecting to a GOT display enables display and operation with custom screens from the panel.

By using the drawing software for the GOT2000 series, original tension display and setting change screens can be created.

For the sample screen for the GT2103, consult your local Mitsubishi Electric representative.



● Digital I/O terminals and analog output terminals Supports actual voltage display of tension detector

■ Digital input

- RDY input and alarm reset input
- Free setting output: Set up to 3 of the following functions: (RDY output, excessive input, left/right monitor unbalance, large inter-CH data deviation, network alarm generation, system alarm generation)

■ Analog outputs

- Voltage output (CH1 to CH4): 4-point output range selectable
- Current output (CH1 to CH4): 4-point output range selectable

■ Actual voltage of the tension detector

The built-in display displays the actual voltage of the tension detector. Signals can be checked easily when a problem occurs.

● Functions that enhance ease of use

■ Alarm history function

Up to 8 alarms are saved as history. The alarm notification method and action can be set.

■ Password protection function

Change of “unchangeable items in RDY state” can be disabled.

■ Reading from and writing to Microsoft® Excel® using MX Sheet

The optional MX Sheet is available to read the tension and write the setting value to Microsoft® Excel®.



■ Backup function and setting value copy function using the memory cassette

The tension meter setting values can be automatically backed up. In addition, the setting values can also be copied to multiple tension meters.

● Equipped as standard with the remote device station function of CC-Link V2 (Ver. 1.10 and Ver. 2.00) Easy connection to FX series PLC via RS-485 communication interface


It is easy to centrally manage the tension with the PLC, check the alarm of the tension meter, and change/adjust the setting. The remote device station function of open field network CC-Link V2 for connecting various FA equipment in wire-saving mode is included as standard.

By attaching an optional RS-485 communication interface (LM-10WA-485), the unit can be easily connected to the FX series PLC as a “slave station for N:N networks.”




Outline dimensions (mm)

● LM-10WA-CCL




Exterior color: Munsell 0.08GY/7.64/0.81

● Option: Tension detector input adapter LM-10WA-TAD



Exterior color: Munsell 0.08GY/7.64/0.81

External connection



Specifications

Item	Specifications			
Ambient temperature	Operating: -5 to +55°C, Storage: -25 to +75°C			
Operating ambient humidity	35 to 85% RH (no condensation)			
Vibration resistance (total 80 minutes each)	DIN rail installation	Frequency	Acceleration	Half amplitude
		10 to 57 Hz	—	0.035 mm
	Direct installation	57 to 150 Hz	4.9 m/s ²	—
		10 to 57 Hz	—	0.075 mm
Impact resistance	98 m/s ² 3 times each in 3 axial directions			
Power noise withstand level	Noise voltage 500 Vp-p, using a noise simulator with noise width of 1 μs and frequency of 30 to 100 Hz			
Withstand voltage	500 V AC for 1 minute (between all terminals together and the grounding terminal)			
Insulation resistance	5 MΩ or more when measured with 500 V DC insulation resistance tester (between all terminals together and the grounding terminal)			
Grounding	Class D grounding (100 Ω or less, common grounding with strong power field not possible)			
Operating environment	Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.			

[LM-10WA-CCL specifications]

● Function specifications

Item		Specifications
Setting procedure		Parameters can be set by button operation on the internal setting display.
Tension signal	Number of input channels (Up to 4 channels)	Main unit: Equipped with 1-channel tension detector input adapter as standard (One detector alone as well as one each on the right and left) Option: Up to 3 channels of tension detector input adapters can be added.
	Support sensor	LX-TD/LX7-F tension detector, strain gauge (2 mV/V)
	Power supply for sensor	Built-in 5 V DC, 20 mA
	Alarm output	Tension lower limit detection, tension upper limit detection
Tension display	Built-in display	7-segment display on the built-in display (display by switching 1 to 4 channels by button operation)
	Analog outputs	Analog voltage output, analog current output (output range switchable)
	Others	- Display by GOT display - Reading from master station by CC-Link connection - Reading from master station by simple inter-PC link connection with FX PLC
Digital input signal		2 points (RDY input and alarm reset input)
Digital output signal		4 points (select output functions from "RDY output, excessive input, left/right monitor unbalance, large inter-CH data deviation, input adapter bus alarm, and input adapter memory alarm")
GOT communication interface		RS-422 port: 1 channel Mitsubishi Electric GOT: Compatible with GT1020, GT1030, GT2103, and GT2104 Connection cable: GT10-C□□R4-8P□ (When the unit is connected without power supply wiring, a cable length of up to 3 m is allowed.)
CC-Link communication interface	Station type	Remote device station
	Number of occupied stations	One tension detector adapter occupies one station.
	CC-Link version	Ver. 1.10 / Ver. 2.00
Option	Tension detector input adapter	Up to 3 LM-10WA-TAD tension detector input adapters can be added. (Maximum 4 channels in total with the tension detector input adapter attached to the main unit)
	RS-485 communication	LM-10WA-485 type RS-485 communication interface can be installed for N:N networks with the FX series PLC. * Simultaneous use of CC-Link and RS-485 communication is disabled.
	USB connectivity	LM-10WA-USB USB communication interface can be installed for connection with MX Sheet. MX Sheet can be used to read the tension value from and write the set value to Microsoft® Excel®. [USB cable] - MR-J3USBCBL3M (3 m) - GT09-C30USB-5P (3 m) Mitsubishi Electric System & Service Co., Ltd.
	External memory	LD-8 EEPROM type memory cassette can be installed for backup and copying settings.
Power supply		24 V DC -15% +20%, allowable momentary power failure time: 5 ms
Power consumption		20 W, inrush current: 20 A, 2 ms
Weight		Approx. 350 g
Installation method		Screwing, DIN rail

● I/O specifications

Main unit		Specifications
Contact input	READY input (RDY-DIC)	24 V DC, ON current: Approx. 5 mA
	ALARM RESET input	
Contact output	Digital output 1 to 3 (DO1 to DO3-DOC) (Output function enabled by contact output setting)	Open collector output, 0.1 A (resistive load), 30 V DC or less
Analog outputs	Analog voltage output 1 to 4 (VO1 to VO4-VOC)	Voltage output switchable (0 to 5 V, 0 to 10 V, 1 to 5 V), load resistance 1 kΩ or more
	Analog current output 1 to 4 (CO2 to CO4-COC)	Current output switchable (0 to 20 mA, 4 to 20 mA), load resistance 500 Ω or less

Tension detector input adapter		Specifications
Support sensor		LX-TD/LX7-F tension detector, strain gauge (2 mV/V)
Number of connected devices/setting		"Display total value of 1 device each on the right and left" or "1 device" can be set.
Power supply for sensor	Sensor power supply (RED-BLK)	5 V DC, 20 mA Up to 2 LX-TD tension detectors can be connected.
Tension sensor input	Left side input (GRL-WHL)	Input range switchable (LX-TD tension detector, and distortion gauge [20 mV/full scale])
	Right-side input (GRR-WHR)	
Contact output	Tension lower limit detection digital output (TLL-TLC)	Open collector output, 0.1 A (resistive load), 30 V DC or less
	Tension upper limit detection digital output (TUL-TLC)	

[Option: Tension detector input adapter LM-10WA-TAD specifications]

Tension detector input adapter		Specifications
Support sensor		LX-TD/LX7-F tension detector, strain gauge (2 mV/V)
Number of connected devices/setting		"Display total value of 1 device each on the right and left" or "1 device" can be set.
Power supply for sensor	Sensor power supply (RED-BLK)	5 V DC, 20 mA Up to 2 LX-TD tension detectors can be connected.
Tension sensor input	Left side input (GRL-WHL)	Input range switchable (LX-TD tension detector, and distortion gauge [20 mV/full scale])
	Right-side input (GRR-WHR)	
Contact output	Tension lower limit detection digital output (TLL-TLC)	Open collector output, 0.1 A (resistive load), 30 V DC or less
	Tension upper limit detection digital output (TUL-TLC)	
Weight		Approx. 80 g
Installation method		Screwing, DIN rail

● GOT device (MX Sheet)/function outline

Common device	Device per channel				Function	Monitor/setting	Minimum value	Maximum value	Change during RDY
	CH1	CH2	CH3	CH4					
-	D0	D32	D64	D96	Total tension	Monitor			-
-	D1	D33	D65	D97	Left tension	Monitor			-
-	D2	D34	D66	D98	Right tension	Monitor			-
-	D3	D35	D67	D99	Output%monitor	Monitor			-
-	D4	D36	D68	D100	Left input voltage	Monitor			-
-	D5	D37	D69	D101	Right input voltage	Monitor			-
-	D6	D38	D70	D102	Input adapter version monitor	Monitor	1.00	9.99	-
-	D7 to D15	D39 to D47	D71 to D79	D103 to D111	Unavailable				
-	D16	D48	D80	D112	Sensor input type	Setting	0	1	×
-	D17	D49	D81	D113	Full scale tension	Setting	1	2000	√
-	D18	D50	D82	D114	Main tension display decimal point position	Setting	0	2	×
-	D19	D51	D83	D115	Span target tension value	Setting	1	Full scale tension	×
-	D20	D52	D84	D116	Tension detection lower limit setting	Setting	0	2000	√
-	D21	D53	D85	D117	Tension detection upper limit setting	Setting	0	2000	√
-	D22	D54	D86	D118	Tension display left gain	Setting	50.0	300.0	×
-	D23	D55	D87	D119	Tension display right gain	Setting	50.0	300.0	×
-	D24	D56	D88	D120	Tension display left bias	Setting	-50.0	50.0	×
-	D25	D57	D89	D121	Tension display right bias	Setting	-50.0	50.0	×
-	D26	D58	D90	D122	Output gain	Setting	50.0	300.0	×
-	D27	D59	D91	D123	Output bias	Setting	-50.0	50.0	×
-	D28	D60	D92	D124	Tension detection filter	Setting	0.0	2.0	√
-	D29	D61	D93	D125	Tension input filter	Setting	0.0	2	√
D126 to D127	-	-	-	-	Unavailable				
D128	-	-	-	-	Tension sampling cycle	Setting	10	60	×
D129	-	-	-	-	Tension display filter	Setting	0.5	4.0	√
D130	-	-	-	-	Output filter	Setting	0.0	4.0	√
D131	-	-	-	-	Link tension filter	Setting	0.0	4.0	√
D132	-	-	-	-	Analog monitor output mode	Setting	0	4	×
D133	-	-	-	-	Channel linkage setting	Setting	0	3	×
D134	-	-	-	-	Inter-channel linkage abnormality judgment tension	Setting	1	50	×
D135	-	-	-	-	Inter-channel linkage watch cycle	Setting	1	30	√
D136	-	-	-	-	READY input	Setting	0	1	√
D137	-	-	-	-	Alarm reset	Setting	0	1	√
D138	-	-	-	-	Password input	Setting	0	999	√
D139 to D143	-	-	-	-	Unavailable				
D144	-	-	-	-	Main system ROM Ver.	Monitor	1.00	9.99	-
D145	-	-	-	-	Memory cassette setting	Setting	0	1	×
D146	-	-	-	-	Contact output setting 1	Setting	0	6	×
D147	-	-	-	-	Contact output setting 2	Setting	0	6	×
D148	-	-	-	-	Contact output setting 3	Setting	0	6	×
D149	-	-	-	-	Transfer between main unit and input adapter	Setting	0	13	×
D150	-	-	-	-	Memory initialization	Setting	0	5	×
D151	-	-	-	-	Password setting	Setting	0	999	×
D152 to D159	-	-	-	-	Unavailable				
D160	-	-	-	-	Start station number setting	Setting	1	64	×
D161	-	-	-	-	Setting of number of occupied stations	Setting	0	Number of input adapters	×
D162	-	-	-	-	Communication speed setting	Setting	0	4	×
D163	-	-	-	-	Extended cyclic setting	Setting	1	4	×
D164	-	-	-	-	CC-Link version	Setting	1	2	×
D165	-	-	-	-	Station No. in N:N Network	Setting	0	7	×
D166 to D175	-	-	-	-	Unavailable				
D176	-	-	-	-	Alarm history 0	Monitor	0	40	-
D177	-	-	-	-	Alarm history 1	Monitor	0	40	-
D178	-	-	-	-	Alarm history 2	Monitor	0	40	-
D179	-	-	-	-	Alarm history 3	Monitor	0	40	-
D180	-	-	-	-	Alarm history 4	Monitor	0	40	-
D181	-	-	-	-	Alarm history 5	Monitor	0	40	-
D182	-	-	-	-	Alarm history 6	Monitor	0	40	-
D183	-	-	-	-	Alarm history 7	Monitor	0	40	-
D184	-	-	-	-	Alarm display time setting	Setting	0	301	×
D185	-	-	-	-	Alarm history holding setting	Setting	0	1	×

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector

Common Item

LM-10PD tension meter


The LM-10PD tension meter displays the winding, unwinding, and intermediate tension in applications that handle paper, wires, and various sheet-like materials by receiving signals from the LX7-F/LX-TD tension detector or a distortion gauge sensor, and outputs amplified signals to devices such as a recorder, external tension meter, or PLC.

Features


- Panel size of 48 × 96 realizes small size and light weight.
- Auto zero, auto span adjustment
Zero and span adjustment of tension detector is possible with one touch.
- Digital value setting of parameters.
- Tension upper/lower limit detection function (detection of 2 points).
- Memory function of tension peak value.
- Usable in combination with a strain gauge type sensor.
- Each output filter can be adjusted individually.
- Manual offset/span adjustment is possible for display and output.



Panel screen configuration



Outline dimensions (mm)




Exterior color: Munsell 7.5 GY 7.5/1

Accessories: 1 set of mounting brackets

Specifications


Item	Specifications
Power supply voltage	100 to 240 V AC (-15 to +10%), 50/60 Hz, Power consumption: 50 VA
Tension signal output	Switching between 0 to 5 V, 0 to 10 V, 1 to 5 V/FS (load resistance: 1 kΩ or more), 4 to 20 mA/FS (load resistance: 500 Ω or less)
Tension detection output	Upper and lower limit tension detection (2-point detection) Open collector output 30 V DC/0.5 A
External tension meter	DC 1 mA/FS meter (internal resistance: 1.5 kΩ or less)
Output for recorder	0 to 5 V for tension full scale (load resistance 10 kΩ or more)
Tension display	4-digit digital display with 7-segment LED. Full scale can be set within the range of 0.01 to 20000 N, unit display switching of [N] and [X10N]. Level meter display with 16 LEDs, and display switching between Left, Total, and Right
Output display	Analog output % display with 7-segment LED
Settings parameter display	LED display of item numbers and 7-segment LED display of setting value
Environmental specifications	Operating ambient temperature
	Operating ambient humidity
	Vibration resistance
	Shock resistance
	Power noise withstand level
	Withstand voltage
	Insulation resistance
Operating environment	Free of corrosive and flammable gases, and must have low levels of dust.
Weight	Approx. 500 g
Installation method	Panel mounting

External connection



When a strain gage type tension detector is used.

2 mV DC/V



LM-10TA tension amplifier

The LM-10TA tension amplifier is used in combination with the LX-TD/LX7-F tension detector and outputs signals that correspond to winding, unwinding, or countershaft tension (to the recorder, external tension meter, controller, etc.) in applications that handle paper, electric wire, or various sheet-like materials.

Features

- **Compact profile**

Compact profile made possible by supporting only the essential functions. It fits easily inside a control panel or in almost any space on a machine.

- **Free choice of applications**

By attaching an external meter, digital or analog can be freely chosen for tension display. It can also be used easily as an input signal to the tension controller.

- **Ideal for centralized display**

By using a PLC and display together, tension display for each process can be performed intensively.

- **Easy remote display**

Using the output signal (DC 0 to 5 or 10 V), tension display can be easily done at a remote place.


- **Easy recording of tension fluctuations**

Tension data can be recorded by connecting a recorder and using recorder signals.

- **DIN rail installation enabled**



Outline dimensions (mm)




Exterior color: Munsell 7.5 GY 7.5/1

Specifications

Item		Specifications
Power supply	Input	24 V DC $\pm 15\%$ Power consumption: Approx. 0.2 A
	Output	Tension detector power supply: Up to 2 LX-TD/LX7-F tension detectors can be connected.
Output signal	Tension signal	Adjustable in the range of (0 to 5) to (0 to 10) V DC at tension scale Load resistance: 1 k Ω or more
	Recorder signal	Adjustable in the range of (0 to 5) to (0 to 10) V DC at tension scale Load resistance: 100 k Ω or more
	Signal for external tension meter	1 mA DC ammeter Load resistance: 300 Ω or less
Adjustment variable resistor		For zero/span adjustment (4 pieces) For external tension meter (1 piece) } Built-in adjustment window
Weight		Approx. 200 g
Installation method		Screwing, DIN rail
Environmental specifications	Operating ambient temperature	0 to 55°C
	Operating ambient humidity	35 to 85% RH (no condensation)
	Vibration resistance	10 to 55 Hz, 0.5 mm (up to 19.6 m/s ²), 2 hours each in 3 axial directions
	Impact resistance	98 m/s ² 3 times each in 3 axial directions
	Power noise withstand level	Noise voltage 1000 Vp-p, using a noise simulator with noise width of 1 μ s and frequency of 30 to 100 Hz
	Insulation resistance	500 V DC, 5 M Ω or more when measured with insulation resistance tester
	Grounding	Class D grounding, grounding resistance 100 Ω or less
	Operating environment	Environment must be free of corrosive gases and conductive dust, and must have low levels of dust. Free from rain and water drops.

External connection




LX-TD tension detector


The LX-TD tension detector is used in combination with a feedback type tension controller such as LE7-40GU-L, LE-10WTA-CCL. It can also be used in combination with the LM-10PD, LM-10WA-CCL, LM7-1LG, or LM7-2LG tension meter to implement tension monitoring.

Features

- A tension detector is a device which converts tension into load once, and uses the load as an electrical signal.
- The electrical signals are input to tension controllers and tension meters.
- Various mounting methods are available: floor mounting, ceiling mounting, and wall mounting.
- By selecting the type of pillow block unit, many reel diameters can be compatible.
- Mounting plates for pillow block units are also available (optional).
- A 7 m cable is included.



Outline dimensions (mm)



Paint color: Munsell 10 GY 7.5/1

Paint color: Munsell 10 GY 7.5/1

Specifications

Item		Specifications					
Model name*1		LX-005TD	LX-015TD	LX-030TD	LX-050TD	LX-100TD	LX-200TD
Rated load (N)		50	150	300	500	1000	2000
Applicable load direction		Both compression and tension directions					
Maximum load withstand level (N)		400	1000	1000	1000	2000	4000
Input power		5 V DC, 20 mA or less (red: 5 V DC, black: GND)					
Output voltage		150 ±30 mV DC (when 10 kΩ load resistance is connected)					
Output voltage polarity	During compression load	Green + , White -					
	During tension load	Green - , White +					
Detection accuracy*2	Temperature drift	1%/FS or less/20°C					
	Linearity	±1% or less					
	Hysteresis	0.5% or less	0.5% or less	0.5% or less	0.5% or less	0.5% or less	1.0% or less
Installation method		Floor mounting, wall mounting, ceiling mounting					
Cable specifications		7 m (accessory)					
Weight (kg)		1.8				3	
Operating conditions		Ambient temperature: -5 to +60°C, Vibration: 2 m/s ² or less					
Outline dimensions		Fig. 1				Fig. 2	
Applicable bearings		UCP201-204 UCP205 can also be used by using the optional LX-030PLT.				UCP201-204 UCP205 and UCP206 can also be used by using the optional LX-100PLT.	
Surface treatment		Painting and plating					
Environmental specifications	Operating temperature/ storage temperature	-5 to 60°C (no freezing)					
	Operating humidity/ storage humidity	85% RH or less (no condensation)					
	Vibration resistance	2 m/s ² or less					
	Impact resistance	98 m/s ² or less: 3 times each in 3 axial directions					
	Power noise withstand level	Noise voltage 1000 Vp-p, Noise width 1 μs					
	Withstand voltage	1000 V AC for 1 min: Measure across all terminals grouped together and the housing.					
	Insulation resistance	100 MΩ or more when measured with 500 V DC insulation resistance tester: Measure across all terminals grouped together and the housing.					
Operating environment		Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.					

*1: Can be manufactured with the nickel plating specifications. Inquire separately.

*2: The detection accuracy is the accuracy for the isolated tension detector. The detection accuracy for the system will vary according to the machine specifications and installation accuracy, etc.


● Selecting a tension detector

This section describes the method of selecting a tension detector corresponding to an arbitrary mounting angle and paper passing angle. Depending on the installation conditions, selection may not be possible. In this case, change the conditions and perform the selection calculation again.

• Calculating the reference angle β

Find the reference angle β from the height C of the pillow block unit.

In the figure below, the intersection of the reference line (the line connecting the fulcrum of the detector and the load center), the mounting plane, and X axis (horizontal line) is the origin of the coordinate.



Detection type	A	B	Recommended pillow block unit
LX-005 to 050TD	56.3	15	UCP-201 to 204
LX-100, 200TD	60.3	20	UCP-201 to 204

A: Distance between the detector's supporting point and the center of the measurement point

B: Height between the detector's supporting point and the reel mounting surface


C: Height of the pillow block unit

A: Mounting angle $\alpha = 0$ to 360

$$\alpha_0: \text{Fulcrum angle } \alpha_0 = \tan^{-1} \frac{B+C}{A} \dots\dots\dots(1)$$

β: Reference angle $\beta = \alpha \pm \alpha_0$ (+ α_0 or - α_0 depending on the position of the fulcrum)

• Component force of load and effective load



$$F_h = F_m \cos \phi$$

$$F_d = F_d' \frac{R_2}{R_1} = F_m \sin \phi / \cos \alpha_0$$

Use the same formula to calculate roll load components.

• Tension components

Fm: Allowable tension per detector (N)

Fh: Tension component that pulls in the direction of the supporting point (N)

Fd: Tension component that pulls in the direction of the measurement point center (N)

• Roll load components


Wm: Roll load per detector (N)

Wh: Roll load component that is applied in the direction of the supporting point (N)

Wd: Roll load component that is applied in the direction of the measurement point center (N)

● Calculating the tension components


• Compression load



$$F_h = F_m (\cos \phi_1 - \cos \phi_2) \dots\dots\dots (2)'$$

$$F_d = F_m (\sin \phi_1 + \sin \phi_2) / \cos \alpha_0 \dots\dots\dots (3)'$$

• Expansion load




$$F_h = F_m (\cos \phi_1 - \cos \phi_2) \dots\dots\dots (2)''$$

$$F_d = -F_m (\sin \phi_1 + \sin \phi_2) / \cos \alpha_0 \dots\dots\dots (3)''$$

● Calculating the roll load components


• Compression load



$$W_h = W_m \cos \phi = W_m \sin \beta \dots\dots\dots (4)''$$

$$W_d = W_m \sin \phi / \cos \alpha_0 = W_m \cos \beta / \cos \alpha_0 \dots\dots\dots (5)''$$

• Expansion load



$$W_h = -W_m \cos \phi = W_m \sin \beta \dots\dots\dots (4)''$$

$$W_d = -W_m \sin \phi / \cos \alpha_0 = W_m \cos \beta / \cos \alpha_0 \dots\dots\dots (5)''$$

● Selection conditions

Select a detector whose load rating (G_0) meets the following criteria.

(1) Roll load component toward the detection center point $W_d = |W_m \cos \beta / \cos \alpha_0| \leq 0.8 G_0$

(0 adjustment range. Ideally this value should be made as small as possible.)

(2) Tension component toward the detection center point $F_d = |\pm F_m (\sin \phi_1 + \sin \phi_2) / \cos \alpha_0| \geq 0.2 G_0$

(From the span adjustable range of the control device, the tension component F_d at the maximum tension is set to 20% or more of the rated load. Ideally this value should be as large as possible.)

(3) Total load that is applied in the direction of the measurement point center $G_d = |F_d + W_d|$

$$= |[\pm F_m (\sin \phi_1 + \sin \phi_2) + W_m \cos \beta] / \cos \alpha_0|$$

$\leq G_0$ (when using a single detector with wire, etc. for detector protection)

$\leq 0.8 G_0$ (when using 2 detectors with a wide material, etc. Considering the fluctuation due to tension of the material, etc. as 20%, assume it is 80% or less of the rated load.)

(4) Supporting point load that is applied to the detector $G_h = |F_h + W_h|$

$$= |F_m (\cos \phi_1 - \cos \phi_2) + W_m \sin \beta| \leq 2 G_0 \text{ (for fulcrum protection)}$$

● Sample calculation

● Conditions


Tension: $F = 150$ to 400 N

Roll load: $W = 250$ N (including pillow block unit weight $\times$ number of units)

Material angle: $\theta_1 = 60^\circ$, $\theta_2 = 30^\circ$

Number of detectors: $N = 2$

Center height of pillow block unit: 33.3 mm (UCP-204)



● Detailed calculation

Temporarily select LX-100TD meeting $G_0 = 1000$ N.

Supporting point angle: $\alpha_0 = \tan^{-1}((20+33.3)/60.3) = 41.47^\circ$

Reference angle: $\beta = 41.47^\circ$

Paper feeding angle: $\phi_1 = \theta_1 - \alpha_0 = 18.53^\circ$

$\phi_2 = \theta_2 + \alpha_0 = 71.47^\circ$

$F_d = 400 (\sin 18.53^\circ + \sin 71.47^\circ) / \cos 41.47^\circ$
 $= 675.8$ N

Suppose the ratio of F_d to the rated load is F_d' ,

$F_d' = F_d / (N \times G_0) = 33.79\% \geq 20\%$ This is within the span adjustment range.

When accuracy is required, however, the larger the percentage, the better. 35% or more is recommended.

$W_d = 250 (\cos 41.47^\circ / \cos 41.47^\circ)$
 $= 250$ N

Suppose the ratio of W_d to the rated load is W_d' ,

$W_d' = W_d / (N \times G_0) = 12.5\% \leq 80\%$
 $\geq -80\%$

This is within the zero adjustment range.

Suppose the ratio of total load G_d to the rated load is G_d' ,

$G_d' = F_d' + W_d' = 46.29\% \leq 80\%$
 $\geq -80\%$

This is within the allowable load range.

This is the case where the tension of the material is assumed to be 20%.

It can be used up to $\pm 100\%$ in the case of a single detector for wires, etc.

Similarly,

$G_h = 252.1 + 165.6 = 417.7$ N

Assuming that the ratio of G_h to the rated load is G_h' ,

$G_h' = G_h / (N \times G_0) = 20.89\% \leq 100\%$
 $\geq -100\%$

This is within the allowable load range.

● Selection result

Based on the above calculation, the use of 2 LX-100TD tension detectors is recommended.

LX7-F tension detector

The LX7-F tension detector is a flange mounted type tension detector. This tension detector is used in combination with the tension controller and tension meter to output a voltage proportional to the load applied to the detection roller.

Features

● Built-in High-accuracy sensor

The sensor part adopts the highly reliable differential transformer type like the stationary mounting type (LX-TD type).


● Thin disc type

The thin shape helps minimize the equipment width. Ease of changing the path line allows the adjacent rollers to be arranged closer, which improves the freedom of layout.


● Nickel plated iron body

The body is made of iron, which is used in many machine frames. Having the same thermal expansion rate as other machine frames helps suppress the effect of changes in ambient temperature.

The surface is treated with electroless nickel plating to increase the corrosion resistance.



Outline dimensions (mm)



● Accessories

- Snap ring (for hole) Nominal 40 2 pcs.
- 7-m shielded cable with connector 1 cable
- Seal (for preventing entry of dust, etc.) ... 2 pcs.

● Recommended bearings

Bearings are not enclosed with this product. Prepare the following recommended bearings.

Tension detector Rated load (N)	Compatible reel diameter (mm)	Bearing manufacturer and nominal No.		
		NSK Ltd.	NTN Corporation	Nachi-Fujikoshi Corporation
50/150/300/500	17	1203	1203S	1203


Specifications

Item		Specifications			
Model name		LX7-50FN17	LX7-150FN17	LX7-300FN17	LX7-500FN17
Rated load (N)		50	150	300	500
Load direction		Compression (+), tension (-)			
Maximum load withstand level		200% of rated load			
Outline dimensions		Outer diameter $\phi 105$ × width 34.4 mm			
Input power		5 V DC, 20 mA or less (brown: 5 V DC, black: GND)			
Output voltage		150 ±30 mV DC (when 10 k Ω load resistance is connected)			
Output voltage polarity	During compression load	Blue + White -			
	During tension load	Blue - White +			
Detection accuracy*	Temperature drift	1%/FS or less/20°C			
	Linearity	±1% or less			
	Hysteresis	0.5% or less			
Installation method		Wall mounting			
Weight		1.2 kg			
Compatible shaft diameter		17 mm (when inserting bearings)			
Surface treatment (exterior part)		Electroless nickel plating			
Environmental specifications	Operating temperature/storage temperature	-5 to 60°C (no freezing)			
	Operating humidity/storage humidity	85% RH or less (no condensation)			
	Vibration resistance	2 m/s ² or less			
	Impact resistance	98 m/s ² or less: 3 times each in 3 axial directions			
	Power noise withstand level	Noise voltage 1000 Vp-p, Noise width 1 μ s Measured by a noise simulator with frequency range of 30 to 100 Hz			
	Withstand voltage	1000 V AC for 1 min: Measure across all terminals grouped together and the housing.			
	Insulation resistance	100 M Ω or more when measured with 500 V DC insulation resistance tester: Measure across all terminals grouped together and the housing.			
	Operating environment	Environment must be free of corrosive or flammable gases as well as conductive dust, and must have low levels of dust.			

*: The detection accuracy is the accuracy for the isolated tension detector. The detection accuracy for the system will vary according to the machine specifications and installation accuracy, etc.

External connection


The color scheme of the cable for the LX7-F flange-type tension detector is different from that of the LX-TD tension detector. Use the following external connection diagram as a reference for wiring.




Usage precautions

LX7-F flange-type tension detector is a precision device.


Especially, the sensor part can be damaged by impact or disassembly. Please handle with care.




Do not drop the tension detector.




Do not touch or press the sensor part (1).




Do not loosen the sensor mounting screw (2).




Do not hit the tension detector when installing the tension detector to the device and when installing bearing/shaft to the tension detector.




Do not hit the tension detector when performing centering adjustment.



Do not pry the shaft.



Do not apply a load which exceeds the maximum load (200% of rated load) when installing and arranging the tension detector.
Do not use the tension detection roller as a foothold while working.



Do not allow the inner wall of the bearing insertion hole to sustain impact when attaching/detaching the retaining ring (1). If the narrowed retaining ring (1) slips off the tool (2) and falls into the bearing insertion hole, the inner wall of the bearing insertion hole could sustain impact via the repulsive force of the retaining ring (1), and the sensor part (3) could be damaged.

To reliably hold the retaining ring (1) firmly in place, use a tool (2) with an anti-slip end that is in proper working condition. Then, slowly return the narrowed retaining ring (1) so as to attach/detach the retaining ring (1) so that no impact is sustained by the inner wall of the bearing insertion hole.

Installing the tension detector

This product is a highly sensitive detector produced with precision machining and assembly technology. Caution is required during assembly and operation.

For details, refer to the instruction manual.


● Selecting a tension detector

Depending on the installation conditions, selection may not be possible. In this case, change the conditions and perform the selection calculation again.

[Sample calculation]

■ Conditions

- Tension : $F = 100 \text{ N}$
- Roll load : $W = 5 \text{ kg}$
- Material angle : $\theta_1 = 30^\circ, \theta_2 = 60^\circ$
- Detector angle : $\theta_d = 20^\circ$
- Number of detectors : $N = 2$



■ Detailed calculation

Temporarily select LX7-150FN meeting $G_o = 150 \text{ N}$.

$$\begin{aligned} (1) \text{ Load by tension} \quad GF &= (\cos(\theta_1 + \theta_d) + \cos(\theta_2 - \theta_d)) \times F \\ &= (\cos(30^\circ + 20^\circ) + \cos(60^\circ - 20^\circ)) \times 100 \\ &= 140.9 \text{ (N)} \end{aligned}$$

$$\begin{aligned} (2) \text{ Load by roll} \quad GW &= \cos(\theta_d) \times W \\ &= \cos(20^\circ) \times 5 \times 9.8 \\ &= 46.0 \text{ (N)} \end{aligned}$$

$$\begin{aligned} (3) \text{ Total load} \quad G &= GF + GW \\ &= 140.9 + 46.0 \\ &= 186.9 \text{ (N)} \end{aligned}$$

$$\begin{aligned} (4) \text{ Hinge load} \quad Gh &= (\sin(\theta_1 + \theta_d) + \sin(\theta_2 - \theta_d)) \times F + \sin(\theta_d) \times W \\ &= (\sin(30^\circ + 20^\circ) + \sin(60^\circ - 20^\circ)) \times 100 + \sin(20^\circ) \times 5 \times 9.8 \\ &= 157.6 \text{ (N)} \end{aligned}$$

(5) Judgment of calculation result

- The ratio of tension load to the rated load is

$$\frac{G}{N \times G_o} = \frac{186.9}{2 \times 150} = 47.0\% \geq 20\%$$

This is within the span adjustment range.

- The ratio of roll load to the rated load is

$$\frac{GW}{N \times G_o} = \frac{46.0}{2 \times 150} = 15.3\% \leq 80\%$$

This is within the zero adjustment range.

- The ratio of total load to the rated load is

$$\frac{G}{N \times G_o} = \frac{186.9}{2 \times 150} = 62.3\% \leq 80\%$$

This is within the allowable load range. (Calculated supposing the tension of the material is 20%)

- The ratio of hinge load to the rated load is

$$\frac{Gh}{N \times G_o} = \frac{157.6}{2 \times 150} = 52.5\% \leq 100\%$$

This is within the allowable load range.

■ Selection result

Based on the above calculation, the use of 2 LX7-150FN tension detectors is recommended.

Common Item

- Corresponding Table for a Powder Clutch Brake and a Tension Controller with a Built-in Amplifier for the Clutch
- Mechanical Load Torque Calculation Method
- How to Determine the Moment of Inertia J
- Moment of Inertia J Calculation Quick Reference Table
- SI Unit and Non-SI Unit Conversion Table
- Product List
- List of Compatible Products
- How to Confirm the Date of Manufacture

Corresponding Table for a Powder Clutch Brake and a Tension Controller with a Built-in Amplifier for the Clutch

Details on tension controllers that can directly drive the powder clutch brake are as follows.

√ : Can directly drive

× : Insufficient drive current It is required to select a different product or an amplifier for the clutch.

Powder Clutch/Brake	Tension Controller		LE7-40GU-L	LD-30FTA	LD-05TL	LD-40PSU	LD-10PAU-A	LD-10PAU-B	LE-50PAU
	Rated current	Maximum output current	2.70 A	3.00 A	0.50 A	3.80 A	1.00 A	1.00 A	4.00 A
ZKG-5AN	0.35 A		√	√	√	√	√	√	√
ZKG-10AN	0.47 A		√	√	√	√	√	√	√
ZKG-20AN	0.55 A		√	√	×	√	√	√	√
ZKG-50AN	0.80 A		√	√	×	√	√	√	√
ZKG-100AN	1.00 A		√	√	×	√	√	√	√
ZKB-0.06AN	0.46 A		√	√	√	√	√	√	√
ZKB-0.3AN	0.53 A		√	√	×	√	√	√	√
ZKB-0.6AN	0.81 A		√	√	×	√	√	√	√
ZKB-1.2BN	0.94 A		√	√	×	√	√	√	√
ZKB-2.5BN	1.24 A		√	√	×	√	×	×	√
ZKB-5BN	2.15 A		√	√	×	√	×	×	√
ZKB-10BN	2.40 A		√	√	×	√	×	×	√
ZKB-20BN	2.70 A		√	√	×	√	×	×	√
ZA-0.6A ₁	0.74 A		√	√	×	√	√	√	√
ZA-1.2A ₁	0.90 A		√	√	×	√	√	√	√
ZA-2.5A ₁	1.10 A		√	√	×	√	×	×	√
ZA-5A ₁	1.40 A		√	√	×	√	×	×	√
ZA-10A ₁	2.00 A		√	√	×	√	×	×	√
ZA-20A ₁	2.50 A		√	√	×	√	×	×	√
ZKG-5YN	0.35 A		√	√	√	√	√	√	√
ZKG-10YN	0.42 A		√	√	√	√	√	√	√
ZKG-20YN	0.50 A		√	√	√	√	√	√	√
ZKG-50YN	0.60 A		√	√	×	√	√	√	√
ZKB-0.06YN	0.46 A		√	√	√	√	√	√	√
ZKB-0.3YN	0.53 A		√	√	×	√	√	√	√
ZKB-0.6YN	0.81 A		√	√	×	√	√	√	√
ZKB-1.2XN	0.94 A		√	√	×	√	√	√	√
ZKB-2.5XN	1.24 A		√	√	×	√	×	×	√
ZKB-5XN	2.15 A		√	√	×	√	×	×	√
ZKB-10XN	2.40 A		√	√	×	√	×	×	√
ZKB-20XN	2.70 A		√	√	×	√	×	×	√
ZKB-2.5HBN	1.24 A		√	√	×	√	×	×	√
ZKB-5HBN	2.15 A		√	√	×	√	×	×	√
ZKB-10HBN	2.40 A		√	√	×	√	×	×	√
ZKB-20HBN	2.70 A		√	√	×	√	×	×	√
ZA-0.6Y	0.30 A		√	√	√	√	√	√	√
ZA-1.2Y ₁	0.39 A		√	√	√	√	√	√	√
ZA-2.5Y ₁	0.73 A		√	√	×	√	√	√	√
ZA-5Y ₁	0.94 A		√	√	×	√	√	√	√
ZA-10Y ₁	1.21 A		√	√	×	√	×	×	√
ZA-20Y ₁	1.90 A		√	√	×	√	×	×	√
ZX-0.3YN-24	0.40 A		√	√	√	√	√	√	√
ZX-0.6YN-24	0.40 A		√	√	√	√	√	√	√
ZX-1.2YN-24	0.50 A		√	√	√	√	√	√	√

Mechanical Load Torque Calculation Method

In many cases, it is difficult to calculate the net power required to operate a machine due to the setting of load conditions, transmission efficiency, etc. For this reason, it is often determined empirically. However, it is necessary to grasp the load torque to select the electromagnetic clutch, so the general formulas are listed below. Note that there are many uncertainties as described above, so values should also be based on experience.

1. From motor to torque

When the load torque is not clear and only the motor output is known, it depends on the following formula.

$$T_L = 9550 \frac{P}{N} \eta \quad (1)$$

where,

T_L : Load torque (N·m)

P : Motor rated output (kW)

N : Clutch shaft rotation speed (r/min)

η : Machine conduction efficiency from motor shaft to clutch shaft

2. Work to move up and down

(Example: Hoisting)

$$T_L = \frac{W \cdot V}{6.3N \cdot \eta} \quad (2)$$

where,

T_L : Load torque (N·m)

W : Total weight (N) of vertically moving part

V : Velocity of vertically moving part (m/min)

N : Rotation speed of shaft for obtaining torque (r/min)

η : Efficiency

(Example: Approx. 0.95 per pair of gears, chains, belts etc.)

Note: This formula can also be applied to lathe spindles that do similar work.

In this case W should be cutting resistance (N).

3. Horizontal motion work with friction

(Example: Table feed, for crane run)

$$T_L = \frac{\mu \cdot W \cdot V}{6.3N \cdot \eta} \quad (3)$$

where,

T_L : Load torque (N·m)

μ : Running resistance (friction coefficient)

(Example: Approx. 0.005 for ball bearings
Approx. 0.15 on bed surface *)

W : Total weight of horizontal moving parts (N)

V : Speed (m/min) of horizontal moving parts

N : Rotation speed of shaft for obtaining torque (r/min)

η : Efficiency

(Example: Approx. 0.95 per pair of gears, chains, belts etc.)

Note: * may be even larger depending on the assembling/finishing condition of the machine.

How to Determine the Moment of Inertia J

The moment of inertia J (kgm^2) of the rotating body can be obtained by the following equation, where the weight of the rotating body is M (kg) and the unit of length is (m).

1. Rotation body J

(1) Solid cylindrical body


$$J = \frac{1}{8} \cdot M \cdot D^2 \dots \dots \dots (1)$$

where,

J : Moment of inertia (kgm^2)

M : Weight (kg)

D : Outside diameter of rotating object (m)




(2) Hollow cylindrical body

$$J = \frac{1}{8} \cdot M \cdot (D^2 + d^2) \dots \dots \dots (2)$$

where,


d : Inside diameter of rotating object (m)



(3) Complicated shape

When the shape is as shown below, divide it into A, B, and C, find J of each part, and sum them up. That is,

$$J = J_A + J_B + J_C \dots \dots \dots (3)$$




(4) Any axis x' parallel to the center axis x passing through the center of gravity of an object

$$J = J_x + M \cdot R^2 \dots \dots \dots (4)$$

where,

J_x : Moment of inertia of object with respect to axis x (kgm^2)

R : Distance between axes x and x' (m)



2. J for linear motion

(1) General formula

$$J = \frac{M \cdot V^2}{4\pi^2 \cdot N^2} \dots\dots\dots (5)$$

where,

M: Weight of linearly moving object (kg)

V: Speed of linearly moving object (m/min)

N: Rotation speed of the rotating shaft for obtaining J
(r/min)


(2) J of various linear motion bodies

(1) When the object moves linearly with a screw
[value on screw axis]

$$J = \frac{M}{4} \left(\frac{P}{\pi} \right)^2 \dots\dots\dots (6)$$

where,

M: Weight of linearly moving object (kg)




(2) Conveyor [value on Do axis]

(However, J of pulley/belt etc. is not included.)

$$J = \frac{M}{4} Do^2 \dots\dots\dots (7)$$

where,

Do: Diameter of pulley or the like (m)




(3) When the weight moves [value on drum axis]
by a rope etc. such as a crane/winches, etc.

$$J = \frac{M}{4} Do^2 \dots\dots\dots (8)$$

where,

Do: Drum diameter (m)



3. Conversion of J to clutch shaft

To convert J_B on the N_2 shaft to the clutch shaft value as shown in the following figure, do as shown in the figure below.

$$J_A = \left(\frac{N_2}{N_1} \right)^2 J_B \dots\dots\dots (9)$$


where,

J_A : J at the clutch shaft (kgm^2)

J_B : J on N_2 shaft (load shaft) (kgm^2)

N_1 : Rotation speed on the clutch shaft (r/min)

N_2 : Rotation speed on the J_B shaft (r/min)



Moment of Inertia J Calculation Quick Reference Table

This table shows J (kgm²) per 10 mm length at $\phi 10$ to $\phi 509$.

- Steel with a specific gravity $\rho = 7.85$ is shown.
- In case of hollow cylindrical body, subtract J of the inside diameter from J of the outside diameter.
- In the case of the following materials, apply the relevant coefficients to this table.

Casting: $\times 0.92$ Brass: $\times 1.14$ Aluminum: $\times 0.35$

- How to use the table

Example:

The moment of inertia of a solid cylindrical body with a diameter of 352 mm and a thickness of 25 mm is determined from the table.

Answer:

From the intersection of row 350 on the left and column 2 at the top, 1.1832×10^{-1} kgm² is obtained, which is multiplied by the

thickness $\frac{25}{10}$, hence:

$$J = 1.1832 \times 10^{-1} \times \frac{25}{10} = 0.2958 \text{ kgm}^2.$$

Diameter (mm)	J (kgm ²)										
	0	1	2	3	4	5	6	7	8	9	
10	7.7 ×10 ⁻⁸	1.13 ×10 ⁻⁷	1.6 ×10 ⁻⁷	2.2 ×10 ⁻⁷	2.96 ×10 ⁻⁷	3.9 ×10 ⁻⁷	5.05 ×10 ⁻⁷	6.44 ×10 ⁻⁷	8.09 ×10 ⁻⁷	1 ×10 ⁻⁶	
20	1.23 ×10 ⁻⁶	1.5 ×10 ⁻⁶	1.81 ×10 ⁻⁶	2.16 ×10 ⁻⁶	2.56 ×10 ⁻⁶	3.01 ×10 ⁻⁶	3.52 ×10 ⁻⁶	4.1 ×10 ⁻⁶	4.74 ×10 ⁻⁶	5.45 ×10 ⁻⁶	
30	6.24 ×10 ⁻⁶	7.12 ×10 ⁻⁶	8.08 ×10 ⁻⁶	9.14 ×10 ⁻⁶	1.03 ×10 ⁻⁵	1.157 ×10 ⁻⁵	1.294 ×10 ⁻⁵	1.444 ×10 ⁻⁵	1.607 ×10 ⁻⁵	1.783 ×10 ⁻⁵	
40	1.973 ×10 ⁻⁵	2.178 ×10 ⁻⁵	2.398 ×10 ⁻⁵	2.635 ×10 ⁻⁵	2.889 ×10 ⁻⁵	3.16 ×10 ⁻⁵	3.451 ×10 ⁻⁵	3.761 ×10 ⁻⁵	4.091 ×10 ⁻⁵	4.443 ×10 ⁻⁵	
50	4.817 ×10 ⁻⁵	5.214 ×10 ⁻⁵	5.635 ×10 ⁻⁵	6.081 ×10 ⁻⁵	6.553 ×10 ⁻⁵	7.052 ×10 ⁻⁵	7.579 ×10 ⁻⁵	8.135 ×10 ⁻⁵	8.721 ×10 ⁻⁵	9.339 ×10 ⁻⁵	
60	9.988 ×10 ⁻⁵	1.067 ×10 ⁻⁴	1.139 ×10 ⁻⁴	1.214 ×10 ⁻⁴	1.293 ×10 ⁻⁴	1.376 ×10 ⁻⁴	1.462 ×10 ⁻⁴	1.553 ×10 ⁻⁴	1.648 ×10 ⁻⁴	1.747 ×10 ⁻⁴	
70	1.85 ×10 ⁻⁴	1.958 ×10 ⁻⁴	2.071 ×10 ⁻⁴	2.189 ×10 ⁻⁴	2.311 ×10 ⁻⁴	2.438 ×10 ⁻⁴	2.571 ×10 ⁻⁴	2.709 ×10 ⁻⁴	2.853 ×10 ⁻⁴	3.002 ×10 ⁻⁴	
80	3.157 ×10 ⁻⁴	3.317 ×10 ⁻⁴	3.484 ×10 ⁻⁴	3.657 ×10 ⁻⁴	3.837 ×10 ⁻⁴	4.023 ×10 ⁻⁴	4.216 ×10 ⁻⁴	4.415 ×10 ⁻⁴	4.622 ×10 ⁻⁴	4.835 ×10 ⁻⁴	
90	5.056 ×10 ⁻⁴	5.285 ×10 ⁻⁴	5.521 ×10 ⁻⁴	5.765 ×10 ⁻⁴	6.017 ×10 ⁻⁴	6.277 ×10 ⁻⁴	6.546 ×10 ⁻⁴	6.823 ×10 ⁻⁴	7.18 ×10 ⁻⁴	7.403 ×10 ⁻⁴	
100	7.707 ×10 ⁻⁴	8.02 ×10 ⁻⁴	8.342 ×10 ⁻⁴	8.674 ×10 ⁻⁴	9.016 ×10 ⁻⁴	9.368 ×10 ⁻⁴	9.73 ×10 ⁻⁴	1.01 ×10 ⁻³	1.048 ×10 ⁻³	1.088 ×10 ⁻³	
110	1.128 ×10 ⁻³	1.17 ×10 ⁻³	1.213 ×10 ⁻³	1.257 ×10 ⁻³	1.302 ×10 ⁻³	1.348 ×10 ⁻³	1.395 ×10 ⁻³	1.444 ×10 ⁻³	1.494 ×10 ⁻³	1.545 ×10 ⁻³	
120	1.598 ×10 ⁻³	1.652 ×10 ⁻³	1.707 ×10 ⁻³	1.764 ×10 ⁻³	1.822 ×10 ⁻³	1.882 ×10 ⁻³	1.942 ×10 ⁻³	2.005 ×10 ⁻³	2.069 ×10 ⁻³	2.134 ×10 ⁻³	
130	2.201 ×10 ⁻³	2.27 ×10 ⁻³	2.34 ×10 ⁻³	2.411 ×10 ⁻³	2.485 ×10 ⁻³	2.56 ×10 ⁻³	2.636 ×10 ⁻³	2.715 ×10 ⁻³	2.795 ×10 ⁻³	2.877 ×10 ⁻³	
140	2.961 ×10 ⁻³	3.046 ×10 ⁻³	3.133 ×10 ⁻³	3.223 ×10 ⁻³	3.314 ×10 ⁻³	3.407 ×10 ⁻³	3.502 ×10 ⁻³	3.599 ×10 ⁻³	3.698 ×10 ⁻³	3.799 ×10 ⁻³	
150	3.902 ×10 ⁻³	4.007 ×10 ⁻³	4.114 ×10 ⁻³	4.223 ×10 ⁻³	4.335 ×10 ⁻³	4.448 ×10 ⁻³	4.564 ×10 ⁻³	4.682 ×10 ⁻³	4.803 ×10 ⁻³	4.926 ×10 ⁻³	
160	5.051 ×10 ⁻³	5.178 ×10 ⁻³	5.308 ×10 ⁻³	5.44 ×10 ⁻³	5.575 ×10 ⁻³	5.712 ×10 ⁻³	5.852 ×10 ⁻³	5.994 ×10 ⁻³	6.139 ×10 ⁻³	6.287 ×10 ⁻³	
170	6.437 ×10 ⁻³	6.59 ×10 ⁻³	6.745 ×10 ⁻³	6.903 ×10 ⁻³	7.064 ×10 ⁻³	7.228 ×10 ⁻³	7.395 ×10 ⁻³	7.564 ×10 ⁻³	7.737 ×10 ⁻³	7.912 ×10 ⁻³	
180	8.09 ×10 ⁻³	8.272 ×10 ⁻³	8.456 ×10 ⁻³	8.643 ×10 ⁻³	8.834 ×10 ⁻³	9.027 ×10 ⁻³	9.224 ×10 ⁻³	9.424 ×10 ⁻³	9.627 ×10 ⁻³	9.834 ×10 ⁻³	
190	1.004 ×10 ⁻²	1.026 ×10 ⁻²	1.047 ×10 ⁻²	1.069 ×10 ⁻²	1.092 ×10 ⁻²	1.114 ×10 ⁻²	1.137 ×10 ⁻²	1.161 ×10 ⁻²	1.184 ×10 ⁻²	1.209 ×10 ⁻²	
200	1.233 ×10 ⁻²	1.258 ×10 ⁻²	1.283 ×10 ⁻²	1.309 ×10 ⁻²	1.335 ×10 ⁻²	1.361 ×10 ⁻²	1.388 ×10 ⁻²	1.415 ×10 ⁻²	1.443 ×10 ⁻²	1.47 ×10 ⁻²	
210	1.499 ×10 ⁻²	1.528 ×10 ⁻²	1.557 ×10 ⁻²	1.586 ×10 ⁻²	1.616 ×10 ⁻²	1.647 ×10 ⁻²	1.678 ×10 ⁻²	1.709 ×10 ⁻²	1.741 ×10 ⁻²	1.773 ×10 ⁻²	
220	1.805 ×10 ⁻²	1.838 ×10 ⁻²	1.872 ×10 ⁻²	1.906 ×10 ⁻²	1.94 ×10 ⁻²	1.975 ×10 ⁻²	2.011 ×10 ⁻²	2.046 ×10 ⁻²	2.083 ×10 ⁻²	2.119 ×10 ⁻²	
230	2.157 ×10 ⁻²	2.194 ×10 ⁻²	2.233 ×10 ⁻²	2.271 ×10 ⁻²	2.311 ×10 ⁻²	2.35 ×10 ⁻²	2.391 ×10 ⁻²	2.431 ×10 ⁻²	2.473 ×10 ⁻²	2.515 ×10 ⁻²	
240	2.557 ×10 ⁻²	2.6 ×10 ⁻²	2.643 ×10 ⁻²	2.687 ×10 ⁻²	2.732 ×10 ⁻²	2.777 ×10 ⁻²	2.822 ×10 ⁻²	2.869 ×10 ⁻²	2.915 ×10 ⁻²	2.963 ×10 ⁻²	
250	3.01 ×10 ⁻²	3.059 ×10 ⁻²	3.108 ×10 ⁻²	3.158 ×10 ⁻²	3.208 ×10 ⁻²	3.259 ×10 ⁻²	3.31 ×10 ⁻²	3.362 ×10 ⁻²	3.415 ×10 ⁻²	3.468 ×10 ⁻²	
260	3.522 ×10 ⁻²	3.576 ×10 ⁻²	3.631 ×10 ⁻²	3.687 ×10 ⁻²	3.744 ×10 ⁻²	3.801 ×10 ⁻²	3.858 ×10 ⁻²	3.917 ×10 ⁻²	3.976 ×10 ⁻²	4.035 ×10 ⁻²	
270	4.096 ×10 ⁻²	4.157 ×10 ⁻²	4.218 ×10 ⁻²	4.281 ×10 ⁻²	4.344 ×10 ⁻²	4.408 ×10 ⁻²	4.472 ×10 ⁻²	4.537 ×10 ⁻²	4.603 ×10 ⁻²	4.67 ×10 ⁻²	
280	4.737 ×10 ⁻²	4.805 ×10 ⁻²	4.874 ×10 ⁻²	4.943 ×10 ⁻²	5.014 ×10 ⁻²	5.084 ×10 ⁻²	5.156 ×10 ⁻²	5.229 ×10 ⁻²	5.302 ×10 ⁻²	5.376 ×10 ⁻²	
290	5.451 ×10 ⁻²	5.526 ×10 ⁻²	5.603 ×10 ⁻²	5.68 ×10 ⁻²	5.758 ×10 ⁻²	5.837 ×10 ⁻²	5.916 ×10 ⁻²	5.996 ×10 ⁻²	6.078 ×10 ⁻²	6.16 ×10 ⁻²	
300	6.242 ×10 ⁻²	6.326 ×10 ⁻²	6.411 ×10 ⁻²	6.496 ×10 ⁻²	6.582 ×10 ⁻²	6.669 ×10 ⁻²	6.757 ×10 ⁻²	6.846 ×10 ⁻²	6.935 ×10 ⁻²	7.026 ×10 ⁻²	
310	7.117 ×10 ⁻²	7.21 ×10 ⁻²	7.303 ×10 ⁻²	7.397 ×10 ⁻²	7.492 ×10 ⁻²	7.588 ×10 ⁻²	7.685 ×10 ⁻²	7.782 ×10 ⁻²	7.881 ×10 ⁻²	7.981 ×10 ⁻²	
320	8.081 ×10 ⁻²	8.183 ×10 ⁻²	8.285 ×10 ⁻²	8.388 ×10 ⁻²	8.493 ×10 ⁻²	8.598 ×10 ⁻²	8.704 ×10 ⁻²	8.812 ×10 ⁻²	8.92 ×10 ⁻²	9.029 ×10 ⁻²	
330	9.14 ×10 ⁻²	9.251 ×10 ⁻²	9.363 ×10 ⁻²	9.476 ×10 ⁻²	9.591 ×10 ⁻²	9.706 ×10 ⁻²	9.823 ×10 ⁻²	9.94 ×10 ⁻²	1.0059 ×10 ⁻¹	1.0178 ×10 ⁻¹	
340	1.0299 ×10 ⁻¹	1.0421 ×10 ⁻¹	1.0543 ×10 ⁻¹	1.0667 ×10 ⁻¹	1.0792 ×10 ⁻¹	1.0918 ×10 ⁻¹	1.1045 ×10 ⁻¹	1.1174 ×10 ⁻¹	1.1303 ×10 ⁻¹	1.1433 ×10 ⁻¹	
350	1.1565 ×10 ⁻¹	1.1698 ×10 ⁻¹	1.1832 ×10 ⁻¹	1.1967 ×10 ⁻¹	1.2103 ×10 ⁻¹	1.224 ×10 ⁻¹	1.2379 ×10 ⁻¹	1.2581 ×10 ⁻¹	1.2659 ×10 ⁻¹	1.2801 ×10 ⁻¹	
360	1.2944 ×10 ⁻¹	1.3089 ×10 ⁻¹	1.3234 ×10 ⁻¹	1.3381 ×10 ⁻¹	1.3529 ×10 ⁻¹	1.3679 ×10 ⁻¹	1.3829 ×10 ⁻¹	1.3981 ×10 ⁻¹	1.4134 ×10 ⁻¹	1.4288 ×10 ⁻¹	
370	1.4444 ×10 ⁻¹	1.4601 ×10 ⁻¹	1.4759 ×10 ⁻¹	1.4918 ×10 ⁻¹	1.5079 ×10 ⁻¹	1.524 ×10 ⁻¹	1.5404 ×10 ⁻¹	1.5568 ×10 ⁻¹	1.5734 ×10 ⁻¹	1.5901 ×10 ⁻¹	
380	1.607 ×10 ⁻¹	1.6239 ×10 ⁻¹	1.6411 ×10 ⁻¹	1.6583 ×10 ⁻¹	1.6757 ×10 ⁻¹	1.6933 ×10 ⁻¹	1.7109 ×10 ⁻¹	1.7287 ×10 ⁻¹	1.7466 ×10 ⁻¹	1.7647 ×10 ⁻¹	
390	1.7829 ×10 ⁻¹	1.8013 ×10 ⁻¹	1.8198 ×10 ⁻¹	1.8384 ×10 ⁻¹	1.8572 ×10 ⁻¹	1.8761 ×10 ⁻¹	1.8952 ×10 ⁻¹	1.9144 ×10 ⁻¹	1.9338 ×10 ⁻¹	1.9533 ×10 ⁻¹	
400	1.9729 ×10 ⁻¹	1.9927 ×10 ⁻¹	2.0127 ×10 ⁻¹	2.0328 ×10 ⁻¹	2.053 ×10 ⁻¹	2.0734 ×10 ⁻¹	2.094 ×10 ⁻¹	2.1147 ×10 ⁻¹	2.1356 ×10 ⁻¹	2.1566 ×10 ⁻¹	
410	2.1777 ×10 ⁻¹	2.1991 ×10 ⁻¹	2.2205 ×10 ⁻¹	2.2422 ×10 ⁻¹	2.264 ×10 ⁻¹	2.2859 ×10 ⁻¹	2.308 ×10 ⁻¹	2.3303 ×10 ⁻¹	2.3528 ×10 ⁻¹	2.3753 ×10 ⁻¹	
420	2.3981 ×10 ⁻¹	2.421 ×10 ⁻¹	2.4441 ×10 ⁻¹	2.4674 ×10 ⁻¹	2.4908 ×10 ⁻¹	2.5144 ×10 ⁻¹	2.5381 ×10 ⁻¹	2.562 ×10 ⁻¹	2.5861 ×10 ⁻¹	2.6104 ×10 ⁻¹	
430	2.6348 ×10 ⁻¹	2.6594 ×10 ⁻¹	2.6841 ×10 ⁻¹	2.7091 ×10 ⁻¹	2.7342 ×10 ⁻¹	2.7595 ×10 ⁻¹	2.7849 ×10 ⁻¹	2.8106 ×10 ⁻¹	2.8364 ×10 ⁻¹	2.8624 ×10 ⁻¹	
440	2.8886 ×10 ⁻¹	2.9149 ×10 ⁻¹	2.9414 ×10 ⁻¹	2.9681 ×10 ⁻¹	2.995 ×10 ⁻¹	3.0221 ×10 ⁻¹	3.0494 ×10 ⁻¹	3.0768 ×10 ⁻¹	3.1044 ×10 ⁻¹	3.1322 ×10 ⁻¹	
450	3.1602 ×10 ⁻¹	3.1884 ×10 ⁻¹	3.2168 ×10 ⁻¹	3.2454 ×10 ⁻¹	3.2741 ×10 ⁻¹	3.3031 ×10 ⁻¹	3.3322 ×10 ⁻¹	3.3615 ×10 ⁻¹	3.391 ×10 ⁻¹	3.4208 ×10 ⁻¹	
460	3.4507 ×10 ⁻¹	3.4808 ×10 ⁻¹	3.5111 ×10 ⁻¹	3.5416 ×10 ⁻¹	3.5723 ×10 ⁻¹	3.6032 ×10 ⁻¹	3.6342 ×10 ⁻¹	3.6655 ×10 ⁻¹	3.697 ×10 ⁻¹	3.7287 ×10 ⁻¹	
470	3.7606 ×10 ⁻¹	3.7927 ×10 ⁻¹	3.8251 ×10 ⁻¹	3.8576 ×10 ⁻¹	3.8903 ×10 ⁻¹	3.9232 ×10 ⁻¹	3.9564 ×10 ⁻¹	3.9897 ×10 ⁻¹	4.0233 ×10 ⁻¹	4.0571 ×10 ⁻¹	
480	4.0911 ×10 ⁻¹	4.1253 ×10 ⁻¹	4.1597 ×10 ⁻¹	4.1943 ×10 ⁻¹	4.2291 ×10 ⁻¹	4.2642 ×10 ⁻¹	4.2995 ×10 ⁻¹	4.335 ×10 ⁻¹	4.3707 ×10 ⁻¹	4.4066 ×10 ⁻¹	
490	4.4428 ×10 ⁻¹	4.4792 ×10 ⁻¹	4.5158 ×10 ⁻¹	4.5526 ×10 ⁻¹	4.5886 ×10 ⁻¹	4.6269 ×10 ⁻¹	4.6644 ×10 ⁻¹	4.7021 ×10 ⁻¹	4.7401 ×10 ⁻¹	4.7783 ×10 ⁻¹	
500	4.8167 ×10 ⁻¹	4.8554 ×10 ⁻¹	4.8942 ×10 ⁻¹	4.9334 ×10 ⁻¹	4.9727 ×10 ⁻¹	5.0123 ×10 ⁻¹	5.0521 ×10 ⁻¹	5.0922 ×10 ⁻¹	5.1325 ×10 ⁻¹	5.173 ×10 ⁻¹	

SI Unit and Non-SI Unit Conversion Table

The transition to SI units has been carried out since October 1, 1999, but some terms still require conversion. The following reference table shows conversion factors related to clutches and brakes.

Physical quantity	Non-SI unit (symbol)	SI unit (symbol)	Conversion relation
Length	Micron (μ)	Meter (m)	$1 \mu = 1 \mu\text{m}$
Frequency	Cycle (c) Cycle per second (c/s)	Hertz (Hz)	$1\text{c} = 1 \text{ c/s} = 1 \text{ Hz}$
Magnetic field strength	Amperage per meter (AT/m) Oersted (Oe)	Ampere meter (A/m)	$1 \text{ AT/m} = 1 \text{ A/m}$ $10\text{e} \approx 79 \text{ A/m}$
Magnetomotive force	Ampere-turn (AT)	Ampere (A)	$1 \text{ AT} = 1 \text{ A}$
Magnetic flux density	Gamma (γ) Gauss (G)	Tesla (T)	$1 \gamma = 1 \text{ nT}$ $1 \text{ G} = 100 \mu\text{T}$
Magnetic flux density	Maxwell (Mx)	Weaver (Wb)	$1 \text{ Mx} = 10 \text{ nWb}$
Sound pressure level	Phone	Decibel (dB)	$1 \text{ phone} = 1 \text{ dB}$
Force (load and tension)	Weight kg (kgf) Weight gram (gf) Weight ton (tf)	Newton (N)	$1 \text{ kgf} \approx 9.8 \text{ N}$ $1 \text{ gf} \approx 9.8 \text{ mN}$ $1 \text{ tf} \approx 9.8 \text{ kN}$
Moment of force (torque)	Weight kilogram meter (kgf·m)	Newton meter (N·m)	$1 \text{ kgf·m} \approx 9.8 \text{ N·m}$
Pressure	Weight kilogram per square meter (kgf/m ²)	Pascal (Pa)	$1 \text{ kgf/m}^2 \approx 9.8 \text{ Pa}$
Stress	Weight kilogram per square meter (kgf/m ²)	Pascal (Pa)	$1 \text{ kgf/m}^2 \approx 9.8 \text{ Pa}$
Work (energy)	Weight kilogram meter (kgf·m)	Joule (J)	$1 \text{ kgf·m} \approx 9.8 \text{ J}$
Rate	Weight kilogram meter per second (kgf·m/s)	Watt (W)	$1 \text{ kgf·m/s} \approx 9.8 \text{ W}$
Calorie	Calorie (cal)	Joule (J)	$1 \text{ cal} \approx 4.2 \text{ J}$
Rotation	Rotation speed (rpm)	Rotation speed (r/min)	$1 \text{ rpm} = 1 \text{ r/min}$
Time	Second (sec) Minute (min) (reference) Hour (Hr) (reference)	Second (s) Minute (min) Hour (h)	$1 \text{ sec} = 1 \text{ s}$ $1 \text{ min} = 1 \text{ min}$ $1 \text{ Hr} = 1 \text{ h}$
Moment of inertia	GD ² (kgf·m ²)	Moment of inertia (kg·m ²)	$1 \text{ kgf·m}^2 \approx 0.25 \text{ kg·m}^2$
Temperature	Degree (°C)	Celsius degree (°C)	$1^\circ\text{C} = 1^\circ\text{C}$
Temperature difference	Degree (deg)	Celsius degree (°C)	$1 \text{ deg} = 1^\circ\text{C}$
Weight	Weight kg (kgf)	Kilogram (kg)	$1 \text{ kgf} = 1 \text{ kg}$

For details other than the above, refer to ISO 1000.

Product List (clutch/brake)

Type			Model name	Page
Powder clutch	Protruding shaft	Natural cooling type	ZKG-5AN	A-10
			ZKG-10AN	
			ZKG-20AN	
			ZKG-50AN	
			ZKG-100AN	
			ZKB-0.06AN	
		Natural cooling type (Forced air cooling)	ZKB-0.3AN	A-12
			ZKB-0.6AN	
			ZKB-1.2BN	A-14
		Natural cooling type (Forced air cooling)	ZKB-2.5BN	
			ZKB-5BN	
			ZKB-10BN	A-16
			ZKB-20BN	
	Through-shaft	Natural cooling type	ZA-0.6A1	A-18
			ZA-1.2A1	
			ZA-2.5A1	
			ZA-5A1	
			ZA-10A1	
			ZA-20A1	

Type			Model name	Page
Powder brake	Protruding shaft	Natural cooling type	ZKG-5YN	A-20
			ZKG-10YN	
			ZKG-20YN	
			ZKG-50YN	
			ZKB-0.06YN	A-22
			ZKB-0.3YN	
			ZKB-0.6YN	
		Natural cooling type (Forced air cooling)	ZKB-1.2XN	A-24
			ZKB-2.5XN	
			ZKB-5XN	
			ZKB-10XN	A-26
			ZKB-20XN	
	Through-shaft	Thermoblock cooling	ZKB-2.5HBN	A-28
			ZKB-5HBN	
			ZKB-10HBN	
			ZKB-20HBN	
		Natural cooling type	ZA-0.6Y	A-30
			ZA-1.2Y1	
			ZA-2.5Y1	
			ZA-5Y1	
			ZA-10Y1	A-32
			ZA-20Y1	
		Natural cooling type Thin type	ZX-0.3YN-24	A-34
			ZX-0.6YN-24	
			ZX-1.2YN-24	

Product List (tension controller)

Discontinued product : Production completion at the end of March 2024

Scheduled completion/order production^{*1} : Scheduled completion of production at the end of March 2025 (Built-to-order production from October 2024)

Scheduled completion/order production^{*2} : Scheduled completion of production at the end of September 2025 (Built-to-order production from April 2024)

Type		Model name	Outline	Page
Feedback tension controller		LE7-40GU-L	Power supply input: 100 to 240 V AC, 2.7 A built-in clutch amplifier	B-4
		LE-10WTA-CCL	Power supply input: 24 V DC (1 LM-10WA-TAD tension detector input adapter included)	B-16
		LE-30CTN Discontinued product	Power supply input: 100 to 240 V AC, 3.0 A built-in clutch amplifier	B-21
		LE-40MTA Discontinued product	Power supply input: 100 to 240 V AC, 4.0 A built-in clutch amplifier, standard type, Japanese display	—
		LE-40MTB Discontinued product	Power supply input: 100 to 240 V AC, 4.0 A built-in clutch amplifier, high-function type, Japanese display	
		LE-40MTA-E Discontinued product	Power supply input: 100 to 240 V AC, 4.0 A built-in clutch amplifier, standard type, English display	
		LE-40MTB-E Discontinued product	Power supply input: 100 to 240 V AC, 4.0 A built-in clutch amplifier, high-function type, English display	
		LE-60EC Scheduled completion/ order production*1	Extension cable for LE-40MTB (LE-40MTB-E) (for CC-Link extension block)	
		LE-40MD Discontinued product	Reel diameter calculation unit (used in combination with LE-40MTB or LE-40MTB-E)	
Open-loop type tension controller		LD-10WTB-CCL	Power supply input: 24 V DC (1 LD-10WTB-DCA reel diameter calculation adapter included)	B-16
		LD-30FTA Scheduled completion/ order production*2	Power supply input: 100 to 240 V AC, 3.0 A built-in clutch amplifier, integrated thickness type	B-21
		LD-05TL Scheduled completion/ order production*2	Power supply input: 24 V DC, 0.5 A built-in clutch amplifier, touch lever (potentiometer) type	B-27
Clutch amplifier		LD-40PSU Scheduled completion/ order production*2	Power supply input: 100 to 240 V AC, clutch amplifier output: 3.8 A, control type: constant-voltage control type	B-31
		LD-10PAU-A	Power supply input: 24 V DC, clutch amplifier output: 1.0 A, control type: constant-current control type	B-33
		LD-10PAU-B	Power supply input: 24 V DC, clutch amplifier output: 1.0 A, control type: constant-current control type, with inter-station communication function (RS-485)	
		LE-50PAU	Power supply input: 100 to 240 V AC, clutch amplifier output: 4.0 A, control type: constant-current constant-voltage control type	B-29
Tension Meter		LM7-1LG	Power supply input: 24 V DC, detector input: 1 shaft	B-37
		LM7-2LG	Power supply input: 24 V DC, detector input: 2 shafts	
		LM-10WA-CCL	Power supply input: 24 V DC, detector input: up to 4 shafts (1 LM-10WA-TAD tension detector input adapter included)	B-41
		LM-10PD	Power supply input: 100 to 240 V AC, detector input: 1 shaft	B-46
		LM-10TA	Tension amplifier, power supply input: 24 V DC, detector input: 1 shaft	B-48
Tension detector and explosion-proof safety barrier	Standard	Stationary type	LX-005TD	B-50
			LX-015TD	
			LX-030TD	
			LX-050TD	
			LX-100TD	
			LX-200TD	
		Flange type	LX7-50FN17	B-54
			LX7-150FN17	
			LX7-300FN17	
			LX7-500FN17	
Option		LE7-DCA	Reel diameter calculation option (for LE7-40GU-L)	B-9
		LE7-CCL	Network option (for LE7-40GU-L)	B-13
		LE7-ATT	Attachment (for LE7-40GU-L)	B-15
		LM-10WA-TAD	Tension detector input adapter (for LE-10WTA-CCL, LD-10WTB-CCL, and LM-10WA-CCL)	B-18, 43
		LD-10WTB-DCA	Reel diameter calculation adapter (for LE-10WTA-CCL and LD-10WTB-CCL)	
		LM-10WA-USB	USB interface (for LE-10WTA-CCL, LD-10WTB-CCL, and LM-10WA-CCL)	B-18
		LM-10WA-485	RS-485 communication interface (for LE-10WTA-CCL, LD-10WTB-CCL, and LM-10WA-CCL)	
		LD-30FTA-1AD Scheduled completion/ order production*2	Analog input option board for LD-30FTA	B-22
		LD-8EEPROM	Memory cassette (for LE-10WTA-CCL, LD-10WTB-CCL, LM-10WA-CCL, LE7-40GU-L, and LD-10PAU-□)	B-34
		LD-10PAU-CAB1M	Digital input cable (1 m) for LD-10PAU-□	—
		LX-030PLT	Mounting plate for pillow block (for LX-005TD, 015TD, 030TD, and 050TD)	B-50
		LX-100PLT	Mounting plate for pillow block (for LX-100TD and 200TD)	

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector

Common Item

List of Compatible Products (clutch/brake)*1

√: Supported □: Excluded from the standard

Type			Model name		CE			KC
					EMC	LVD	RoHS	
Powder clutch	Protruding shaft	Natural cooling type	ZKG-5AN	√	□	□	√	□
			ZKG-10AN	√	□	□	√	□
			ZKG-20AN	√	□	□	√	□
			ZKG-50AN	√	□	□	√	□
			ZKG-100AN	√	□	□	√	□
			ZKB-0.06AN	√	□	□	√	□
			ZKB-0.3AN	√	□	□	√	□
			ZKB-0.6AN	√	□	□	√	□
	Through shaft	Natural cooling type (forced air cooling type)	ZKB-1.2BN	√	□	□	√	□
			ZKB-2.5BN	√	□	□	√	□
			ZKB-5BN	√	□	□	√	□
			ZKB-10BN	√	□	□	√	□
			ZKB-20BN	√	□	□	√	□
		Natural cooling type	ZA-0.6A1	√	□	□	√	□
			ZA-1.2A1	√	□	□	√	□
			ZA-2.5A1	√	□	□	√	□
			ZA-5A1	√	□	□	√	□
			ZA-10A1	√	□	□	√	□
			ZA-20A1	√	□	□	√	□
Powder brake	Protruding shaft	Natural cooling type	ZKG-5YN	√	□	□	√	□
			ZKG-10YN	√	□	□	√	□
			ZKG-20YN	√	□	□	√	□
			ZKG-50YN	√	□	□	√	□
			ZKB-0.06YN	√	□	□	√	□
			ZKB-0.3YN	√	□	□	√	□
			ZKB-0.6YN	√	□	□	√	□
		Natural cooling type (forced air cooling type)	ZKB-1.2XN	√	□	□	√	□
			ZKB-2.5XN	√	□	□	√	□
			ZKB-5XN	√	□	□	√	□
			ZKB-10XN	√	□	□	√	□
			ZKB-20XN	√	□	□	√	□
		Thermoblock cooling type	ZKB-2.5HBN	√	□	□	√	□
			ZKB-5HBN	√	□	□	√	□
			ZKB-10HBN	√	□	□	√	□
			ZKB-20HBN	√	□	□	√	□
	Through shaft	Natural cooling type	ZA-0.6Y	√	□	□	√	□
			ZA-1.2Y1	√	□	□	√	□
			ZA-2.5Y1	√	□	□	√	□
			ZA-5Y1	√	□	□	√	□
			ZA-10Y1	√	□	□	√	□
			ZA-20Y1	√	□	□	√	□
		Natural cooling, thin type	ZX-0.3YN-24	√	□	□	√	□
			ZX-0.6YN-24	√	□	□	√	□
			ZX-1.2YN-24	√	□	□	√	□

UL/cUL standards are not complied with.

*1: Status of support as of October 1, 2024

List of Compatible Products (tension controller, etc.)^{*3}

√: Supported □: Excluded from the standard —: Not supported

Discontinued product : Production completion at the end of March 2024

Scheduled completion/order production^{*1} : Scheduled completion of production at the end of March 2025 (Built-to-order production from October 2024)

Scheduled completion/order production^{*2} : Scheduled completion of production at the end of September 2025 (Built-to-order production from April 2024)

Type			Model name		CE			KC			
					EMC	LVD	RoHS				
Feedback tension controller			LE7-40GU-L	√	√	√	√	√			
			LE-10WTA-CCL	√	√	□	√	√			
			LE-30CTN Discontinued product	√	√	√	√	√			
			LE-40MTA Discontinued product	—	—	—	—	√			
			LE-40MTB Discontinued product	—	—	—	—	√			
			LE-40MTA-E Discontinued product	—	—	—	—	√			
			LE-40MTB-E Discontinued product	—	—	—	—	√			
			LE-60EC Scheduled completion/ order production* ¹	—	□	□	—	□			
			LE-40MD Discontinued product	—	—	—	—	—			
			Open-loop tension controller			LD-10WTB-CCL	√	√	□	√	√
						LD-30FTA Scheduled completion/ order production* ²	—	—	—	—	√
LD-05TL Scheduled completion/ order production* ²	—	—				□	—	—			
Clutch amplifier						LD-40PSU Scheduled completion/ order production* ²	—	—	—	—	√
			LD-10PAU-A	—	—	□	—	√			
			LD-10PAU-B	√	√	□	√	√			
			LE-50PAU	—	—	—	—	√			
			Tension meter			LM7-1LG	√	√	□	√	√
LM7-2LG	√	√				□	√	√			
LM-10WA-CCL	√	√				□	√	√			
LM-10PD	—	—				—	—	√			
LM-10TA	—	—				□	—	√			
Tension detector						Standard	Stationary type	LX-005TD	√	□	□
			LX-015TD	√	□			□	√	□	
			LX-030TD	√	□			□	√	□	
			LX-050TD	√	□			□	√	□	
			LX-100TD	√	□			□	√	□	
			LX-200TD	√	□			□	√	□	
			Flange type	LX7-50FN17	√	□	□	√	□		
				LX7-150FN17	√	□	□	√	□		
				LX7-300FN17	√	□	□	√	□		
				LX7-500FN17	√	□	□	√	□		
Option			LE7-DCA	√	√	□	√	√			
			LE7-CCL	√	√	□	√	√			
			LE7-ATT	—	□	□	—	□			
			LM-10WA-TAD	√	√	□	√	√			
			LD-10WTB-DCA	√	√	□	√	√			
			LM-10WA-USB	√	√	□	√	√			
			LM-10WA-485	√	√	□	√	√			
			LD-30FTA-1AD Scheduled completion/ order production* ²	—	—	□	—	□			
			LD-8EEPROM	√	√	□	√	√			
			LD-10PAU-CAB1M	√	□	□	√	□			
			LX-030PLT	□	□	□	√	□			
			LX-100PLT	□	□	□	√	□			

UL/cUL standards are not complied with.

*1: Scheduled completion of production at the end of March 2025 (Built-to-order production from October 2024)

*2: Scheduled completion of production at the end of September 2025 (Built-to-order production from April 2024)

*3: Status of support as of October 1, 2024

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector


Common Item

How to Confirm the Date of Manufacture


To confirm the date of manufacture, use the serial number of the product.

The serial number can be confirmed via the nameplate or the number described on the package when you purchased the product.

■ For electromagnetic clutches and brakes



Clutch: ZKB-5BN
Nameplate example



Note: The description on the nameplate differs depending on the model.

<Products manufactured from April 2007 to November 2013>

Described using six digits

Example: Manufactured in April 2007

0 7 4 0 1 0

Consecutive numbers: 001 to 999

Month of manufacture:

1 to 9: January to September;

X: October; Y: November; Z: December

Year of manufacture: Last two digits of the year

<Products manufactured since March 2013>

Described using seven digits

Example: Manufactured in December 2013

1 3 Z 0 0 0 1

Consecutive numbers: 0001 to 9999


Month of manufacture:

1 to 9: January to September;


X: October; Y: November; Z: December

Year of manufacture: Last two digits of the year

■ For tension detectors



Tension detector: LX-050TD
Nameplate example



Note: The description on the nameplate differs depending on the model.

<Products manufactured since June 2007>

Described using seven digits

Example: Manufactured in June 2007

0 7 6 0 1 0 0

Consecutive numbers: 0001 to 9999


Month of manufacture:

1 to 9: January to September;

X: October; Y: November; Z: December

Year of manufacture: Last two digits of the year

■ For tension controllers, clutch amplifiers, tension meters, and tension amplifiers



Note: For a date of manufacture that is not described as above, consult your local Mitsubishi Electric representative.

Powder Clutch/Brake

Tension Controller

Clutch Amplifier

Tension Meter/Tension Amplifier

Tension Detector

Common Item

Safety precautions

(Please read before considering installation.)

Safety Guidelines

- Before using our products, please read this catalog and instruction manual carefully, pay sufficient attention to safety, and use the products properly.
- These products are manufactured as general-purpose products for general industry. They are not designed or manufactured for use with equipment or systems that may affect human life.
- If you are considering using these products for nuclear power, power generation, aerospace, medical, or passenger vehicle equipment or systems, consult our sales department.
- Although the products shown in this catalog are manufactured under strict quality control, please make sure to incorporate a systematic backup and fail safe function when installing the products in a facility where failure of a product may cause a serious accident or loss.

The safety precautions are classified into [ WARNING] and [ CAUTION] in this catalog. The meaning and symbols for each classification are as follows.

 **WARNING** If not operated properly, it may lead to a dangerous situation and cause death or serious injury.

 **CAUTION** If not operated properly, it may lead to a dangerous situation and cause a moderate or minor injury. Alternatively, it may cause damage to property.

Precautions for clutches/brakes in general

 **WARNING** Install a protective cover.



If a rotating object is exposed to the outside, a dangerous situation could occur if a part of the human body such as a hand, finger, etc. comes in contact. Install a protective cover with sufficient ventilation to prevent contact with the human body. In addition, make sure to provide a safety mechanism which immediately stops the rotating object when the cover is opened.

 **WARNING** Make sure to operate the products within the allowable heat capacity.



If operated exceeding the allowable heat capacity, the working surfaces may become red-hot due to excessive heat buildup and cause a fire. In addition, the products may not perform as designed. Make sure to operate the products within the allowable heat capacity.

 **WARNING** Do not operate the products exceeding the allowable rotation speed.

If operated exceeding the allowable rotation speed, the products may break and be scattered due to excessive vibration. Make sure to operate the products within the allowable rotation speed and install a protective cover.

 **WARNING** Upon breaking the DC current, make sure to install a surge absorber in parallel with the clutch/brake coil.

Breaking the DC current may generate a massive surge voltage and adversely affect peripheral equipment. Use a surge absorber (diode, varistor, protective resistor, and so on).

 **WARNING** When designing the system, make sure to specify electrical wire of a suitable size for the specified current capacity.



Make sure to use electrical wire of a suitable size for the specified current capacity. If the electrical wire is not thick enough, the insulator may melt and cause an insulation failure. The failure may cause an electric shock, electric leakage, or fire.

 **WARNING** Check the surrounding environment.

Do not operate the products in an environment exposed to dust, high temperature, condensation, wind, and rain. Additionally, do not mount the products in a location where vibration or shock is directly applied. Otherwise, it may lead to damage, malfunction, and insufficient performance of the products.

 **WARNING** Make sure not to operate the products in an atmosphere where an ignition and/or explosion may occur.



Slipping may cause sparks at the working surfaces in the products. Do not operate the products in an atmosphere containing oils, fats, or flammable gas which may cause an ignition and/or explosion. In addition, make sure to enclose the main unit of the products at a location where there are flammable materials such as cotton. Note that enclosing the main unit lowers the allowable heat dissipation of the product.

 **WARNING** When designing the system, make sure to avoid the infiltration of water, oils, and fats.

If the products are exposed to water, oils, and fats, such contaminants will eventually reach the working surfaces and significantly lower the torque. This may cause the machine to run by inertia or go out of control, which may lead to an accidental injury.

 **WARNING** Make sure to operate the products within the rated torque.

If operated exceeding the rated torque, it may cause loss of efficiency and mechanical damage leading to injury. Make sure to operate the products within the rated torque.

 **WARNING** Make sure to use bolts having the specified strength and to install devices to securely prevent looseness.

The bolts, depending on the strength, may be sheared and damaged, which may lead to injury. Use bolts that satisfy the requirements stipulated in Strength Classification II 7T of JIS B 1051 or better and prevent looseness by using an adhesive, spring washers, etc.

Precautions for tension controllers in general

 **WARNING** Make sure to construct an emergency stop circuit externally isolated from the tension controllers.

Make sure to construct an emergency stop circuit for the machine externally isolated from the products. Otherwise, the machine may go out of control and cause an accident when a malfunction occurs.

 **WARNING** Provide class D grounding (100 Ω or less).

Make sure to provide the grounding terminal and sheet metal body of the products with class D grounding (100 Ω or less) using electrical wires with a thickness of 2 mm² or more. Failure to do so may cause electric shock.
* Provide class A grounding (10 Ω or less) for the safety barrier.

 **WARNING** Do not operate the switches and keys with wet hands.

Do not operate the switches and keys with wet hands. Doing so may cause an electric shock.

 **WARNING** Make sure not to operate the products in an atmosphere where an ignition and/or explosion may occur.

Doing so may cause a fire and/or explosion.

 **WARNING** Do not modify or disassemble.

Do not modify or disassemble. It may cause a malfunction and accidents such as fire, injury, etc.

 **CAUTION** Make sure to isolate the strong current system wiring and weak current system wiring from each other.

Make sure to isolate the strong current system wiring and weak current system wiring from each other and do not provide any common grounding. Otherwise, electric noise accumulated on the weak current system wiring may cause a malfunction.

 **WARNING** When designing the system, make sure to specify electrical wire of a suitable size for the specified current capacity.

Make sure to use electrical wire of a suitable size for the specified current capacity. If the electrical wire is not thick enough, the insulator may melt and cause an insulation failure. The failure may cause an electric shock, electric leakage, or fire.

 **CAUTION** Check the surrounding environment.

Do not mount the products in an environment or location exposed to dust, oil mist, conductive dust, corrosive gas, high temperature, condensation, wind, and rain. Additionally, do not mount the products in a location where vibration or shock is directly applied. Otherwise, it may lead to damage, malfunction, and deterioration of the products.

Notes

- We shall not be held responsible for any damages and losses caused by repair, disassembly, or modification performed by a third party other than Mitsubishi Electric Corporation or those appointed by Mitsubishi Electric Corporation.
- The safety precautions and specifications shown in this catalog are subject to change without prior notice.

Trademarks and Registered Trademarks

- Microsoft, Microsoft Access, ActiveX, Excel, SQL Server, Visual Basic, Visual C++, Visual C#, Visual Studio, Windows, Windows NT, Windows Server, Windows Vista, and Windows XP are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- The company names, system names and product names mentioned in this document are either registered trademarks or trademarks of their respective companies.
- In some cases, trademark symbols such as '™' or '®' are not specified in this document.

Creating Solutions Together.



Low-voltage Power Distribution Products



Transformers, Med-voltage Distribution Products



Power Monitoring and Energy Saving Products



Power (UPS) and Environmental Products



Compact and Modular Controllers



Servos, Motors and Inverters



Visualization: HMIs



Edge Computing Products



Numerical Control (NC)



Collaborative and Industrial Robots



Processing machines: EDM, Lasers




SCADA, analytics and simulation software

Mitsubishi Electric's product lineup, from various controllers and drives to energy-saving devices and processing machines, all help you to automate your world. They are underpinned by software, innovative data monitoring, and modelling systems supported by advanced industrial networking and Edgecross IT/OT connectivity. Together with a worldwide partner ecosystem, Mitsubishi Electric factory automation (FA) has everything to make IoT and Digital Manufacturing a reality.

With a complete portfolio and comprehensive capabilities that combine synergies with diverse business units, Mitsubishi Electric provides a one-stop approach to how companies can tackle the shift to clean energy and energy conservation, carbon neutrality and sustainability, which are now a universal requirement of factories, buildings, and social infrastructure.

We at Mitsubishi Electric FA are your solution partners waiting to work with you as you take a step toward the realization of sustainable manufacturing and society through the application of automation. Let's automate the world together!



MITSUBISHI ELECTRIC CORPORATION

HEAD OFFICE: TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

www.MitsubishiElectric.com