



for a greener tomorrow



**MITSUBISHI
ELECTRIC**

Changes for the Better

FACTORY AUTOMATION

Ethernet-based Open Network CC-Link IE Compatible Servo System

Emancipation of IA components
from shackles of the conventional Network



CC-Link *IE* *Field*

MITSUBISHI SERVO AMPLIFIERS & MOTORS

**MELSERVO
SYSTEM**

GLOBAL IMPACT OF MITSUBISHI ELECTRIC



Through Mitsubishi Electric's vision, "Changes for the Better" are possible for a brighter future.

Changes for the Better

We bring together the best minds to create the best technologies. At Mitsubishi Electric, we understand that technology is the driving force of change in our lives. By bringing greater comfort to daily life, maximizing the efficiency of businesses and keeping things running across society, we integrate technology and innovation to bring changes for the better.

Mitsubishi Electric is involved in many areas including the following

Energy and Electric Systems

A wide range of power and electrical products from generators to large-scale displays.

Electronic Devices

A wide portfolio of cutting-edge semiconductor devices for systems and products.

Home Appliance

Dependable consumer products like air conditioners and home entertainment systems.

Information and Communication Systems

Commercial and consumer-centric equipment, products and systems.

Industrial Automation Systems

Maximizing productivity and efficiency with cutting-edge automation technology.

OVERVIEW

Concept	3
Product Lines	17
Servo Amplifiers	19
Servo Motors	25
Simple Motion Modules	31
Engineering Software	43
CC-Link Partner Association (CLPA)	47
Support	48
Warranty	49

1

2

3

4

5

6



Extensive visualization with advanced data connectivity

Big Data analytics requires deterministic data collection, which can be realized by incorporating two key features: SLMP*¹ that enables seamless connectivity between devices in the IT layer and on the shop floor; and a high-speed, large-capacity 1 Gbps communications network that enables the handling of large-data, such as production, quality and control data between different production processes.

*1. Seamless Message Protocol


*2. MELSEC iQ-R Series is supported by GX Works3.
MELSEC-Q Series and MELSEC-L Series are supported by GX Works2.

General, motion and safety control integrated into one network

CC-Link IE incorporates generic distributed control, synchronous motion control, and safety control enabling safety communications across multiple safety devices, all on the same network. The topology is quite versatile, based on twisted-pair cables, which enables flexibility in system configuration while helping to keep installation cost low.


Comprehensive diagnosis realizing higher reliability

Disruptions to the control system are kept to a minimum via comprehensive diagnostics functions, high communications integrity owing to the noise-resistant characteristics of the optical cable, and communication re-routing capabilities made possible as the result of using a ring topology. Also, network errors can be rectified quickly by visualizing the network system image using the engineering software*², and remotely from a GOT (HMI) directly on the machine or production line.




Seamless connectivity within all levels of automation

The backbone of e-F@ctory, leveraging connectivity between the shop floor and IT



CONNEC





T FLEXIB

Emancipation of IA components from shac



LY

kles of the conventional Network

A dramatic new update of the Mitsubishi Electric Servo System with CC-Link IE Field bringing vast possibilities to the world of Industrial Automation

- Reduced wiring, improved noise-immunity drastically improve ease of use.
- Mitsubishi Electric CC-Link IE and Partner products are designed with simple connectivity in mind.
- Access easily from anywhere is possible for maximum flexibility to perform engineering tasks from programming to diagnosis.



! IA Components

■ Integration of IA components on a single network of CC-Link IE

Optimizing conventional servo systems can be challenging and requires high cost and time commitments during start-up, operation, and maintenance. A key solution to this issue is the network.

What if we could connect all the components from servo amplifiers and inverters to high-speed counters, I/O modules, etc., over a single network?

CC-Link users have simplified system configurations, reduced wiring, and significantly improved diagnostic efficiency.

The Mitsubishi Servo System is the optimized CC-Link IE Field compatible system, solving common network issues by connecting all components over a single network.

All-in-One Network

1
Concept




CC-Link IE Field Network - Integration of IA components on ONE single network

CC-Link IE Field Network is a single network which combines the versatility of Ethernet and highly accurate synchronous operation for Motion control. With the single network, various field devices, such as servo amplifiers, I/O modules, and high-speed counter modules, are connected with no restriction.

CC-Link IE Field Network enables a further upgrade of your machine with the flexible servo system configuration.

All-in-One Engineering Software



Covering all aspects of the product development cycle - From Easy Settings to Diagnosis with ONE engineering software

To meet customer needs, such as easy programming, easy startup, and easy maintenance, we offer the All-in-One engineering software as an easy manipulation tool with various new functions and technology.

Various tasks, such as Simple Motion parameter settings, servo adjustment, and debugging as well as creating a sequence program, such as a function block (FB), are performed only with this All-in-One engineering software.

Flexible Servo System Configuration with CC-Link IE Field Network

Synchronous control up to μsec precision, suitable for high-accuracy positioning

Simple Motion module

+

Motion mode

This system configuration is suited for a wide range of high-accuracy motion control, such as multi-axis interpolation, synchronous, and speed-torque control.




A high flexibility enabling versatile control with Motion and I/O modes

Simple Motion module

+

Motion mode + I/O mode

This system configuration enables an easy addition of an axis for single-axis positioning to a machine which requires a wide range of high-accuracy motion control, such as multi-axis interpolation, synchronous, and speed-torque control.




Compatible with a wide range of applications for positioning control

CC-Link IE embedded CPU

+

I/O mode


This system configuration enables an easy connection of the axis for single-axis positioning to a master station, such as a CC-Link IE embedded CPU without the Simple Motion module.



Motion mode: This mode enables advanced motion control, such as positioning for multi-axis interpolation, synchronous, and speed-torque control in combination with the Simple Motion module.

I/O mode: This mode easily drives a belt conveyor, a rotary table, a ball screw mechanism, etc. by using the built-in positioning function in a servo amplifier.

[Dispensing Machine for FPD] Using Motion mode



■ Motion mode


Application examples

Dispensing machines for FPD, Packing machines, Pressing machines, X-Y tables, and Converting machines

Main functions

- Tandem control of a gantry application
- 2-axis continuous trajectory control
- Advanced synchronous control

[Packing and Liquid Filling Machines] Using Motion mode and I/O mode



■ Motion mode

Application examples

Packing machines, Liquid filling machines, Material handling machines, and Converting machines

Main functions

- Advanced synchronous control
- Cam control
- Cam auto-generation
- Mark detection function

■ I/O mode


Application examples

Material handling axes and Belt conveyor axes

Main functions

- Speed control
- Positioning control

[Belt Conveyor Axis] Using I/O mode



■ I/O mode

Application examples


Material handling axes and Belt conveyor axes

Main functions

- Speed control
- Positioning control

Synchronization of Inputs and Outputs with Servo Control


1 Concept



[An example of inputs and outputs synchronized with the command communication cycle of a servo amplifier]

In a single network, inputs/outputs are synchronized with the command communication cycle of the servo amplifier. For example, an input from a synchronous encoder and an output to a printing machine are synchronized in the same network. CC-Link IE Field Network enables a wide range of Motion control applications.

Flexible network topology




Using the switching hub enables the network configuration with a combination of star, line, and star/line mixed topologies to be easily modified without any settings. An easy topology created only by a cable being connected to a free port of the switching hub allows field devices to be added to the system more flexibly.

Star topology

Each module is connected via the switching hub allowing field devices to be added easily.

Line topology

Continuous connection of modules along the Ethernet line.



A wide range of product series and capacities for various system applications


MELSERVO-J4 series is the newest member to the MELSERVO family, backed by Mitsubishi leadership in all-digital technology. With the Ethernet-based "CC-Link IE Field Network", safety, and energy-efficient design of the new MELSERVO-J4 series - man, machine, and environment can at last work together in perfect harmony.



From rotary to linear and direct drive motors, a wide range of servo motors is available.


Rotary servo motors are available in capacities from 50 W to 7 kW.

Linear servo motors and direct drive motors satisfy new needs in driving control by providing high rigidity, performance, and flexibility in system configurations unique to direct drive. These motors also offer easy maintenance and cleanliness.



iQ Platform for maximum return on investment

Minimize TCO, Seamless integration, Maximize productivity, Transparent communications: these are common items that highlight the benefits of the iQ Platform and e-F@ctory. The iQ Platform minimizes TCO at all phases of the automation life cycle by improving development times, enhancing productivity, reducing maintenance costs, and making information more easily accessible across the plant. Together with e-F@ctory, offering various best-in-class solutions through its e-F@ctory alliance program, the capabilities of the manufacturing enterprise is enhanced even further realizing the next level for future intelligent manufacturing plants.



Further reduce TCO while securing your manufacturing assets

Automation Controller

Improve productivity and product quality

1. High-speed system bus realizing improved system performance
2. On-screen multi-touch control enabling smooth GOT (HMI) operations

Integrated Network

Best-in-class integrated network optimizing production capabilities

1. CC-Link IE supporting 1 Gbps high-speed communication
2. Seamless connectivity within all levels of manufacturing with SLMP

Centralized Engineering

Integrated engineering environment with system level features

1. Automatic generation of system configuration
2. Share parameters across multiple engineering software via MELSOFT Navigator
3. Changes to system labels are reflected between PAC and HMI




Mitsubishi Servo System

As the leading supplier of automation products and solutions worldwide, Mitsubishi Electric, known for its high quality and diverse range of automation products including servo system controllers, servo amplifiers, and servo motors, together with "CC-Link IE Field Network" and our exclusive engineering software, boasts a whole range of solutions specific to your needs.

SOLUTION



HUMAN MACHINE I/F
CONTROLLER



e-F@ctory is the Mitsubishi Electric solution for improving the performance of any manufacturing enterprise by enhancing productivity, and reducing the maintenance and operation costs together with seamless information flow throughout the plant.

Graphic Operation Terminal

Personal computer



SOFTWARE

SERVO AMPLIFIER
LOW-VOLTAGE
SWITCHGEAR

Programmable Controller Engineering Software
MELSOFT GX Works3

Programmable Controller Engineering Software
MELSOFT GX Works2


Servo Setup Software
MELSOFT MR Configurator2

Capacity Selection Software


NETWORK

SERVO MOTOR


Rotary servo motor




Small capacity,
low inertia
HG-KR series
Capacity: 50 to 750 W




Small capacity,
ultra-low inertia
HG-MR series
Capacity: 50 to 750 W




Medium capacity,
medium inertia
HG-SR series
Capacity: 0.5 to 7 kW



Medium/large capacity,
low inertia
HG-JR series
Capacity: 0.5 to 7 kW





Medium capacity,
ultra-low inertia
HG-RR series
Capacity: 1 to 5 kW



Medium capacity,
flat type
HG-UR series
Capacity: 0.75 to 5 kW



Mitsubishi Electric's integrated FA platform for achieving lateral integration of controllers & HMI, engineering environments and networks at production sites.





CC-Link IE Field Network Compatible Servo Amplifier

MR-J4-GF NEW

MR-J4-GF-RJ NEW

CC-Link IE Field Network compatible servo amplifier executes positioning of one or multiple axes, synchronous control, and speed-torque control by being connected to the various master modules compatible with CC-Link IE Field Network, including the Simple Motion module, and CC-Link IE embedded CPU module, etc.

CC-Link IE Field Network Compatible Servo Amplifier

Features

Two types of modes are available according to your needs:

- Motion mode for a wide range of motion control such as positioning of multiple axes, synchronous control, etc.
- I/O mode for positioning of one axis

●: Compatible

Connectable module with MR-J4-GF	MR-J4-GF	
	Motion mode	I/O mode
Simple Motion module	●	●
CC-Link IE embedded CPU module	—	●
Master/local module	—	●

Wide Range of Capacities and Series

The servo amplifiers support motors from rotary servo motors to linear servo motors and direct drive motors, and greatly enhance system performance.

Diagnosis

Reading information of the servo amplifier from the PLC CPU via a network helps the preventive maintenance such as the machine diagnosis.

Product Lines

●: Compatible ■: Available in the future

Model	Power supply	Fully closed loop control (Note-2)	Servo motor			Capacity range [kW]		
			Rotary	Linear (Note-3)	Direct drive			
MR-J4-GF	200 V	●	●	●	●	0.1 kW	■ 7 kW	■ 11 kW to 22 kW
MR-J4-GF-RJ (Note-1)	400 V	●	●	● (Note-4)	—	0.6 kW	■ 7 kW	■ 11 kW to 22 kW

(Note-1): MR-J4-GF-RJ is compatible with two-wire type and four-wire type serial linear encoders, and pulse train interface (A/B/Z-phase differential output type) linear encoders. MR-J4-GF-RJ is compatible with DC power supply input.

(Note-2): MR-J4-GF is compatible only with two-wire type serial linear encoders. For four-wire type serial linear encoders and pulse train interface (A/B/Z-phase differential output type) linear encoders, use MR-J4-GF-RJ.

(Note-3): MR-J4-GF is compatible only with two-wire type and four-wire type serial linear encoders. For pulse train interface (A/B/Z-phase differential output type) linear encoders, use MR-J4-GF-RJ.


(Note-4): Linear servo motor (400 V) will be compatible in the future.

Control Mode

Motion mode

Combined with the Simple Motion module, the servo amplifier can perform advanced motion control including multiple-axis positioning and synchronous control, in addition to speed and torque control.

[Function block (FB)]




[Positioning data]

No.	Operation	Control	...	Address
1	1:CONT	08h:INC 2	...	200000.0
2	0:END	08h:INC 2	...	-200000.0

Positioning operation is executed easily from a function block (FB).

RD77GF




The motion mode enables motion control including tandem control, 2-axis (X-Y) continuous trajectory control, and synchronous control for gantry applications.

I/O mode

Combined with the CC-Link IE embedded CPU or a master/local module, the servo amplifier can perform positioning operations just as easy as I/O operations, suitable for belt conveyers, rotary tables, ball screws, etc.

[Function block (FB)]





[Point table example]

No.	Position data	Speed	...	M-code
1	1000	2000	...	1
2	2000	1600	...	2
...
255	3000	3000	...	99

Setting position data (target position), servo motor speed, and acceleration/deceleration time constants in point table is as easy as setting a parameter.

CC-Link IE embedded CPU module (R04ENCPU)







Positioning operation will be executed after the point table No. is selected and started from the function block (FB).

Industry-leading Level of Servo Amplifier Basic Performance

[Settling time comparison]



[Dedicated execution engine]




Speed frequency response of 2.5 kHz is achieved by applying our original high-speed servo control architecture evolved from the conventional two-degrees-of-freedom model adaptive control to the dedicated execution engine. Together with a high-resolution absolute position encoder of 4,194,304 pulses/rev, fast and accurate operation is enabled. The performance of the high-end machines is utilized to the fullest.

Servo Gain Adjustment

The following two functions are available for adjusting servo gain: auto tuning that eliminates a manual servo adjustment and one-touch tuning function that enables an advanced servo gain adjustment.

Auto tuning


Servo gain is automatically adjusted to an optimum value for a machine in real time when the servo amplifier is operated in auto tuning mode.



One-touch tuning function


Just turn on the one-touch tuning function to complete servo gain adjustment automatically, including machine resonance filter, advanced vibration suppression control II (Note-1), and robust filter for maximizing your machine performance. This function also sets responsiveness automatically, while the real-time auto tuning requires manual setting.

(Note-1): The advanced vibration suppression control II automatically adjusts one frequency.



Start tuning just by clicking.


Adjustment results are displayed.





Machine, Man, Environment in perfect harmony

Functions According to IEC/EN 61800-5-2



STO (Safe torque off) is integrated as standard, enabling the safety system to be configured easily in the machine.


- By using STO, it is not necessary to turn off the control power of the servo amplifier, resulting in shorter restart time. In addition, home position return is not also necessary.
- Magnetic contactor for preventing unexpected motor start is not needed. (Note-1)

(Note-1): For MR-J4 series servo amplifier, magnetic contactors are not required to meet the STO requirements. However, this figure has a magnetic contactor installed to prevent servo alarms and electric shock.

IEC/EN 61800-5-2:2007 function	Safety level
STO (Safe torque off)	Category 3, PL e, SIL 3 (Note-2)

(Note-2): Parameter setting is required to meet Category 3, PL e, SIL 3.

Touch Probe Function




The touch probe function latches a current position when the registration mark signal is turned ON.

The current position is transmitted to the Simple Motion module via CC-Link IE Field Network and used for compensating the servo amplifier axis.

Direct Access to IT System


Information of the servo amplifiers and the servo motors is collected via CC-Link IE Field Network. The information is centralized by a host system and can be used for managing the status of the entire line. The CC-Link IE Field Network compatible servo system helps IoT (Note-1) of the machine.

(Note-1): IoT (Internet of Things)




Power Monitoring Function

Driving/regenerative power is calculated from the data such as speed and current in the servo amplifier, and MR Configurator2 monitors the operation data including power consumption. The data are transmitted to a servo system controller, and the power consumption is analyzed and displayed.




Preventive Maintenance

Machine diagnosis function detects changes of machine parts (ball screw, guide, bearing, belt, etc.) by analyzing machine friction, load moment of inertia, unbalanced torque, and changes in vibration component from the data inside the servo amplifier, supporting timely maintenance of the driving parts. In addition, the data are transferred to the host system and used to monitor the entire line.




Backup/Restoration


Parameters of servo amplifiers, I/O modules, and inverters which are connected to CC-Link IE Field Network are backed up and restored by the PLC CPU and GOT2000. Therefore, the efficiency of replacement and maintenance of the modules is improved.



Large Capacity Drive Recorder

Servo data such as motor current and position command before and after the alarm occurrence are stored in non-volatile memory of the servo amplifier. Reading the servo data on MELSOFT MR Configurator2 helps you analyze the cause of the alarm.





Servo Motor

Rotary Servo Motor

Linear Servo Motor

Direct Drive Motor

HG Series
LM Series
TM-RFM Series

Rotary Servo Motor HG Series

High-speed, high-torque servo motors for fast, precise machine operation

■ High-resolution Absolute Position Encoder


Servo motors are equipped with a high-resolution absolute position encoder of 4,194,304 pulses/rev (22-bit) as standard, increasing positioning accuracy.

■ Improved Environmental Resistance

HG-KR/HG-MR/HG-RR/HG-UR and HG-SR/HG-JR are rated IP65 and IP67 ^(Note-1), respectively. ^(Note-2)


(Note-1): HG-JR1000 r/min series 15 kW or larger, and HG-JR1500 r/min series 22 kW or larger are rated IP44. HG-JR series servo motors of 8 kW or larger will be compatible in the future.

(Note-2): The shaft-through portion is excluded.



■ Cable Leading Direction

Cables for power, encoder, and electromagnetic brake are capable of connecting either in direction or in opposite direction of the load side, depending on the cable selection. (HG-KR, HG-MR series)



Product lines

Compatible in the future

Series	Rated speed [r/min]	Maximum speed [r/min]	Capacity range [kW]					IP rating (Note-1)
HG-KR	3000	6000	0.05 kW		0.75 kW			IP65
HG-MR	3000	6000	0.05 kW		0.75 kW			IP65
HG-SR	1000	1500		0.5 kW	4.2 kW			IP67
	2000	3000		0.5 kW	7 kW			IP67
HG-JR	3000	6000/5000		0.5 kW	9 kW			IP67
	1500	3000/2500			7 kW	22 kW		IP67/IP44
	1000	2000/1500			6 kW	25 kW		IP67/IP44
HG-RR	3000	4500		1 kW	5 kW			IP65
HG-UR	2000	3000/2500		0.75 kW	5 kW			IP65

0.01 kW 0.1 kW 1 kW 10 kW 100 kW

(Note-1): The shaft-through portion is excluded.

HG-KR/HG-MR



HG-KR: Small capacity, low inertia. Perfect for general-purpose industrial machines.

HG-MR: Small capacity, ultra-low inertia. Perfect for high-throughput operations.

Capacity: 50 W to 750 W Rated speed: 3000 r/min Maximum speed: 6000 r/min

[Application example]

- Inserters, mounters and bonders ●PCB drilling machines
- In-circuit testers and label printers ●Knitting and embroidery machines
- Compact robots and robot hand sections

HG-SR



Medium capacity, medium inertia. Suitable for machines having large load inertia.

Capacity: 0.5 kW to 7 kW Rated speed: 1000 r/min and 2000 r/min

[Application example]

- Material handling systems ●Dedicated machines ●Robots
- Loaders and unloaders ●Winders and tension units ●Turrets ●X-Y tables

HG-JR



Medium to large capacity, low inertia. Perfect for high-throughput positioning or high acceleration/deceleration operations.

Capacity: 0.5 kW to 7 kW Rated speed: 1000 r/min, 1500 r/min, and 3000 r/min

[Application example]

- Food packaging machines ●Printers ●Injection molding machines ●Press machines

HG-RR



Medium capacity, ultra-low inertia. Perfect for high-throughput operation.

Capacity: 1 kW to 5 kW Rated speed: 3000 r/min

[Application example]

- Roll feeders ●Loaders and unloaders
- Ultra high-throughput material handling systems

HG-UR



Medium capacity, flat type. Perfect for applications with limited mounting space.

Capacity: 0.75 kW to 5 kW Rated speed: 2000 r/min

[Application example]

- Robots ●Conveyors ●Winders and tension machines
- Food processing machines


Linear Servo Motor

Suitable for linear motion systems requiring high speed and accuracy


Basic Performance

- Supporting maximum speed of 3 m/s (LM-H3 series)
- Supporting maximum thrust of 150 N to 18000 N
Small size and high thrust are achieved by the increased winding density and the optimized core and magnet geometries as a result of electromagnetic field analysis.
- Available in four types: core, liquid-cooling core, magnetic attraction counter-force core, and coreless types
- Supporting A/B/Z-phase differential output type linear encoders (MR-J4-GF-RJ)
- Enabling an advanced system including high-accuracy tandem synchronous control with a combination of the servo amplifiers and the CC-Link IE Field Network compatible servo system controller

Tandem configuration




Multi-head configuration



Product lines

Series	Maximum speed [m/s]	Magnetic attraction force [N]	<div><div></div>Continuous thrust [N]</div> <div><div></div>Maximum thrust [N]</div> <div><div></div>Compatible in the future</div>	IP rating
LM-H3	3	630 to 8800	<div><div>70 N</div><div>175 N</div><div>960 N</div><div>2400 N</div></div>	IP00
LM-F	2	4500 to 45000	(Natural cooling) <div><div>300 N</div><div>1800 N</div><div>3000 N</div><div>18000 N</div></div>	IP00
			(Liquid cooling) <div><div>600 N</div><div>1800 N</div><div>6000 N</div><div>18000 N</div></div>	
LM-K2	2	0	<div><div>120 N</div><div>2400 N</div><div>6000 N</div></div>	IP00
LM-U2	2	0	<div><div>50 N</div><div>800 N</div><div>3200 N</div></div>	IP00
			10100100010000100000	



Direct Drive Motor

For compact and simplified machine driving part with high-accuracy control


Basic Performance

- High performance with the latest technologies
Our latest magnetic design and winding technologies enable high torque density. In addition, extremely smooth rotation is achieved by the minimized torque ripple.
- Compact and low-profile design
Due to high level of structural design technology, compact and low-profile design is achieved. This design enables a small mounting space and a low center of gravity.
- 20-bit high-resolution absolute position encoder
The direct drive motor is equipped with 20-bit high-resolution absolute position encoder (1,048,576 pulses/rev) as standard, increasing positioning accuracy.
- Hollow shaft diameter range: $\varnothing 20$ mm to 104 mm
The motor is equipped with a large hollow shaft resulting from using bearing and encoder with large diameter. It allows cables and air tubing to pass through.

Product lines

Series	Rated speed [r/min]	Maximum speed [r/min]	Rated torque [N·m]	Maximum torque [N·m]	IP rating ^(Note-1)
TM-RFM	200	500	2 N·m	6 N·m	IP42
	200	500	6 N·m	18 N·m	IP42
	200	500	12 N·m	72 N·m	IP42
	100	200	40 N·m	240 N·m	IP42


(Note-1): Connectors and gap between rotor and stator are excluded.



MR-J4-GF Product lines

■ Servo amplifier

●: Compatible —: Not compatible

Servo amplifier ^{(*)5}		Number of control axes	Power supply specifications	Rated output [kW] ^{(*)1}	Control mode				Compatible servo motor series												
					Position	Speed	Torque	Positioning function	Fully closed loop control ^{(*)2}	HG-KR	HG-MR	HG-SR	HG-JR	HG-AK	HG-RR	HG-UR	LM-H3	LM-F	LM-K2	LM-U2	TM-RFM
CC-Link IE Field Network	MR-J4-GF(-RJ) ^{(*)4} <div>NEW</div>	1 axis	3-phase 200 VAC	0.1, 0.2, 0.4, 0.6, 0.75, 1, 2, 3.5, 5, 7	●	●	●	●	●	●	●	●	●	—	●	●	●	●	●	●	
			3-phase 400 VAC	0.6, 1, 2, 3.5, 5, 7	●	●	●	●	●	—	—	●	●	—	—	—	—	—	—	—	

*1. The listed are the rated output of the servo amplifier. For the compatible servo motor capacities, refer to "MELSERVO-J4 catalog (L(NA)03058)."





*2. MR-J4-GF is compatible with two-wire type serial linear encoders. For four-wire type serial linear encoders and pulse train interface (A/B/Z-phase differential output type) linear encoders, use MR-J4-GF-RJ.

*3. MR-J4-GF is compatible with two-wire type and four-wire type serial linear encoders. For pulse train interface (A/B/Z-phase differential output type) linear encoders, use MR-J4-GF-RJ.


*4. MR-J4-GF(-RJ) of 11 kW or larger will be available in the future.

*5. Some functions are available only with the servo amplifier with specific versions. Refer to relevant Servo Amplifier Instruction Manual for details.

■ Linear servo motor







Linear servo motor series	Maximum speed [m/s]	Continuous thrust [N] ^(*)1, 2)	Maximum thrust [N] ^(*)1, 2)	Cooling method	Features	Application examples
Core type   	3.0	9 types 70, 120, 240, 360, 480, 720, 960	175, 300, 600, 900, 1200, 1800, 2400	Natural cooling	Suitable for space-saving. Compact size and high thrust. Maximum speed: 3 m/s.	<ul style="list-style-type: none"> •Mounters •Wafer cleaning systems •LCD assembly machines •Material handlings
	2.0	8 types 300, 600, 900, 1200, 1800, 2400, 3000	1800, 3600, 5400, 7200, 10800, 14400, 18000	Natural cooling	Compact size. The integrated liquid-cooling system doubles the continuous thrust.	<ul style="list-style-type: none"> •Press feeders •NC machine tools •Material handlings
	2.0	8 types 600, 1200, 1800, 2400, 3600, 4800, 6000	1800, 3600, 5400, 7200, 10800, 14400, 18000	Liquid cooling		
Coreless type 	2.0	7 types 120, 240, 360, 720, 1200, 1440, 2400	300, 600, 900, 1800, 3000, 3600, 6000	Natural cooling	High thrust density. Magnetic attraction counter-force structure enables longer life of the linear guides and lower audible noise.	<ul style="list-style-type: none"> •Mounters •Wafer cleaning systems •LCD assembly machines
	2.0	9 types 50, 75, 100, 150, 225, 400, 600, 800	150, 225, 300, 450, 675, 1600, 2400, 3200	Natural cooling	No cogging and small speed fluctuation. No magnetic attraction force structure extends life of the linear guides.	<ul style="list-style-type: none"> •Screen printing systems •Scanning exposure systems •Inspection systems •Material handlings

*1.  will be compatible in the future with 400 V.

*2.  will be compatible in the future.

Rotary servo motor

●: Available —: Not available

Rotary servo motor series		Rated speed (maximum speed) [r/min]	Rated output [kW] (*1)	Servo motor type			IP rating (*3)	Features	Application examples
				With electro-magnetic brake (B)	With reducer (G1) (*2)	With reducer (G5, G7) (*2)			
Small capacity	HG-KR series 	3000 (6000)	5 types 0.05, 0.1, 0.2, 0.4, 0.75	●	●	●	IP65	Low inertia Perfect for general industrial machines.	•Belt drives •Robots •Mounters •Sewing machines •Food processing machines •Semiconductor manufacturing equipment •Knitting and embroidery machines
	HG-MR series 	3000 (6000)	5 types 0.05, 0.1, 0.2, 0.4, 0.75	●	—	—	IP65	Ultra-low inertia Well suited for high-throughput operations.	•Inserters •Mounters
Medium capacity	HG-SR series 	1000 (1500)	6 types 0.5, 0.85, 1.2, 2.0, 3.0, 4.2	●	—	—	IP67	Medium inertia This series is available with two rated speeds.	•Material handling systems •Robots
		2000 (3000)	14 types 0.5, 1.0, 1.5, 2.0, 3.5, 5.0, 7.0 0.5, 1.0, 1.5, 2.0, 3.5, 5.0, 7.0	●	●	●	IP67		
Medium/large capacity	HG-JR series (*6) 	3000 (6000: 0.5 to 5 kW 5000: 7, 9 kW)	18 types 0.5, 0.75, 1.0, 1.5, 2.0, 3.5, 5.0, 7.0, 9.0 0.5, 0.75, 1.0, 1.5, 2.0, 3.5, 5.0, 7.0, 9.0	●	—	—	IP67	Low inertia Well suited for high-throughput and high-acceleration/ deceleration operations.	•Food packaging machines •Printing machines
		1500 (3000: 7 to 15 kW 2500: 22 kW)	14 types 7.0, 11, 15, 22 7.0, 11, 15, 22	● (*5)	—	—	IP67/ IP44 (*4)		•Injection molding machines •Press machines
		1000 (2000: 6 to 12 kW 1500: 15 to 25 kW)	16 types 6.0, 8.0, 12, 15, 20, 25 6.0, 8.0, 12, 15, 20, 25	● (*5)	—	—	IP67/ IP44 (*4)		
Medium capacity	HG-RR series 	3000 (4500)	5 types 1.0, 1.5, 2.0, 3.5, 5.0	●	—	—	IP65	Ultra-low inertia Well suited for high-throughput operations.	•Ultra-high-throughput material handling systems
Medium capacity, flat type	HG-UR series 	2000 (3000: 0.75 to 2 kW 2500: 3.5, 5 kW)	5 types 0.75, 1.5, 2.0, 3.5, 5.0	●	—	—	IP65	Flat type The flat design makes this unit well suited for situations where the installation space is limited.	•Robots •Food processing machines

*1. : For 400 V.

*2. G1 for general industrial machines. G5 and G7 for high precision applications.

*3. The shaft-through portion is excluded. Refer to "MELSERVO-J4 catalog (L(NA)03058)" for the shaft-through portion.


For geared servo motor, IP rating of the reducer portion is equivalent to IP44.

*4. For HG-JR1500 r/min series, 15 kW or smaller is rated IP67, and 22 kW is rated IP44. For HG-JR 1000 r/min series, 12 kW or smaller is rated IP67, and 15 kW or larger is rated IP44.

*5. The servo motor with electromagnetic brake is not available for HG-JR 1500 r/min series 22 kW, and 1000 r/min series 15 kW or larger.

*6. HG-JR series servo motors of 8 kW or larger will be compatible in the future.

Direct drive motor

Direct drive motor series	Motor outer diameter [mm]	Hollow shaft diameter [mm]	Rated speed [r/min]	Maximum speed [r/min]	Rated torque [N·m]	Maximum torque [N·m]	IP rating (*1)	Features	Application examples
TM-RFM series 	φ130	φ20	200	500	3 types 2, 4, 6	6, 12, 18	IP42	•Suitable for low-speed and high-torque operations. •Smooth operation with less audible noise. •The motor's low profile design contributes to compact construction and a low center of gravity for enhanced machine stability. •Clean room compatible.	•Semiconductor manufacturing devices •Liquid crystal manufacturing devices •Machine tools
	φ180	φ47	200	500	3 types 6, 12, 18	18, 36, 54	IP42		
	φ230	φ62	200	500	3 types 12, 48, 72	36, 144, 216	IP42		
	φ330	φ104	100	200	3 types 40, 120, 240	120, 360, 720	IP42		

*1. Connectors and gap between rotor and stator are excluded.




The Simple Motion module is the module that enables various motion control, such as positioning including interpolation and trajectory control, synchronous, cam, and speed-torque control.

Advanced motion control is easily performed by parameter settings and a sequence program, such as a function block (FB).

The 4, 8, and 16-axis models are available to best suit your control needs.

CC-Link IE Field Network Compatible Simple Motion Module

This CC-Link IE Field Network compatible Simple Motion module has not only a function for Motion control, but also a function as a master station of CC-Link IE Field Network.



Motion mode

This mode enables advanced Motion control, such as positioning for multi-axis interpolation, synchronous, and speed-torque control in combination with the Simple Motion module.

Maximum number of control axes: 16 axes


I/O mode

This mode easily drives a belt conveyor, a rotary table, a ball screw mechanism, etc. by using the built-in positioning function in a servo amplifier.

Number of control stations: 120 stations

RD77GF: Including the number of motion mode compatible servo amplifiers
QD77GF: 16 motion mode compatible servo amplifiers + 104 I/O devices

CC-Link IE Field Network Master Station



The CC-Link IE Field Network compatible Simple Motion module is equipped with functions as a link device and a master station equivalent to a CC-Link IE field Network master/local module. (Note-1)

Suppressing the cost of a system configuration is possible since this module is used not only for Motion control, but also as a master station of the network.

(Note-1): The sub-master and safety communication functions are not supported.

Maximum link points per network

Item	RD77GF	QD77GF	Master module
Remote input (RX)/Remote output (RY)	16k points each (16384 points, 2k byte)	8k points each (8192 points, 1k byte)	16k points each (16384 points, 2k byte)
Remote register (RWw, RWr)	8k points each (8192 points, 16k byte)	1k points each (1024 points, 2k byte)	8k points each (8192 points, 16k byte)

Diagnosis and Setting Functions by CC-Link IE Field Network


Setting parameters and collecting information of field devices are possible from anywhere via CC Link IE Field Network.

Easy parameter settings

Selecting each field device on the screen of CC-Link IE Field configuration via drag & drop enables easy parameter settings.

Easy diagnosis of network

Engineering software enables users to identify network errors at a glance. The users can instantly identify the cause of trouble when it occurs thus downtime will be shortened.




Programming

Control, such as positioning control, is easily executed by a sequence program, such as a function block (FB) being started.


Function Block Compatible in the future

The sequence program using FBs is created with the same interface regardless of whether the motion mode or the I/O mode is used.




Sequence Program

The operation starts from the designated positioning data No. in the sequence program.




Extensive Motion control

A wide range of control, such as positioning, speed-torque, cam, and synchronous control, is applicable to various machines, such as X-Y tables, packaging machines, and converting machines. Selecting the best suitable control methods and functions for your application achieves optimal solutions.




■ Positioning control (Interpolation Function and Trajectory Control)

Positioning control is easily performed with a Motion profile table in the sequence program.



- To respond to various application needs, the Simple Motion module offers various control methods, such as linear interpolation, 2-axis circular interpolation, fixed-pitch feed, and continuous trajectory control.
- Setting positioning addresses and speeds, etc. in the sequence program enables automatic operation.
- Powerful auxiliary functions, such as M-code output, skip, speed change, and target position change functions, are available.

■ Advanced Synchronous Control



The advanced synchronous control can be achieved using software instead of controlling mechanically with physical gears, shafts, clutches, speed change gears or cams etc. Additionally, a cam is easily created with the cam auto-generation function. The synchronous control is started/ended on an axis-by-axis basis, thus enabling mixed axes of synchronous control and positioning control in one project.


(Note-1): MR-J4-GF-RJ is required when the serial absolute synchronous encoder is used.

Module configuration of synchronous control

The whole module configuration of the advanced synchronous control is displayed in one screen, and monitoring of the target modules is also viewed, which enables more efficient debugging.



Synchronous control parameters




Module configuration

- Synchronous control is easily performed only with parameter settings.
- All the output axes that are connected to the main shaft main input axes modules are displayed in the monitoring screen.
- Monitoring on each module and parameter settings are possible.

■ Speed-torque Control

The Simple Motion module is used for tension control, such as unwinding or rewinding applications. Since the current position is controlled even during the speed-torque control, the positioning operation based on the absolute position coordinates is performed after switching from the speed-torque control back to the position control.



Various Functions

JOG operation

While the JOG start signal is ON, the workpiece is being moved in the designated direction.

JOG operation can be used without completing home position return.

Motion profile table

A motion profile table, where position data and feed speed are set, is used in this automatic operation. Once the start operation signal is turned ON, instructions are executed sequentially from the set start point to the set end point.

Stroke limit functions

This function is used to establish the physical movable range for a machine. The hardware stroke limit function and the software stroke limit function are available.

Absolute position system

This function restores the absolute position of the designated axis. If the home position return is executed at the start of system, after that, it is unnecessary to carry out the home position return again when the power is turned ON.

Step function

This function temporarily stops the operation to confirm the positioning operation during debugging, etc.

The operation can be stopped at each "automatic deceleration" or "positioning data".

M-code output function

This function issues commands for sub works corresponding to the M-code No. 0 to 65535 that can be set for each positioning data. The commands are used for clamp or drill stop, tool change, etc.

External input signal setting function

This function allows you to set the input type, the input terminal, and the input filter for each external input signal (the upper/lower limit signal, the proximity dog signal, and the stop signal).

Phase compensation

In synchronous control with a synchronous encoder, the phase compensation function is used to make up the delay time caused by a communication delay in the synchronous encoder data, etc.

Home position return methods

Various types of home position return methods, the retry function and the shift function are available to establish a home position used as the machine reference point. Select any of these home position return methods that suits your machine type.

Stop operation functions

Forced stop, axis stop, and forced stop for servo amplifiers are available. Utilize these stop operation functions based on your application.

Unlimited length feed

Unlimited length feed can be performed by disabling the stroke limit function. This function can be used for a rotary table, a belt conveyor, etc.

Amplifier-less operation

This function executes the positioning control by the Simple Motion module without connecting to servo amplifiers. So, you can execute debugging of a user program and simulation of positioning operation on a personal computer.

Skip function

This function stops the positioning being executed when the skip signal is inputted, and carries out the next positioning. It can be used for measurement with a sensor.

Execution data backup function

This function stores the "setting data", currently being executed, into the flash ROM/internal memory without a battery. The command for this function can be executed on MELSOFT GX Works3 or a sequence program.

External I/O signal logic switching function

This function switches I/O signal logic according to devices connected to the Simple Motion module, etc.


CC-Link IE Field
MELSEC iQ-R
series

CC-Link IE Field Network
MELSEC iQ-R series Simple Motion module

RD77GF4/RD77GF8/RD77GF16

5

Simple Motion Modules




Slave station: 120 stations (Including the number of motion mode compatible servo amplifiers)

(Note): A switching hub is required for star topology.

CC-Link IE Field
MELSEC Q series

CC-Link IE Field Network
MELSEC-Q series Simple Motion module

QD77GF4/QD77GF8/QD77GF16



Slave station: 120 stations (16 motion mode compatible servo amplifiers + 104 I/O devices)

(Note): A switching hub is required for star topology.

Simple Motion Modules

■ Module specifications

Simple Motion module RD77GF4/RD77GF8/RD77GF16

Item	Specifications		
	RD77GF4	RD77GF8	RD77GF16
Maximum number of control axes (Virtual servo amplifier axis included)	4 axes	8 axes	16 axes
Servo amplifier connection system	CC-Link IE Field Network		
Maximum distance between stations [m(ft.)]	100(328.08)		
Peripheral I/F	Via CPU module (USB, Ethernet)		
Manual pulse generator operation function	Possible to connect 1 module (via link device)		
Synchronous encoder operation	4 modules	8 modules	16 modules
	A total of link devices, interfaces via CPU and interfaces via servo amplifier		
Number of I/O occupying points	32 points (I/O allocation: Intelligent function module, 32 points)		
Number of module occupied slots	1		
5VDC internal current consumption [A]	1.1		
Mass [kg]	0.23		
Exterior dimensions [mm(inch)]	106.0(4.17) (H) × 27.8(1.09) (W) × 110.0(4.33) (D)		

Applicable CPU

PLC CPU	R04CPU, R08CPU, R16CPU, R32CPU, R120CPU, R04ENCPU, R08ENCPU, R16ENCPU, R32ENCPU, R120ENCPU
---------	---

Simple Motion module QD77GF4/QD77GF8/QD77GF16

Item	Specifications		
	QD77GF4	QD77GF8	QD77GF16
Maximum number of control axes (Virtual servo amplifier axis included)	4 axes	8 axes	16 axes
Servo amplifier connection system	CC-Link IE Field Network		
Maximum distance between stations [m(ft.)]	100(328.08)		
Peripheral I/F	Via CPU module (USB, RS-232, Ethernet)		
Manual pulse generator operation function	Possible to connect 1 module		
External command signal	Number of input points	4 points	
	Input method	Positive common/Negative common shared (Photocoupler isolation)	
	Rated input voltage/current	24 VDC/Approx. 5 mA	
	Operating voltage range	21.6 to 26.4 VDC (24 VDC ±10%, ripple ratio 5% or less)	
	ON voltage/current	17.5 VDC or more/3.5 mA or more	
	OFF voltage/current	5 VDC or less/0.9 mA or less	
	Input resistance	Approx. 5.6 kΩ	
	Response time	1 ms or less (OFF→ON, ON→OFF)	
Forced stop input signal (EMI)	Recommended wire size	AWG24 (0.2 mm ²)	
	Number of input points	1 point	
	Input method	Positive common/Negative common shared (Photocoupler isolation)	
	Rated input voltage/current	24 VDC/Approx. 2.4 mA	
	Operating voltage range	20.4 to 26.4 VDC (24 VDC +10%/-15%, ripple ratio 5% or less)	
	ON voltage/current	17.5 VDC or more/2 mA or more	
	OFF voltage/current	1.8 VDC or less/0.18 mA or less	
	Input resistance	Approx. 10 kΩ	
Manual pulse generator/Incremental synchronous encoder signal	Response time	1 ms or less (OFF→ON, ON→OFF)	
	Recommended wire size	AWG24 (0.2 mm ²)	
	Signal input form	Phase A/Phase B (magnification by 4/magnification by 2/magnification by 1), PULSE/SIGN	
	Input frequency	1 Mpps (After magnification by 4, up to 4 Mpps) (Differential output type) 200 kpps (After magnification by 4, up to 800 kpps) (Voltage-output/Open-collector type)	
Number of occupied I/O points		32 points (I/O allocation: Intelligent function module, 32 points)	
Number of module occupied slots		1	
5 VDC internal current consumption [A]		0.8	
Mass [kg]		0.26	
Exterior dimensions [mm(inch)]		98.0(3.86) (H) × 27.4(1.08) (W) × 115(4.53) (D)	

Applicable CPU

Universal model QCPU (Upper five digit of Serial No. is "12012" or later)	Q00UJCPU, Q00UCPU, Q01UCPU, Q02UCPU, Q03UDCPU, Q04UDHCPU, Q06UDHCPU, Q10UDHCPU, Q13UDHCPU, Q20UDHCPU, Q26UDHCPU, Q03UDECPU, Q04UDEHCPU, Q06UDEHCPU, Q10UDEHCPU, Q13UDEHCPU, Q20UDEHCPU, Q26UDEHCPU, Q50UDEHCPU, Q100UDEHCPU
High-speed universal model QCPU	Q03UDVCPU, Q04UDVCPU, Q06UDVCPU, Q13UDVCPU, Q26UDVCPU

■ Performance specifications of CC-Link IE Field Network

Item		MELSEC IQ-R series			MELSEC-Q series			
		RD77GF4	RD77GF8	RD77GF16	QD77GF4	QD77GF8	QD77GF16	
Maximum link points per network		RX	16k points (16384 points, 2k bytes)			8k points (8192 points, 1k byte)		
		RY	16k points (16384 points, 2k bytes)			8k points (8192 points, 1k byte)		
		RWr	8k points (8192 points, 16k bytes)			1k points (1024 points, 2k bytes)		
		RWw	8k points (8192 points, 16k bytes)			1k points (1024 points, 2k bytes)		
Maximum link points per station	Master station	RX	16k points (16384 points, 2k bytes)			8k points (8192 points, 1k byte)		
		RY	16k points (16384 points, 2k bytes)			8k points (8192 points, 1k byte)		
		RWr	8k points (8192 points, 16k bytes)			1k points (1024 points, 2k bytes)		
		RWw	8k points (8192 points, 16k bytes)			1k points (1024 points, 2k bytes)		
	Local station	RX	2k points (2048 points, 256 bytes)			—		
		RY	2k points (2048 points, 256 bytes)			—		
		RWr	1k points (1024 points, 2k bytes)			—		
		RWw	1k points (1024 points, 2k bytes)			—		
	Intelligent device station	RX	2k points (2048 points, 256 bytes)			2k points (2048 points, 256 bytes)		
		RY	2k points (2048 points, 256 bytes)			2k points (2048 points, 256 bytes)		
		RWr	1k points (1024 points, 2048 bytes)			1k points (1024 points, 2048 bytes)		
		RWw	1k points (1024 points, 2048 bytes)			1k points (1024 points, 2048 bytes)		
	Remote device station	RX	128 points, 16 bytes			128 points, 16 bytes		
		RY	128 points, 16 bytes			128 points, 16 bytes		
		RWr	64 points, 128 bytes			64 points, 128 bytes		
		RWw	64 points, 128 bytes			64 points, 128 bytes		
Ethernet	Communication speed		1 Gbps					
	Connection cable		1000BASE-T Ethernet cable ^(Note-1) (Category 5e or higher), (Double shielded/STP) Straight cable					
	Maximum distance between stations [m(ft.)]		100(328.08) (conforms to ANSI/TIA/EIA-568-(Category 5e))					
	Topology		Line type, star type, line/star mixed type					
Overall cable distance	Line type [m(ft.)]		12000(39370.08) (When 1 master station and 120 slave stations are connected)					
	Star type		Depends on system configuration					
Maximum stations per network		121 stations (1 master station, 120 slave stations)			121 stations (1 master station, 120 slave stations) (4, 8, or 16 servo amplifiers + 104 I/O devices)			
Maximum number of networks		239						

(Note-1): Use the cables recommended by CC-Link Partner Association for CC-Link IE Field Network.
CC-Link IE Controller Network cables are not compatible with CC-Link IE Field Network.

Ethernet Cable Specifications

Item		Description
Ethernet cable		Category 5e or higher, (double shielded/STP) straight cable
	Standard	The cable must meet the following standards: • IEEE802.3 (1000BASE-T) • ANSI/TIA/EIA-568-B (Category 5e)
	Connector	RJ-45 connector with shield

■ Products on the Market

Ethernet Cable

Item		Model		Note
Ethernet cable	For indoor	SC-E5EW-S_M	_ : cable length (100 m max., unit of 1 m)	Double shielded cable (Category 5e)
	For moving part, indoor	SC-E5EW-S_M-MV	_ : cable length (45 m max., unit of 1 m)	
	For indoor/outdoor	SC-E5EW-S_M-L	_ : cable length (100 m max., unit of 1 m)	

Manual pulse generator

Mitsubishi Electric has confirmed the operation of the following manual pulse generators. Contact each manufacturer for details.

Product	Model	Description	Manufacturer
Manual pulse generator	RE45BA2R5C	Number of pulses per revolution: 25 pulse/rev (100 pulse/rev after magnification by 4), Permitted speed: 200 r/min (Normal rotation)	Tokyo Sokuteikizai Co., Ltd.
	UFO-M2-0025-2Z1-B00E	Number of pulses per revolution: 25 pulse/rev (100 pulse/rev after magnification by 4), Permitted speed: 200 r/min (Normal rotation)	Nemicon Corporation

■ Control specifications

Item		Specifications						
		MELSEC iQ-R series			MELSEC-Q series			
		RD77GF4	RD77GF8	RD77GF16	QD77GF4	QD77GF8	QD77GF16	
Maximum number of control axes (Virtual servo amplifier axis included)		4 axes	8 axes	16 axes	4 axes	8 axes	16 axes	
Operation cycle (Operation cycle settings)		0.5 ms, 1.0 ms, 2.0 ms, 4.0 ms			1.0 ms, 2.0 ms, 4.0 ms			
Interpolation function		Linear interpolation (Up to 4 axes), Circular interpolation (2 axes), Helical interpolation (3 axes) ^(Note-1)						
Control modes		PTP (Point To Point) control, Trajectory control (Linear, arc, and helical), Speed control, Speed-position switching control, Position-speed switching control, Speed-torque control						
Acceleration/deceleration process		Trapezoidal acceleration/deceleration, S-curve acceleration/deceleration						
Compensation function		Backlash compensation, Electronic gear, Near pass function						
Synchronous control		Synchronous encoder input, Cam, Phase compensation, Cam auto-generation						
Control unit		mm, inch, degree, pulse						
Number of positioning data		600 data (positioning data No. 1 to 600)/axis						
Backup		Parameters, positioning data, and block start data can be saved on flash ROM (battery-less backup)						
Home position return	Home position return method	Driver home position return method						
	Fast home position return control	Provided						
Positioning control	Linear control	Linear interpolation control (Up to 4 axes) ^(Note-2) (Vector speed, Reference axis speed)						
	Fixed-pitch feed control	Fixed-pitch feed control (Up to 4 axes)						
	2-axis circular interpolation	Auxiliary point-specified circular interpolation, Central point-specified circular interpolation						
	Speed control	Speed control (Up to 4 axes)						
	Speed-position switching control	INC mode, ABS mode						
	Position-speed switching control	INC mode						
	Current value change	Positioning data, Start No. for a current value changing						
	NOP instruction	Provided						
	JUMP instruction	Unconditional JUMP, Conditional JUMP						
	LOOP, LEND	Provided						
Manual control	High-level positioning control	Block start, Condition start, Wait start, Simultaneous start, Repeated start						
	JOG operation	Provided						
	Inching operation	Provided						
	Manual pulse generator	Possible to connect 1 module (Incremental), Unit magnification (1 to 10000 times)						
Via link device			Via internal interface					
Expansion control	Speed-torque control	Speed control without positioning loops, Torque control						
Absolute position system		Made compatible by setting a battery to a servo amplifier						
Synchronous encoder interface		4CH	8CH	16CH	4CH			
	Internal interface	—			1CH (Incremental)			
	Via CPU	Provided (Incremental)						
	Via link device	Provided (Incremental)						
	Via servo amplifier	4CH	8CH	16CH	4CH			
Functions that limit control	Speed limit function	Speed limit value, JOG speed limit value						
	Torque limit function	Torque limit value same setting, torque limit value individual setting						
	Forced stop	Valid/Invalid setting						
	Software stroke limit function	Movable range check with current feed value, movable range check with machine feed value						
Functions that change control details	Hardware stroke limit function	Provided						
	Speed change function	Provided						
	Override function	0 to 300 [%]						
	Acceleration/deceleration time change function	Provided						
Other functions	Torque change function	Provided						
	Target position change function	Target position address and speed are changeable						
	M-code output function	WITH mode/AFTER mode						
	Step function	Deceleration unit step, Data No. unit step						
	Skip function	Via PLC CPU, Via external command signal						
	Teaching function	Provided						
Parameter initialization function		Provided						
External input signal setting function	Internal interface	—			Provided			
	Via link device	Provided			—			
	Via servo amplifier	Provided			Provided			
Event history function		Provided						
Amplifier-less operation function (Virtual servo amplifier function)		Provided						
Mark detection function			Continuous Detection mode, Specified Number of Detections mode, Ring Buffer mode					
	Mark detection signal	Up to 16 points ^(Note-4)			Up to 4 points			
	Mark detection setting	16 settings						
Optional data monitor function		4 points/axis						
Digital oscilloscope function ^(Note-3)	Bit data	16CH						
	Word data	16CH						

(Note-1): Available with RD77MS.

(Note-2): 4-axis linear interpolation control is enabled only at the reference axis speed.

(Note-3): 8CH word data and 8CH bit data are displayed in real time.

(Note-4): The synchronous input timing acquisition function of a remote input module is used.

■ Synchronous control specifications

Item		Number of settable axes					
		MELSEC iQ-R series			MELSEC-Q series		
		RD77GF4	RD77GF8	RD77GF16	QD77GF4	QD77GF8	QD77GF16
Input axis module	Servo input axis	4 axes/module	8 axes/module	16 axes/module	4 axes/module	8 axes/module	16 axes/module
	Synchronous encoder axis	4 axes/module	8 axes/module	16 axes/module	4 axes/module		
Main shaft module	Composite main shaft gear	1 module/output axis					
	Main shaft main input axis	1 module/output axis					
	Main shaft sub input axis	1 module/output axis					
	Main shaft gear	1 module/output axis					
	Main shaft clutch	1 module/output axis					
Auxiliary shaft module	Auxiliary shaft	1 module/output axis					
	Auxiliary shaft gear	1 module/output axis					
	Auxiliary shaft clutch	1 module/output axis					
	Auxiliary shaft composite gear	1 module/output axis					
Speed change gear module	Speed change gear	2 modules/output axis					
Output axis module	Output axis (Cam axis)	4 axes/module	8 axes/module	16 axes/module	4 axes/module	8 axes/module	16 axes/module

■ Cam control

Item			Specifications										
			MELSEC iQ-R series					MELSEC-Q series					
			RD77GF4	RD77GF8	RD77GF16	QD77GF4	QD77GF8	QD77GF16					
Memory capacity	Cam storage area		Up to 3 MB					256k bytes					
	Cam working area		Up to 16 MB					1024k bytes					
Number of registration			Up to 1024 ^(Note-1)					Up to 256 ^(Note-1)					
Comment			Up to 32 characters for each cam data										
Cam data	Stroke ratio data type	Maximum number of cam registration	RD77GF										
			Cam resolution	256	512	1024	2048	4096	8192	16384	32768		
			Number of cam registration	1024	1024	1024	1024	1024	512	256	128		
			QD77GF										
			Cam resolution	256	512	1024	2048	4096	8192	16384	32768		
			Number of cam registration	256	128	64	32	16	8	4	2		
	Stroke ratio		-214.7483648 to 214.7483647 [%]										
	Coordinate data type	Maximum number of cam registration	RD77GF										
			Number of coordinates	128	256	512	1024	2048	4096	8192	16384	32768	65535
			Number of cam registration	1024	1024	1024	1024	1024	512	256	128	64	32
			QD77GF										
			Number of coordinates	128	256	512	1024	2048	4096	8192	32768		
Number of cam registration			256	128	64	32	16	8	4	2			
Coordinate data		Input value: 0 to 2147483647, Output value: -2147483648 to 2147483647											
Cam auto-generation	Cam for rotary cutter		Available					Available					
	Easy stroke ratio cam		Available					—					
	Advanced stroke ratio cam		Available					—					

(Note-1): The number of registration varies depending on memory capacity, cam resolution, and the number of coordinates.

■ Compatibility with servo amplifier

Item	MELSEC iQ-R series			MELSEC-Q series		
	RD77GF4	RD77GF8	RD77GF16	QD77GF4	QD77GF8	QD77GF16
MR-J4-GF(-RJ)	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible ^(Note-1)

(Note-1): Only QD77GF16 with the first 5 digits of product information on and after 17102 is compatible with MR-J4-GF(-RJ).

■ Component


Part		Model	Description	Standards
Simple Motion modules	MELSEC iQ-R series	RD77GF4 NEW	Up to 4 axes	CE, UL, KC
		RD77GF8 NEW	Up to 8 axes	CE, UL, KC
		RD77GF16 NEW	Up to 16 axes	CE, UL, KC
	MELSEC-Q series	QD77GF4 NEW	Up to 4 axes	CE, UL, KC
		QD77GF8 NEW	Up to 8 axes	CE, UL, KC
		QD77GF16	Up to 16 axes	CE, UL, KC
Internal I/F connector set (Note-1)		LD77MHIOCON	Incremental synchronous encoder/Mark detection signal interface connector set	—

(Note-1): Use this connector set for QD77GF.

GX Works3

One Software, Many Possibilities

GX Works3 consists of various different components that help to simplify project creation and maintenance tasks.



All-in-one Tool for Quick and Easy Startup

This all integrated software offers a wide range of features - creation of a sequence program such as a function block (FB), parameter settings for Simple Motion modules, servo adjustment and debugging.

■ Easy-to-use features

- Various intuitive features, such as graphics-based system configuration and an extensive module library (module label/FB), are provided as standard.
- MELSOFT GX Works3 conforms to an international standard, IEC 61131-3, supporting structured programming.

■ Powerful security features protecting intellectual property


- Security key authentication function protects your project data.

■ Global realization by multi-language support

- Multiple languages (Japanese, English, and Chinese) are supported at various levels (Menu display, etc.).

■ Easy settings and diagnostic functions

- Network is set up easily only with parameter settings.
- Troubleshooting is performed even with little experience.



All-in-One Engineering Software

This all-in-one software covers all aspects of the product development cycle - from system design, programming, to debugging and maintenance - maximizing efficiency while minimizing your effort.

Easy system design

No need of manuals in system and parameter settings

- MELSOFT GX Works3 includes everything needed from system configuration to servo parameter settings.
- Parameters for CC-Link IE Field Network are easy to be set.

[Servo parameter]



[CC-Link IE configuration]



System Design


Programming

Easy motion control

[Positioning data]



[Synchronous control parameter]



Increased usability in synchronous/positioning control settings


- An array of sub functions helps you create positioning data.
- Synchronous control is performed easily just by parameter settings.
- Creation of a rough cam waveform on a graph via drag & drop, or direct numerical value input to the graph enables easy creation of cam data.

Easy programming

Simple point-and-click programming

- A sequence program is created effortlessly via drag & drop of module labels/FBs.

[Sequence program]




Debug

Maintenance

Easy startup

[One-touch tuning]



[Network diagnostics]



Increased efficiency in debugging and maintenance

- Servo adjustment is automatically completed using the One-touch tuning function.
- Debugging of a program without an actual machine is possible by simulation. **Compatible in the future**
- The network errors are displayed by Network diagnostics.

■Operating environment

MELSOFT GX Works3

Item	Description
OS	Microsoft® Windows® 8.1 (64bit/32bit), Microsoft® Windows® 8.1 (Enterprise, Pro) (64bit/32bit) Microsoft® Windows® 8 (64bit/32bit), Microsoft® Windows® 8 (Enterprise, Pro) (64bit/32bit) Microsoft® Windows® 7 (Enterprise, Ultimate, Professional, Home Premium, Starter) (64bit/32bit) Microsoft® Windows Vista® (Enterprise, Ultimate, Business, Home Premium, Home Basic) (32bit) Microsoft® Windows® XP Service Pack3 (Professional, Home Edition) (32bit)
CPU	Intel® Core™ 2 Duo Processor 2 GHz or more recommended
Required memory	For 32-bit edition: 1GB or more recommended For 64-bit edition: 2GB or more recommended
Available hard disk capacity	When installing MELSOFT GX Works3: HDD available capacity is 5GB or more.
Optical drive	DVD-ROM supported disk drive
Monitor	Resolution 1024 x 768 dots or higher

MELSOFT GX Works2

Item	Description
OS	Microsoft® Windows® 8.1 (64bit/32bit), Microsoft® Windows® 8.1 (Enterprise, Pro) (64bit/32bit) Microsoft® Windows® 8 (64bit/32bit), Microsoft® Windows® 8 (Enterprise, Pro) (64bit/32bit) Microsoft® Windows® 7 (Enterprise, Ultimate, Professional, Home Premium, Starter) (64bit/32bit) Microsoft® Windows Vista® (Enterprise, Ultimate, Business, Home Premium, Home Basic) (32bit) Microsoft® Windows® XP Service Pack2 or later (Professional, Home Edition) (32bit)
CPU	Recommended Intel® Core™ 2 Duo Processor 2GHz or more
Required memory	Recommended 1GB or more
Available hard disk capacity	When installing GX Works2: HDD available capacity is 2.5GB or more. When operating GX Works2: Virtual memory available capacity is 512MB or more.
Optical drive	CD-ROM supported disk drive
Monitor	Resolution 1024 x 768 dots or higher

■Engineering software list

Product	Model	Description	
MELSOFT GX Works3	SW1DND-GXW3-E	<ul style="list-style-type: none"> Programmable Controller Engineering Software [MELSOFT GX Works3, GX Works2, GX Developer] MITSUBISHI ELECTRIC FA Library 	DVD-ROM
MELSOFT GX Works2	SW1DNC-GXW2-E	<ul style="list-style-type: none"> Programmable Controller Engineering Software [MELSOFT GX Works2, GX Developer] 	CD-ROM
MELSOFT iQ Works	SW2DND-IQWK-E	<ul style="list-style-type: none"> FA Engineering Software ^(Note-1) System Management Software [MELSOFT Navigator] Programmable Controller Engineering Software [MELSOFT GX Works3, GX Works2, GX Developer] Motion Controller Engineering Software [MELSOFT MT Works2] Screen Design Software [MELSOFT GT Works3] Robot Total Engineering Support Software [MELSOFT RT ToolBox2 mini] Inverter Setup Software [MELSOFT FR Configurator2] 	DVD-ROM

(Note-1): Refer to each product manual for software needed for the model.

MEMO


CC-Link Partner Association (CLPA) - Actively promoting worldwide adoption of CC-Link networks

Proactively supporting CC-Link, from promotion to specification development

The CC-Link Partner Association (CLPA) was established to promote the worldwide adoption of the CC-Link open-field network. By conducting promotional activities such as organizing trade shows and seminars, conducting conformance tests, and providing catalogs, brochures and website information, CLPA activities are successfully increasing the number of CC-Link partner manufacturers and CC-Link-compatible products. As such, CLPA is playing a major role in the globalization of CC-Link.



Seminar



Trade show



Conformance testing lab

Visit the CLPA website for the latest CC-Link information.


URL:<http://www.cc-link.org>

6F Ozone Front Bldg. 3-15-58 Ozone
Kita-ku, Nagoya 462-0825, JAPAN
TEL: +81-52-919-1588 FAX: +81-52-916-8655
E-mail: info@cc-link.org




Global influence of CC-Link continues to spread

CC-Link is supported globally by CLPA. With offices throughout the world, support for partner companies can be found locally. Each regional CLPA office undertakes various support and promotional activities to further the influence of the network in that part of the world. For companies looking to increase their presence in Asia, CLPA is well placed to assist these efforts through offices in all major Asian regions.



Global FA Centers



China

Shanghai FA Center
Mitsubishi Electric Automation
(China) Ltd. Shanghai FA Center
 Mitsubishi Electric Automation Center,
 No.1386 Hongqiao Road, Shanghai, China
 Tel: 86-21-2322-3030 Fax: 86-21-2322-3000 (9611#)

Beijing FA Center
Mitsubishi Electric Automation
(China) Ltd. Beijing FA Center
 Unit 901, Office Tower 1, Henderson Centre,
 18 Jianguomennei Avenue, Dongcheng District,
 Beijing, China
 Tel: 86-10-6518-8830 Fax: 86-10-6518-2938

Tianjin FA Center
Mitsubishi Electric Automation
(China) Ltd. Tianjin FA Center
 Room 2003 City Tower, No.35, Youyi Road,
 Hexi District, Tianjin, China
 Tel: 86-22-2813-1015 Fax: 86-22-2813-1017

Guangzhou FA Center
Mitsubishi Electric Automation
(China) Ltd. Guangzhou FA Center
 Room 1609, North Tower, The Hub Center,
 No.1068, Xingang East Road, Haizhu District,
 Guangzhou, China
 Tel: 86-20-8923-6730 Fax: 86-20-8923-6715

Taiwan

Taipei FA Center
SETSUYO ENTERPRISE CO., LTD.
 3F, No.105, Wugong 3rd Road, Wugu District,
 New Taipei City 24889, Taiwan
 Tel: 886-2-2299-9917 Fax: 886-2-2299-9963

Korea

Korea FA Center
Mitsubishi Electric Automation
Korea Co., Ltd.
 7F-9F, Gangseo Hangang Xi-tower A, 401,
 Yangcheon-ro, Gangseo-Gu, Seoul 07528, Korea
 Tel: 82-2-3660-9605 Fax: 82-2-3664-0475

Thailand

Thailand FA Center
Mitsubishi Electric Factory Automation
(Thailand) Co., Ltd.
 12th Floor, SV.City Building, Office Tower 1,
 No. 896/19 and 20 Rama 3 Road,
 Kwaeng Bangpongpan, Khet Yannawa, Bangkok
 10120, Thailand
 Tel: 66-2682-6522 to 6531 Fax: 66-2682-6020

ASEAN

ASEAN FA Center
Mitsubishi Electric Asia Pte. Ltd.
 307 Alexandra Road, Mitsubishi Electric Building,
 Singapore 159943
 Tel: 65-6470-2475 Fax: 65-6476-7439

Indonesia

Indonesia FA Center
PT. Mitsubishi Electric Indonesia
Cikarang Office
 Jl. Kenari Raya Blok G2-07A Delta Silicon 5,
 Lippo Cikarang - Bekasi 17550, Indonesia
 Tel: 62-21-2961-7797 Fax: 62-21-2961-7794

Vietnam

Hanoi FA Center
Mitsubishi Electric Vietnam Company
Limited Hanoi Branch Office
 6th Floor, Detech Tower, 8 Ton That Thuyet Street,
 My Dinh2 Ward, Nam Tu Liem District, Hanoi,
 Vietnam
 Tel: 84-4-3937-8075 Fax: 84-4-3937-8076

Ho Chi Minh FA Center
Mitsubishi Electric Vietnam Company Limited
 Unit 01-04, 10th Floor, Vincom Center, 72 Le
 Thanh Ton Street, District 1, Ho Chi Minh City,
 Vietnam
 Tel: 84-8-3910-5945 Fax: 84-8-3910-5947

India

India Pune FA Center
Mitsubishi Electric India Pvt. Ltd.
Pune Branch
 Emerald House, EL-3, J Block, M.I.D.C., Bhosari,
 Pune - 411026, Maharashtra, India
 Tel: 91-20-2710-2000 Fax: 91-20-2710-2100

India Gurgaon FA Center
Mitsubishi Electric India Pvt. Ltd.
Gurgaon Head Office
 2nd Floor, Tower A & B, Cyber Greens, DLF
 Cyber City, DLF Phase - III, Gurgaon - 122002,
 Haryana, India
 Tel: 91-124-463-0300 Fax: 91-124-463-0399

India Bangalore FA Center
Mitsubishi Electric India Pvt. Ltd.
Bangalore Branch
 Prestige Emerald, 6th Floor, Municipal No.2,
 Madras Bank Road, Bangalore - 560001,
 Karnataka, India
 Tel: 91-80-4020-1600 Fax: 91-80-4020-1699

India Chennai FA Center
Mitsubishi Electric India Pvt. Ltd.
Chennai Branch
 Citilights Corporate Centre No. 1,
 Vivekananda Road, Srinivasa Nagar, Chetpet,
 Chennai - 600031, Tamil Nadu, India
 Tel: 91-4445548772 Fax: 91-4445548773

India Ahmedabad FA Center
Mitsubishi Electric India Pvt. Ltd.
Ahmedabad Branch
 B/4, 3rd Floor, SAFAL Profitaire, Corporate Road,
 Prahaladnagar, Satellite, Ahmedabad - 380015,
 Gujarat, India
 Tel: 91-7965120063 Fax: -

America

North America FA Center
Mitsubishi Electric Automation, Inc.
 500 Corporate Woods Parkway, Vernon Hills,
 IL 60061, U.S.A.
 Tel: 1-847-478-2110 Fax: 1-847-478-2253

Mexico

Mexico FA Center
Mitsubishi Electric Automation, Inc.
Mexico Branch
 Mariano Escobedo #69, Col.Zona Industrial,
 Tlalnepanitla Edo. Mexico, C.P.54030
 Tel: 52-55-3067-7511 Fax: -

Brazil

Brazil FA Center
Mitsubishi Electric do Brasil
Comercio e Servicos Ltda.
 Avenida Adelino Cardana, 293, 21 andar,
 Bethaville, Barueri SP, Brazil
 Tel: 55-11-4689-3000 Fax: 55-11-4689-3016

Europe

Europe FA Center
Mitsubishi Electric Europe B.V.
Polish Branch
 ul. Krakowska 50, 32-083 Balice, Poland
 Tel: 48-12-347-65-00 Fax: 48-12-630-47-01

Germany FA Center
Mitsubishi Electric Europe B.V.
German Branch
 Gothaer Strasse 8, D-40880 Ratingen, Germany
 Tel: 49-2102-486-0 Fax: 49-2102-486-1120

UK FA Center
Mitsubishi Electric Europe B.V.
UK Branch
 Travellers Lane, Hatfield, Hertfordshire, AL10
 8XB, U.K.
 Tel: 44-1707-27-8780 Fax: 44-1707-27-8695

Czech Republic FA Center
Mitsubishi Electric Europe B.V.
Czech Branch
 Avenir Business Park, Radlicka 751/113e,
 158 00 Praha5, Czech Republic
 Tel: 420-251-551-470 Fax: 420-251-551-471

Russia FA Center
Mitsubishi Electric (Russia) LLC
St. Petersburg Branch
 Piskarevsky pr. 2, bld 2, lit "Sch", BC "Benua",
 office 720; 195027, St. Petersburg, Russia
 Tel: 7-812-633-3497 Fax: 7-812-633-3499

Turkey FA Center
Mitsubishi Electric Turkey A.S.
Umraniye Branch
 Serifali Mahallesi Nutuk Sokak No:5,
 TR-34775 Umraniye / Istanbul, Turkey
 Tel: 90-216-526-3990 Fax: 90-216-526-3995

General-purpose AC servo

1. Warranty period and coverage

We will repair any failure or defect hereinafter referred to as "failure" in our FA equipment hereinafter referred to as the "Product" arisen during warranty period at no charge due to causes for which we are responsible through the distributor from which you purchased the Product or our service provider. However, we will charge the actual cost of dispatching our engineer for an on-site repair work on request by customer in Japan or overseas countries. We are not responsible for any on-site readjustment and/or trial run that may be required after a defective unit is repaired or replaced.

[Term]

The term of warranty for Product is twelve (12) months after your purchase or delivery of the Product to a place designated by you or eighteen (18) months from the date of manufacture whichever comes first ("Warranty Period"). Warranty period for repaired Product cannot exceed beyond the original warranty period before any repair work.

[Limitations]

- (1) You are requested to conduct an initial failure diagnosis by yourself, as a general rule.
It can also be carried out by us or our service company upon your request and the actual cost will be charged.
However, it will not be charged if we are responsible for the cause of the failure.
- (2) This limited warranty applies only when the condition, method, environment, etc. of use are in compliance with the terms and conditions and instructions that are set forth in the instruction manual and user manual for the Product and the caution label affixed to the Product.
- (3) Even during the term of warranty, the repair cost will be charged on you in the following cases;
 - (i) a failure caused by your improper storing or handling, carelessness or negligence, etc., and a failure caused by your hardware or software problem
 - (ii) a failure caused by any alteration, etc. to the Product made on your side without our approval
 - (iii) a failure which may be regarded as avoidable, if your equipment in which the Product is incorporated is equipped with a safety device required by applicable laws and has any function or structure considered to be indispensable according to a common sense in the industry
 - (iv) a failure which may be regarded as avoidable if consumable parts designated in the instruction manual, etc. are duly maintained and replaced
 - (v) any replacement of consumable parts (battery, fan, smoothing capacitor, etc.)
 - (vi) a failure caused by external factors such as inevitable accidents, including without limitation fire and abnormal fluctuation of voltage, and acts of God, including without limitation earthquake, lightning and natural disasters
 - (vii) a failure generated by an unforeseeable cause with a scientific technology that was not available at the time of the shipment of the Product from our company
 - (viii) any other failures which we are not responsible for or which you acknowledge we are not responsible for

2. Term of warranty after the stop of production

- (1) We may accept the repair at charge for another seven (7) years after the production of the product is discontinued. The announcement of the stop of production for each model can be seen in our Sales and Service, etc.
- (2) Please note that the Product (including its spare parts) cannot be ordered after its stop of production.

3. Service in overseas countries

Our regional FA Center in overseas countries will accept the repair work of the Product. However, the terms and conditions of the repair work may differ depending on each FA Center. Please ask your local FA Center for details.

4. Exclusion of loss in opportunity and secondary loss from warranty liability

Regardless of the gratis warranty term, Mitsubishi shall not be liable for compensation to:

- (1) Damages caused by any cause found not to be the responsibility of Mitsubishi.
- (2) Loss in opportunity, lost profits incurred to the user by Failures of Mitsubishi products.
- (3) Special damages and secondary damages whether foreseeable or not, compensation for accidents, and compensation for damages to products other than Mitsubishi products.
- (4) Replacement by the user, maintenance of on-site equipment, start-up test run and other tasks.

5. Change of Product specifications

Specifications listed in our catalogs, manuals or technical documents may be changed without notice.

6. Application and use of the Product

- (1) For the use of our General-Purpose AC Servo, its applications should be those that may not result in a serious damage even if any failure or malfunction occurs in General-Purpose AC Servo, and a backup or fail-safe function should operate on an external system to General-Purpose AC Servo when any failure or malfunction occurs.
- (2) Our General-Purpose AC Servo is designed and manufactured as a general purpose product for use at general industries. Therefore, applications substantially influential on the public interest for such as atomic power plants and other power plants of electric power companies, and also which require a special quality assurance system, including applications for railway companies and government or public offices are not recommended, and we assume no responsibility for any failure caused by these applications when used.
In addition, applications which may be substantially influential to human lives or properties for such as airlines, medical treatments, railway service, incineration and fuel systems, man-operated material handling equipment, entertainment machines, safety machines, etc. are not recommended, and we assume no responsibility for any failure caused by these applications when used.
We will review the acceptability of the abovementioned applications, if you agree not to require a specific quality for a specific application. Please contact us for consultation.

Servo system controller

1. Warranty period and coverage

We will repair any failure or defect (hereinafter referred to as "failure") in our FA equipment (hereinafter referred to as the "Product") arisen during warranty period at no charge due to causes for which we are responsible through the distributor from which you purchased the Product or our service provider. However, we will charge the actual cost of dispatching our engineer for an on-site repair work on request by customer in Japan or overseas countries. We are not responsible for any on-site readjustment and/or trial run that may be required after a defective unit is repaired or replaced.

[Term]

The term of warranty for Product is thirty six (36) months after your purchase or delivery of the Product to a place designated by you or forty two (42) months from the date of manufacture whichever comes first ("Warranty Period"). Warranty period for repaired Product cannot exceed beyond the original warranty period before any repair work.

[Limitations]

- (1) You are requested to conduct an initial failure diagnosis by yourself, as a general rule.
It can also be carried out by us or our service company upon your request and the actual cost will be charged.
However, it will not be charged if we are responsible for the cause of the failure.
- (2) This limited warranty applies only when the condition, method, environment, etc. of use are in compliance with the terms and conditions and instructions that are set forth in the instruction manual and user manual for the Product and the caution label affixed to the Product.
- (3) Even during the term of warranty, the repair cost will be charged on you in the following cases;
 - (i) a failure caused by your improper storing or handling, carelessness or negligence, etc., and a failure caused by your hardware or software problem
 - (ii) a failure caused by any alteration, etc. to the Product made on your side without our approval
 - (iii) a failure which may be regarded as avoidable, if your equipment in which the Product is incorporated is equipped with a safety device required by applicable laws and has any function or structure considered to be indispensable according to a common sense in the industry
 - (iv) a failure which may be regarded as avoidable if consumable parts designated in the instruction manual, etc. are duly maintained and replaced
 - (v) any replacement of consumable parts (battery, fan, etc.)
 - (vi) a failure caused by external factors such as inevitable accidents, including without limitation fire and abnormal fluctuation of voltage, and acts of God, including without limitation earthquake, lightning and natural disasters
 - (vii) a failure generated by an unforeseeable cause with a scientific technology that was not available at the time of the shipment of the Product from our company
 - (viii) any other failures which we are not responsible for or which you acknowledge we are not responsible for

2. Term of warranty after the stop of production

- (1) We may accept the repair at charge for another seven (7) years after the production of the product is discontinued. The announcement of the stop of production for each model can be seen in our Sales and Service, etc.
- (2) Please note that the Product (including its spare parts) cannot be ordered after its stop of production.

3. Service in overseas countries

Our regional FA Center in overseas countries will accept the repair work of the Product. However, the terms and conditions of the repair work may differ depending on each FA Center. Please ask your local FA Center for details.

4. Exclusion of loss in opportunity and secondary loss from warranty liability

Regardless of the gratis warranty term, Mitsubishi shall not be liable for compensation to:

- (1) Damages caused by any cause found not to be the responsibility of Mitsubishi.
- (2) Loss in opportunity, lost profits incurred to the user by Failures of Mitsubishi products.
- (3) Special damages and secondary damages whether foreseeable or not, compensation for accidents, and compensation for damages to products other than Mitsubishi products.
- (4) Replacement by the user, maintenance of on-site equipment, start-up test run and other tasks.

5. Change of Product specifications

Specifications listed in our catalogs, manuals or technical documents may be changed without notice.

6. Application and use of the Product

- (1) For the use of our Servo System Controller, its applications should be those that may not result in a serious damage even if any failure or malfunction occurs in Servo System Controller, and a backup or fail-safe function should operate on an external system to Servo System Controller when any failure or malfunction occurs.
- (2) Our Servo System Controller is designed and manufactured as a general purpose product for use at general industries. Therefore, applications substantially influential on the public interest for such as atomic power plants and other power plants of electric power companies, and also which require a special quality assurance system, including applications for railway companies and government or public offices are not recommended, and we assume no responsibility for any failure caused by these applications when used.
In addition, applications which may be substantially influential to human lives or properties for such as airlines, medical treatments, railway service, incineration and fuel systems, man-operated material handling equipment, entertainment machines, safety machines, etc. are not recommended, and we assume no responsibility for any failure caused by these applications when used.
We will review the acceptability of the abovementioned applications, if you agree not to require a specific quality for a specific application. Please contact us for consultation.

Microsoft, Windows , Internet Explorer, and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
Celeron and Pentium are registered trademarks of Intel Corporation in the U.S. and/or other countries.
Ethernet is a trademark of Xerox Corporation.
Cognex is registered trademarks of Cognex Corporation.
All other company names and product names used in this document are trademarks or registered trademarks of their respective companies.

Precautions before use


This publication explains the typical features and functions of the products herein and does not provide restrictions or other information related to usage and module combinations. Before using the products, always read the product user manuals. Mitsubishi Electric will not be held liable for damage caused by factors found not to be the cause of Mitsubishi Electric; opportunity loss or lost profits caused by faults in Mitsubishi Electric products; damage, secondary damage, or accident compensation, whether foreseeable or not, caused by special factors; damage to products other than Mitsubishi Electric products; or any other duties.



For safe use

- To use the products given in this publication properly, always read the relevant manuals before beginning operation.
- The products have been manufactured as general-purpose parts for general industries, and are not designed or manufactured to be incorporated in a device or system used in purposes related to human life.
- Before using the products for special purposes such as nuclear power, electric power, aerospace, medicine or passenger-carrying vehicles, consult with Mitsubishi Electric.
- The products have been manufactured under strict quality control. However, when installing the products where major accidents or losses could occur if the products fail, install appropriate backup or fail-safe functions in the system.

YOUR SOLUTION PARTNER



Mitsubishi Electric offers a wide range of automation equipment from PLCs and HMIs to CNC and EDM machines.

A NAME TO TRUST

Since its beginnings in 1870, some 45 companies use the Mitsubishi name, covering a spectrum of finance, commerce and industry.

The Mitsubishi brand name is recognized around the world as a symbol of premium quality.

Mitsubishi Electric Corporation is active in space development, transportation, semi-conductors, energy systems, communications and information processing, audio visual equipment and home electronics, building and energy management and automation systems, and has 237 factories and laboratories worldwide in over 121 countries.

This is why you can rely on Mitsubishi Electric automation solution - because we know first hand about the need for reliable, efficient, easy-to-use automation and control in our own factories.

As one of the world's leading companies with a global turnover of over 4 trillion Yen (over \$40 billion), employing over 100,000 people, Mitsubishi Electric has the resource and the commitment to deliver the ultimate in service and support as well as the best products.



Low voltage: MCCB, MCB, ACB



Medium voltage: VCB, VCC



Power monitoring, energy management



Compact and Modular Controllers



Inverters, Servos and Motors



Visualization: HMIs, Software, MES connectivity



Numerical Control (NC)



Robots: SCARA, Articulated arm



Processing machines: EDM, Lasers, IDS



Air-conditioning, Photovoltaic, EDS

Ethernet-based Open Network CC-Link IE Compatible Servo System

Country/Region	Sales office	Tel/Fax
USA	Mitsubishi Electric Automation, Inc. 500 Corporate Woods Parkway, Vernon Hills, IL 60061, U.S.A.	Tel : +1-847-478-2100 Fax : +1-847-478-2253
Mexico	Mitsubishi Electric Automation, Inc. Mexico Branch Mariano Escobedo #69, Col.Zona Industrial, Tlalnepantla Edo. Mexico, C.P.54030	Tel : +52-55-3067-7500 Fax : —
Brazil	Mitsubishi Electric do Brasil Comercio e Servicos Ltda. Avenida Adelino Cardana, 293, 21 andar, Bethaville, Barueri SP, Brazil	Tel : +55-11-4689-3000 Fax : +55-11-4689-3016
Germany	Mitsubishi Electric Europe B.V. German Branch Mitsubishi-Electric-Platz 1, 40882 Ratingen, Germany	Tel : +49-2102-486-0 Fax : +49-2102-486-1120
UK	Mitsubishi Electric Europe B.V. UK Branch Travellers Lane, UK-Hatfield, Hertfordshire, AL10 8XB, U.K.	Tel : +44-1707-28-8780 Fax : +44-1707-27-8695
Italy	Mitsubishi Electric Europe B.V. Italian Branch Centro Direzionale Colleoni - Palazzo Sirio, Viale Colleoni 7, 20864 Agrate Brianza (Milano), Italy	Tel : +39-039-60531 Fax : +39-039-6053-312
Spain	Mitsubishi Electric Europe B.V. Spanish Branch Carretera de Rubi, 76-80-Apdo. 420, 08190 Sant Cugat del Valles (Barcelona), Spain	Tel : +34-935-65-3131 Fax : +34-935-89-1579
France	Mitsubishi Electric Europe B.V. French Branch 25, Boulevard des Bouvets, 92741 Nanterre Cedex, France	Tel : +33-1-55-68-55-68 Fax : +33-1-55-68-57-57
Czech Republic	Mitsubishi Electric Europe B.V. Czech Branch Avenir Business Park, Radlicka 751/113e, 158 00 Praha 5, Czech Republic	Tel : +420-251-551-470 Fax : +420-251-551-471
Poland	Mitsubishi Electric Europe B.V. Polish Branch ul. Krakowska 50, 32-083 Balice, Poland	Tel : +48-12-347-65-00 Fax : +48-12-630-47-01
Russia	Mitsubishi Electric (Russia) LLC St. Petersburg Branch Piskarevsky pr. 2, bld 2, lit "Sch", BC "Benua", office 720; 195027 St. Petersburg, Russia	Tel : +7-812-633-3497 Fax : +7-812-633-3499
Sweden	Mitsubishi Electric Europe B.V. (Scandinavia) Fjellievagen 8, SE-22736 Lund, Sweden	Tel : +46-8-625-10-00 Fax : +46-46-39-70-18
Turkey	Mitsubishi Electric Turkey A.S. Umraniye Branch Serifali Mahallesi Nutuk Sokak No:5, TR-34775 Umraniye / Istanbul, Turkey	Tel : +90-216-526-3990 Fax : +90-216-526-3995
UAE	Mitsubishi Electric Europe B.V. Dubai Branch Dubai Silicon Oasis, P.O.BOX 341241, Dubai, U.A.E.	Tel : +971-4-3724716 Fax : +971-4-3724721
South Africa	Adroit Technologies 20 Waterford Office Park, 189 Witkoppen Road, Fourways, South Africa	Tel : +27-11-658-8100 Fax : +27-11-658-8101
China	Mitsubishi Electric Automation (China) Ltd. Mitsubishi Electric Automation Center, No.1386 Hongqiao Road, Shanghai, China	Tel : +86-21-2322-3030 Fax : +86-21-2322-3000
Taiwan	SETSUYO ENTERPRISE CO., LTD. 6F, No.105, Wugong 3rd Road, Wugu District, New Taipei City 24889, Taiwan	Tel : +886-2-2299-2499 Fax : +886-2-2299-2509
Korea	Mitsubishi Electric Automation Korea Co., Ltd. 7F-9F, Gangseo Hangang Xi-tower A, 401, Yangcheon-ro, Gangseo-Gu, Seoul 07528, Korea	Tel : +82-2-3660-9510 Fax : +82-2-3664-8372/8335
Singapore	Mitsubishi Electric Asia Pte. Ltd. 307 Alexandra Road, Mitsubishi Electric Building, Singapore 159943	Tel : +65-6473-2308 Fax : +65-6476-7439
Thailand	Mitsubishi Electric Factory Automation (Thailand) Co., Ltd. 12th Floor, SV.City Building, Office Tower 1, No. 896/19 and 20 Rama 3 Road, Kwaeng Bangpongpan, Khet Yannawa, Bangkok 10120, Thailand	Tel : +66-2682-6522 to 6531 Fax : +66-2682-6020
Indonesia	PT. Mitsubishi Electric Indonesia Gedung Jaya 11th Floor, JL. MH. Thamrin No.12, Jakarta Pusat 10340, Indonesia	Tel : +62-21-3192-6461 Fax : +62-21-3192-3942
Vietnam	Mitsubishi Electric Vietnam Company Limited Unit 01-04, 10th Floor, Vincom Center, 72 Le Thanh Ton Street, District 1, Ho Chi Minh City, Vietnam	Tel : +84-8-3910-5945 Fax : +84-8-3910-5947
India	Mitsubishi Electric India Pvt. Ltd. Pune Branch Emerald House, EL-3, J Block, M.I.D.C., Bhosari, Pune - 411026, Maharashtra, India	Tel : +91-20-2710-2000 Fax : +91-20-2710-2100
Australia	Mitsubishi Electric Australia Pty. Ltd. 348 Victoria Road, P.O. Box 11, Rydalmere, N.S.W 2116, Australia	Tel : +61-2-9684-7777 Fax : +61-2-9684-7245

Mitsubishi Electric Corporation Nagoya Works is a factory certified for ISO 14001 (standards for environmental management systems) and ISO 9001 (standards for quality assurance management systems).



MITSUBISHI ELECTRIC CORPORATION

HEAD OFFICE: TOKYO BUILDING, 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN
NAGOYA WORKS: 1-14, YADA-MINAMI 5, HIGASHI-KU, NAGOYA, JAPAN